
# PHYSICAL SCIENCE

## From Fundamental Principles to Modern Applications



$$E = mc^2$$

$$\nabla \cdot \mathbf{E} = \frac{\rho}{\varepsilon_0}$$

$$i\hbar \frac{\partial \psi}{\partial t} = \hat{H}\psi$$


**Editors**

**Ms. Rutuja Ashok Bhosale**
**Ms. Monika Shyamkumarji Dixit**
**Ms. Tahenishjahan Kalim Mujawar**
**Dr. Ponmani Swaminathan**



Nature Light Publications

*An International Edited Book* *ISBN-978-81-69492-07-2*

# Physical Science: From Fundamental Principles to Modern Applications

***Editors***

**Ms. Rutuja Ashok Bhosale**
Assistant Professor
Department of Physics
Eknath Sitaram Divekar Mahavidyalaya, Varvand,
Tal- Daund, Dist- Pune, (MH), India.

**Ms. Monika Dixit**
Assistant Professor
Department of Physics
Jagadamba Mahavidyalaya, Achalpur., (MH), India.

**Ms. Mujawar Tahenishjahan Kalim**
Assistant Professor
Department of Physics
New Arts, Commerce and Science college, Parner,
Dist.- Ahilyanagar, (MH), India.

**Dr. Ponmani Swaminathan**
Associate Professor and Head
Department of Petroleum Engineering,
AMET University, Chennai, Tamil Nadu, India.

***Published By***

***Nature Light Publications, Pune***

© Reserved by Editor's

# Physical Science: From Fundamental Principles to Modern Applications

*Editors*

**Ms. Rutuja Ashok Bhosale**
**Ms. Monika Dixit**
**Ms. Mujawar Tahenishjahan Kalim**
**Dr. Ponmani Swaminathan**

**First Edition: July, 2026**

**An International Edited Book**

**ISBN- 978-81-69492-07-2**

**Published by:**
***Nature Light Publications, Pune***
309 West 11, Manjari VSI Road, Manjari Bk.,
Haveli, Pune- 412 307.
Website: www.naturelightpublications.com
Email: naturelightpublications@gmail.com
Contact No: +91 9822489040 / 9922489040

*The editors/Associate editors/publisher shall not be responsible for originality and thought expressed in the book chapter/ article. The author shall be solely held responsible for the originality and thoughts expressed in their book chapter or article.*

# *Preface*

*Physical Science: From Fundamental Principles to Modern Applications is an edited volume that brings together important areas of physical science and their applications in contemporary research and technology. The book highlights the connection between fundamental scientific principles and their practical use in fields such as energy, nanotechnology, transportation, biological systems, sensors, and advanced materials.*

*The chapter "Thermodynamics of Biological Systems: Energy Flow from Molecules to Ecosystems" explores the principles of thermodynamics in biological systems and explains energy transfer from molecules to ecosystems. The chapters on the Akbari–Ganji Method present analytical solutions for nonlinear ship roll motion and reaction kinetics in packed catalytic pellets, demonstrating the application of mathematical techniques to complex physical and engineering problems.*

*Modern energy applications are discussed through chapters on nanomaterials in energy conversion and storage devices and the physical principles of electric vehicles and battery management systems. These contributions emphasize the importance of advanced materials, energy storage, battery technologies, and intelligent mobility in developing sustainable energy solutions.*

*The volume also includes research on green synthesis of gold nanoparticles using plant extracts, highlighting environmentally friendly approaches to nanotechnology and their biological applications. The chapter on sensors and smart detection systems focuses on the growing importance of sensing technologies in monitoring, detection, automation, and intelligent systems.*

*The final contribution, "Thin Films and Coating Technologies," discusses fundamental principles, processing methods, characterization, applications, reliability, and future perspectives of thin-film and coating*

*technologies. It reflects the significance of advanced materials and surface engineering in modern scientific and industrial applications.*

*Collectively, the chapters demonstrate the broad and interdisciplinary nature of physical science. They show how fundamental concepts can be developed into innovative technologies and practical solutions for contemporary challenges. The book is intended to serve as a useful reference for students, researchers, academicians, and professionals interested in physical science and its emerging applications.*

*The editors hope that this volume will contribute to the advancement of scientific knowledge, encourage interdisciplinary research, and inspire further exploration of innovative applications of physical science for a sustainable and technologically advanced future.*

***Editors***

# Physical Science: From Fundamental Principles to Modern Applications

## *Table of Content*


| Sl. No. | Title and Authors | Page No. |
|---|---|---|
| 1 | **Thermodynamics of Biological Systems: Energy Flow from Molecules to Ecosystems**<br>*Ranjana* | 01 - 13 |
| 2 | **Analytical Solution of the Nonlinear Forced Ship Roll Motion Equation Using the Akbari–Ganji Method**<br>*K. Nirmala* | 14 - 19 |
| 3 | **Analytical Solution of Reaction Kinetics in Packed Catalytic Pellets of Fixed-Bed Reactors Using the Akbari–Ganji Method**<br>*P. Jeyabarathi, L. Rajendrana, R. Saravanakumar* | 20 - 31 |
| 4 | **Nanomaterials in Energy Conversion and Storage Devices**<br>*Manish Kumar, Ajeet Singh, Garima Chauhan, Narender Singh, Bal Krishna Yadav, Vidhi Goyal* | 32 - 40 |
| 5 | **Physical Principles of Electric Vehicles and Battery Management Systems: From Energy Storage to Intelligent Mobility**<br>*R. Deivanayaki, Dr. S. Muthurajan, Dr. Arul Kulandaivel* | 41 - 52 |
| 6 | **Physical Science: From Fundamental Principles to Modern Applications**<br>*Dr. G. D. Jemi* | 53 - 57 |
| 7 | **Green Synthesis, Characterization and Biological Studied of Gold Nanoparticles from Various Plant Extracts**<br>*D.T. Sakhare* | 58 - 76 |
| 8 | **Sensors and Smart Detection Systems**<br>*Aswini M, S. Muthurajan* | 77 - 88 |
| 9 | **Thin Films and Coating Technologies: Fundamentals, Processing Methods, Characterization, Applications, Reliability, Performance, and Future Perspectives**<br>*Prathamesh B. Dahivade, Balkrishna J Lokhande* | 89 - 99 |

Physical Science: From Fundamental Principles to Modern Applications
ISBN: 978-81-69492-07-2| Year: 2026 | pp: 01 - 13

# Thermodynamics of Biological Systems: Energy Flow from Molecules to Ecosystems

**Ranjana**

Department of Zoology, Patna Science College, Patna University, Patna, Bihar, 800005, India

**Email:** ranjana.prakash81@gmail.com

Article DOI Link: https://zenodo.org/uploads/22046779

DOI: 10.5281/zenodo.22046779

## Introduction

### Life as a Thermodynamic System

Life, at its most fundamental level, is a thermodynamic phenomenon. Every biochemical reaction, every muscular contraction, every photon captured by a leaf chloroplast, and every predator-prey interaction in a savanna is governed by the universal laws of thermodynamics. Understanding how biological systems acquire, transform, store, and dissipate energy is central to fields as diverse as cell biology, ecology, physiology, and evolutionary biology. This chapter presents an integrated account of biological energy flow, from the quantum-level events of photosynthetic light harvesting through the coupled enzymatic reactions of cellular metabolism to the grand-scale energy budgets of global ecosystems (1,2).

Living organisms are quintessential open systems: they continuously exchange both matter and energy with their environment. Unlike closed systems that evolve toward thermodynamic equilibrium, biological systems maintain a state of dynamic non-equilibrium — often called a steady state — by coupling energy-releasing (exergonic) reactions to energy-requiring (endergonic) processes (3). The currency that mediates virtually all such coupling in cells is adenosine triphosphate (ATP), a molecule whose hydrolysis releases approximately 30.5 kJ/mol under standard conditions and up to 50–60 kJ/mol under typical cellular concentrations (4).

The thermodynamic framework that best describes biological transformations is that of Josiah Willard Gibbs, whose formulation of free energy (G) elegantly combines the enthalpic and entropic contributions to spontaneity. A process is thermodynamically spontaneous when $\Delta G < 0$, meaning the system releases free energy to the surroundings. The Second Law of Thermodynamics guarantees that the total entropy of the universe increases in every real process, a principle that has

profound implications for the efficiency of biological energy transduction and the ecological structure of biotic communities (5).

## Thermodynamic Laws and Their Biological Manifestations

### 1. The First Law: Energy Conservation in Metabolism

The First Law of Thermodynamics states that energy can neither be created nor destroyed, only converted from one form to another. In biological contexts, this principle dictates the energy balance of every organism: the chemical energy ingested or synthesised must equal the sum of heat lost, work performed, and energy stored. For a heterotrophic organism: $\text{Energy in} = \text{Heat released} + \text{Work done} + \Delta\text{Energy stored}$. Metabolic rate measurements using direct and indirect calorimetry confirm this balance with remarkable precision (6).

Hess's Law, a direct corollary of the First Law, enables biochemists to calculate the overall enthalpy change ($\Delta H$) of metabolic pathways by summing the enthalpies of individual steps, regardless of pathway. The complete oxidation of glucose to carbon dioxide and water releases 2,803 kJ/mol — energy that is partially captured as ATP and partially dissipated as heat, maintaining mammalian core body temperature (7).

### 2. The Second Law: Entropy and Biological Order

The Second Law introduces the concept of entropy (S), a measure of the dispersal of energy and matter. It states that in any spontaneous process, the total entropy of the universe increases ($\Delta S_{\text{universe}} > 0$). Biological systems appear to violate this principle at first glance: a developing embryo, a growing plant, or a protein folding into its native conformation all represent dramatic increases in local order. However, these decreases in local entropy are always accompanied by greater entropy increases in the surrounding environment, principally through heat dissipation (8).

Erwin Schrödinger famously described living organisms as systems that "feed on negative entropy" — they absorb low-entropy energy (photons or chemical bonds) and export high-entropy energy (heat and carbon dioxide) to maintain their organisational complexity (9). The Gibbs free energy equation, $\Delta G = \Delta H - T\Delta S$, quantifies the maximum useful work extractable from a process at constant temperature and pressure, integrating both energy and entropy considerations into a single, biologically actionable parameter.

### 3. Key Thermodynamic Parameters in Biology

Table 1 summarises the principal thermodynamic quantities relevant to biological energy transformations, with representative values drawn from well-characterised systems (4,10).

*Table 1. Key Thermodynamic Parameters in Biological Systems*

| Parameter | Symbol / Unit | Typical Biological Value | Biological Significance |
|---|---|---|---|
| Gibbs Free Energy Change | ΔG (kJ/mol) | ATP hydrolysis: −30.5 kJ/mol | Determines spontaneity; drives biosynthesis |
| Enthalpy Change | ΔH (kJ/mol) | Glucose oxidation: −2803 kJ/mol | Heat released or absorbed in metabolic reactions |
| Entropy Change | ΔS (J/mol·K) | Protein folding: −50 to −400 J/mol·K | Reflects molecular disorder; key in folding, assembly |
| Proton Motive Force | Δp (mV) | ∼−180 to −220 mV (mitochondria) | Drives ATP synthesis via chemiosmosis |
| Standard Reduction Potential | E°′ (V) | $NAD^+$/NADH: −0.32 V; $O_2$/$H_2O$: +0.82 V | Determines direction of electron transfer in ETC |
| Metabolic Efficiency | η (%) | Aerobic respiration: ~38–40% | Proportion of chemical energy conserved as ATP |

*ETC: Electron Transport Chain; GTP: Guanosine triphosphate; ΔΨ: membrane potential.*

## Cellular Energy Transduction: From Glucose to ATP

### 1. Glycolysis: The Universal Anaerobic Pathway

Glycolysis, the ten-step enzymatic conversion of glucose to pyruvate, is evolutionarily the most ancient energy-harvesting pathway, occurring in the cytoplasm of virtually every living cell. Despite its antiquity and universality, glycolysis exhibits sophisticated thermodynamic regulation. The pathway has an overall standard free energy change of −96 kJ/mol, but this is unevenly distributed across its steps. Three reactions — catalysed by hexokinase ($\Delta G^{\circ\prime} = -16.7$ kJ/mol), phosphofructokinase-1 (PFK-1; $\Delta G^{\circ\prime} = -21.4$ kJ/mol), and pyruvate kinase ($\Delta G^{\circ\prime} = -31.4$ kJ/mol) — are strongly exergonic under cellular conditions, rendering them physiologically irreversible and serving as key regulatory control points (11).

Figure 3 illustrates the cumulative free energy profile of glycolysis, highlighting these irreversible steps and the overall thermodynamic driving force of the pathway. The net yield of glycolysis is 2 mol of ATP, 2 mol of NADH, and 2 mol of pyruvate per mole of glucose. Under anaerobic conditions, pyruvate is reduced to lactate (in animals) or ethanol (in yeast), regenerating NAD+ to sustain glycolytic flux — a thermodynamic necessity when mitochondrial reoxidation of NADH is unavailable (12).





*Figure 1. Cumulative standard free energy profile (ΔG°') along the ten steps of glycolysis. Red dots indicate physiologically irreversible reactions (hexokinase, PFK-1, pyruvate kinase) that serve as metabolic regulatory points. Note the large drops in free energy at steps 1, 3, and 10. PGI: phosphoglucose isomerase; TPI: triose phosphate isomerase; PGK: phosphoglycerate kinase; PGM: phosphoglycerate mutase; PK: pyruvate kinase*.

## 2. The Tricarboxylic Acid Cycle and Oxidative Decarboxylation

Pyruvate generated by glycolysis is transported into the mitochondrial matrix where it undergoes oxidative decarboxylation by the pyruvate dehydrogenase complex (PDC), yielding acetyl-CoA ($\Delta G^{\circ\prime} = -33.4$ kJ/mol per pyruvate). The PDC is a massive multi-enzyme complex (MW ~9.5 MDa in mammals) that couples decarboxylation, oxidation, and acyl transfer through a sophisticated lipoic acid shuttle mechanism — a remarkable example of channelling substrates between active sites to minimise thermodynamic losses (13).

The tricarboxylic acid (TCA) cycle, also known as the Krebs or citric acid cycle, then oxidises acetyl-CoA through eight enzymatic steps, releasing two molecules of $CO_2$ and generating 3 NADH, 1 $FADH_2$, and 1 GTP per turn. Critically, the TCA cycle does not directly synthesise large quantities of ATP; rather, it functions primarily as an electron-harvesting machine, loading high-energy electrons onto the electron carriers NADH and $FADH_2$ for subsequent oxidative phosphorylation (14). The overall standard free energy change of the complete cycle is −60 kJ/mol of acetyl-CoA oxidised.

## 3. Oxidative Phosphorylation and Chemiosmosis

The most thermodynamically productive stage of aerobic respiration is oxidative phosphorylation, occurring across the inner mitochondrial membrane. The chemiosmotic theory, first proposed by Peter Mitchell in 1961 and for which he was awarded the Nobel Prize in Chemistry in 1978, posits that electron transfer through the respiratory chain (Complexes I–IV) is coupled to the vectorial pumping of protons from the matrix to the intermembrane space, creating an electrochemical

proton gradient — the proton motive force (PMF, Δp) — that drives ATP synthesis (15).

The PMF has two components: a membrane potential (ΔΨ, typically −150 to −180 mV) and a pH gradient (ΔpH, ~0.5–1.0 units), related by $\Delta p = \Delta\Psi - (2.303RT/F)\Delta pH$. Under physiological conditions, Δp ≈ −200 mV, providing approximately 19 kJ/mol of free energy per proton. The $F_1F_o$-ATP synthase harnesses this energy to phosphorylate ADP, with approximately 2.5 protons required per ATP synthesised from NADH and 1.5 from $FADH_2$ (accounting for the proton cost of Pi and ADP/ATP transport) (16).





*Figure 2. Schematic of the electron transport chain (ETC) and ATP synthesis by chemiosmosis in the inner mitochondrial membrane. Complexes I–IV pump protons into the intermembrane space (high $H^+$), generating the proton motive force. The $F_1F_o$-ATP synthase (Complex V) uses the downhill flow of protons back into the matrix to drive ATP synthesis. CoQ: Coenzyme Q (ubiquinone); Cyt c: Cytochrome c.*

## 4. Comparative ATP Yields and Metabolic Efficiency

Modern estimates, revised from earlier textbook values in light of the P/O ratios determined by isolated mitochondrial studies and the stoichiometry of the ATP synthase c-ring, place the net ATP yield of complete glucose oxidation at 30–32 mol ATP per mol glucose — significantly lower than the classical textbook figure of 36–38 (17). The thermodynamic efficiency of this process, defined as the ratio of free energy captured as ATP to the total free energy available from glucose oxidation, is approximately 38–40% — remarkably high compared to most human-engineered energy conversion devices.

Table 2 provides a comparative overview of ATP yields and key characteristics of major metabolic pathways, illustrating the dramatic thermodynamic advantages of aerobic over anaerobic catabolism, and of lipid over carbohydrate oxidation on a per-gram basis (18).

*Table 2. Comparative ATP Yields of Major Catabolic Pathways*

| **Metabolic Pathway** | **Location** | **Substrate** | **Net ATP Yield** | **$O_2$ Required?** |
|---|---|---|---|---|
| Glycolysis | Cytoplasm | Glucose | 2 ATP (net) | No |
| Pyruvate Oxidation | Mitochondrial matrix | Pyruvate (×2) | 0 ATP (2 NADH) | Yes |
| Krebs / TCA Cycle | Mitochondrial matrix | Acetyl-CoA (×2) | 2 GTP, 6 NADH, 2 $FADH_2$ | Yes |
| Oxidative Phosphorylation (ETC) | Inner mitoch. membrane | NADH, $FADH_2$ | ~28–32 ATP | Yes |
| **Total Aerobic Respiration** | Integrated | 1 Glucose | **~30–32 ATP** | Yes |
| Anaerobic Fermentation (lactic acid) | Cytoplasm | Glucose | 2 ATP (net) | No |
| Beta-Oxidation (palmitate) | Mitochondrial matrix | Palmitate (C16) | ~106 ATP (net) | Yes |

*GTP: guanosine triphosphate (energetically equivalent to ATP); ETC: electron transport chain; revised P/O ratios used.*

## Photosynthesis: Thermodynamics of Solar Energy Capture

### 1. Light Harvesting and the Quantum Biology of Photosystems

Photosynthesis is arguably the most thermodynamically significant biological process on Earth, annually fixing approximately 120 Pg (petagrams) of carbon and capturing ~2.5 × $10^{2'}$ J of solar energy — more than human civilisation currently consumes in a year (19). The process begins with the absorption of photons by antenna pigment complexes — intricate arrays of chlorophyll and accessory pigments embedded in the thylakoid membrane — which funnel excitation energy towards the photosynthetic reaction centres with near-unity quantum efficiency.

In oxygenic photosynthesis, the two photosystems (PS II and PS I) operate in series (the "Z-scheme"). PS II absorbs photons at 680 nm (energy ≈ 176 kJ per einstein), using this energy to drive the thermodynamically unfavourable oxidation of water ($E^{\circ'}$ = +0.82 V), extracting electrons and releasing $O_2$ as a by-product. These electrons are then energised further by PS I (absorbing at 700 nm) and used to reduce NADP+ to NADPH (20). The overall light-dependent reactions can be summarised as: $2H_2O + 2NADP^+ + \sim 8$ photons $\rightarrow O_2 + 2NADPH + 2H^+$, with a standard free energy requirement of +438 kJ/mol.

### 2. Carbon Fixation: Thermodynamics of the Calvin–Benson Cycle

The light-independent reactions of photosynthesis (the Calvin–Benson–Bassham cycle) use the ATP and NADPH generated by the light reactions to fix atmospheric $CO_2$ into triose phosphates — the precursors of glucose and other organic compounds. The initial carboxylation step, catalysed by ribulose-1,5-bisphosphate carboxylase/oxygenase (RuBisCO), is strongly exergonic ($\Delta G^{\circ\prime} = -35.1$ kJ/mol), ensuring irreversibility and thermodynamic commitment to carbon fixation (21).

The overall thermodynamic balance of C3 photosynthesis requires 3 ATP and 2 NADPH per $CO_2$ fixed. The maximum theoretical efficiency of solar energy conversion by photosynthesis is approximately 11% for C3 plants and up to 6% for whole-plant productivity, with actual field efficiencies of most crops falling between 0.5% and 2% due to photorespiration, light saturation, and other limiting factors (22). C4 and CAM plants have evolved biochemical $CO_2$-concentrating mechanisms that suppress photorespiration, improving thermodynamic efficiency in hot, arid environments at the cost of additional ATP expenditure.

## Ecosystem Thermodynamics: Energy Flow from Producers to Decomposers

### 1. Primary Productivity and Energy Entry into Ecosystems

At the ecosystem scale, thermodynamic principles govern the quantity and quality of energy available to biological communities. Gross primary productivity (GPP) represents the total rate of photosynthetic carbon fixation; net primary productivity (NPP) is the energy remaining after autotrophic respiration ($R_a$) is subtracted: $NPP = GPP - R_a$. NPP constitutes the energy base for all heterotrophic organisms in an ecosystem and is itself strongly constrained by thermodynamic factors including temperature, water availability, nutrient supply, and light interception geometry (23).

Global NPP is estimated at approximately 120 Pg C/yr for terrestrial ecosystems and 50 Pg C/yr for marine ecosystems, with substantial spatial variation reflecting differences in solar irradiance, water availability, and nutrient inputs (24). Table 4.3 compares the energy budgets of major ecosystem types, illustrating how thermodynamic constraints shape productivity across biomes.

***Table 3. Comparative Energy Budgets of Major Ecosystem Types***

| Ecosystem Type | GPP (g C/m²/yr) | NPP (g C/m²/yr) | R/GPP Ratio | Dominant Energy Source |
|---|---|---|---|---|
| Tropical Rainforest | 3,300 | 1,800 | 0.45 | Solar (high canopy irradiance) |
| Temperate Deciduous Forest | 1,200 | 600 | 0.50 | Solar (seasonal) |
| Open Ocean | 500 | 140 | 0.72 | Solar |

| | | | | |
|---|---|---|---|---|
| | | | | (phytoplankton) |
| Coral Reef | 5,000 | 2,500 | 0.50 | Solar (zooxanthellae symbiosis) |
| Tundra | 140 | 60 | 0.57 | Solar (limited growing season) |
| Deep-Sea Hydrothermal Vent | ~5–20 | ~3–12 | 0.40 | Chemical ($H_2S$ oxidation — chemolithotrophy) |
| Agricultural Cropland (wheat) | 1,400 | 560 | 0.60 | Solar (managed, subsidized) |

*GPP: Gross Primary Productivity; NPP: Net Primary Productivity; R/GPP: autotrophic respiration ratio. Values are approximate means from global synthesis studies.*

## 2. Trophic Energy Transfer and the Ten Percent Rule

Energy flow through trophic levels is profoundly inefficient, a direct consequence of the Second Law. At each trophic transfer, typically only 5–20% of the energy stored in prey biomass is incorporated into predator biomass — the remainder is lost as heat through respiration, excreted as metabolic waste, or rendered unavailable in indigestible tissues. Lindeman's classic ecological efficiency ratio (subsequently refined to the "ten percent rule") codifies this observation: approximately 10% of energy is transferred between successive trophic levels on average (25).





*Figure 3. Ecological energy pyramid illustrating trophic energy flow. Approximate energy content (kcal/m²/yr) is shown at each level. The 10% trophic efficiency rule means ~90% of energy is dissipated as heat at each transfer. Decomposers receive inputs from all trophic levels. NPP: Net Primary Productivity.*

This thermodynamic constraint has fundamental consequences for ecosystem structure and function. It limits the number of viable trophic levels to approximately four or five (since energy diminishes by ~90% at each level, the energy available to a fifth-order consumer is approximately 0.001% of NPP), explains why large carnivores are necessarily rare relative to herbivores, and has direct implications for human nutrition and agriculture — consuming plant-based foods is thermodynamically approximately ten times more energy-efficient than consuming animal-based foods at the same trophic position (26).

### 3. Decomposers and the Completion of Energy Dissipation

Decomposers — principally bacteria and fungi — play a thermodynamically indispensable role in ecosystems by catalysing the final oxidation of organic detritus to inorganic forms, recovering approximately 80–95% of NPP that bypasses grazing food chains as dead organic matter. Decomposition rates are themselves thermodynamically regulated: the metabolic rate of microbial decomposers follows Arrhenius kinetics with a $Q_{10}$ of approximately 2–3, meaning decomposition roughly doubles for every 10°C rise in temperature (27). This temperature sensitivity has major implications for soil carbon storage and the global carbon cycle under climate warming scenarios.

The concept of ecosystem "energy balance" or "energy budget" integrates all these flows: solar inputs are balanced by NPP, trophic transfers, and ultimately total ecosystem respiration (TER), which returns virtually all captured solar energy to the environment as heat. In climax ecosystems at steady state, GPP ≈ TER, with net ecosystem productivity (NEP = NPP − heterotrophic respiration) approaching zero (28).

## Non-Equilibrium Thermodynamics and Biological Organisation

### 1. Dissipative Structures in Biology

Ilya Prigogine's theory of dissipative structures, for which he was awarded the Nobel Prize in Chemistry in 1977, provides a thermodynamic framework for understanding how biological order can self-organise and be maintained far from equilibrium (29). Dissipative structures are spatiotemporal patterns that arise spontaneously in open systems driven by sustained energy and matter flows, increasing local order at the cost of greater entropy production in their surroundings. Biological examples range from the oscillatory dynamics of glycolysis and circadian rhythms to the morphogenetic patterns of embryonic development and the self-organisation of ecosystems.

A key insight from non-equilibrium thermodynamics is that living systems are not merely energy transducers but entropy-producing engines operating at maximum efficiency consistent with kinetic constraints. Lotka's principle of maximum energy flux and Odum's maximum power principle both propose that biological systems

evolve to maximise energy throughput rather than efficiency per se — a thermodynamic perspective that reconciles the coexistence of metabolic inefficiency with evolutionary optimisation (30).

### 2. Entropy Production and Metabolic Rate Scaling

One of the most striking quantitative regularities in biology is the allometric scaling of metabolic rate with body mass: basal metabolic rate (BMR) $\propto M^{3/4}$, where M is body mass. This three-quarter power law (Kleiber's law), empirically robust across organisms spanning 27 orders of magnitude in body mass — from unicellular microbes to blue whales — reflects fundamental thermodynamic and transport constraints on energy delivery to cells (31). The West–Brown–Enquist model explains this scaling as a consequence of fractal-like, space-filling transport networks (cardiovascular, respiratory) optimised to minimise entropy production during energy distribution.

Entropy production rates, calculated from oxygen consumption and carbon dioxide evolution (respiratory quotient analysis), are remarkably consistent across taxonomic groups when normalised per unit biomass: approximately 1–10 mW/g in homeotherms and 0.01–1 mW/g in poikilotherms at equivalent temperatures. This convergence suggests deep thermodynamic constraints on the architecture of metabolic networks that transcend phylogenetic boundaries (32).

## Applied Biological Thermodynamics: Medicine, Biotechnology and Climate

### 1. Thermodynamic Perspectives in Medicine

The thermodynamic framework has numerous clinical applications. Cancer metabolism, characterised by the Warburg effect — preferential reliance on aerobic glycolysis even in the presence of abundant oxygen — represents a thermodynamic rewiring of cellular energy metabolism that confers proliferative advantages including biosynthetic precursor supply and redox balance, at the cost of ATP efficiency (33). Targeting this altered thermodynamic landscape is a major strategy in cancer metabolomics.

Mitochondrial diseases, involving dysfunction of the electron transport chain or ATP synthase, manifest clinically as energy deficiency syndromes particularly affecting high-energy-demand tissues (brain, heart, skeletal muscle). Thermodynamic analysis of isolated mitochondria from patient biopsies — measuring respiratory control ratios, ADP/O ratios, and membrane potential — has become a valuable diagnostic tool (34). Similarly, the thermodynamics of protein folding and aggregation is central to understanding and treating conformational diseases such as Alzheimer's disease, Parkinson's disease, and type II diabetes, where pathological protein aggregation represents a thermodynamically metastable state.

## 2. Bioenergetics in the Context of Global Climate Change

The thermodynamics of biological energy flow is inextricably linked to global biogeochemical cycles and climate dynamics. Terrestrial ecosystems currently act as net carbon sinks, absorbing approximately 3.1 Pg C/yr, partially offsetting anthropogenic emissions of ~10.9 Pg C/yr from fossil fuel combustion and land-use change (35). However, temperature-dependent increases in ecosystem respiration may erode or reverse this sink function under projected warming scenarios, as the $Q_{10}$ of heterotrophic respiration exceeds that of photosynthesis.

The thermodynamic efficiency of agricultural systems is a growing concern in the context of food security and sustainability. The energy return on investment (EROI) of conventional agriculture — the ratio of food energy output to fossil fuel energy input — has declined from approximately 10–1 in pre-industrial agriculture to below 1–1 in some modern intensive systems, meaning more energy is expended producing food than the food contains (36). Improving agricultural EROI through reduced fossil fuel inputs, precision fermentation, and optimised crop photosynthesis is a central challenge of the coming decades.

## Summary and Conclusions

This chapter has traced the thermodynamics of biological systems across scales spanning twelve orders of magnitude, from the subnanometre events of electron transfer in the respiratory chain to the continental-scale fluxes of ecosystem carbon and energy. The unifying theme is the operation of the Second Law: energy flows from concentrated, low-entropy sources (sunlight, chemical bonds) through the ordered structures of living organisms, inevitably degrading to dispersed heat. Life is best understood as a thermodynamically sustained, self-organising system that maintains order by coupling its internal reactions to the large potential gradients available in the chemical and electromagnetic environment.

Key conclusions from this analysis include: (i) ATP is the universal energy currency that couples exergonic and endergonic reactions, operating at thermodynamic efficiencies of 38–40% in aerobic respiration; (ii) chemiosmosis and the proton motive force represent an elegant thermodynamic machine that converts redox energy into phosphodiester bond synthesis; (iii) photosynthesis captures approximately 1–2% of incident solar radiation into organic matter under field conditions, limited by thermodynamic and kinetic constraints; (iv) the 10% trophic transfer efficiency emerges inevitably from the Second Law and fundamentally shapes ecosystem structure; and (v) non-equilibrium thermodynamics provides a rigorous framework for understanding biological self-organisation and metabolic scaling.

The thermodynamic perspective on biology is not merely conceptual: it has direct practical implications for medicine, biotechnology, agricultural sustainability, and climate policy. As our ability to manipulate biological systems advances through

synthetic biology and metabolic engineering, thermodynamic principles will remain the inviolable constraints within which all biological innovations must operate.

***References***


1. Nicholls DG, Ferguson SJ. Bioenergetics 4. 4th ed. London: Academic Press; 2013.
2. Harold FM. The Way of the Cell: Molecules, Organisms and the Order of Life. Oxford: Oxford University Press; 2001.
3. Prigogine I, Stengers I. Order Out of Chaos: Man's New Dialogue with Nature. New York: Bantam Books; 1984.
4. Lehninger AL, Nelson DL, Cox MM. Lehninger Principles of Biochemistry. 8th ed. New York: W.H. Freeman; 2021.
5. Atkins PW, de Paula J, Keeler J. Physical Chemistry. 11th ed. Oxford: Oxford University Press; 2018.
6. Lusk G. The Elements of the Science of Nutrition. 4th ed. Philadelphia: W.B. Saunders; 1928.
7. Stryer L, Berg JM, Tymoczko JL, Gatto GJ. Biochemistry. 9th ed. New York: W.H. Freeman; 2019.
8. Boltzmann L. Lectures on Gas Theory. Berkeley: University of California Press; 1964.
9. Schrödinger E. What is Life? The Physical Aspect of the Living Cell. Cambridge: Cambridge University Press; 1944.
10. Berg JM, Tymoczko JL, Stryer L. Thermodynamics of biochemical reactions. Biochemistry. 2002;5th ed:Chapter 14.
11. Fersht A. Structure and Mechanism in Protein Science: A Guide to Enzyme Catalysis and Protein Folding. New York: W.H. Freeman; 1999.
12. Voet D, Voet JG. Biochemistry. 4th ed. Hoboken: John Wiley & Sons; 2011.
13. Perham RN. Swinging arms and swinging domains in multifunctional enzymes. Annu Rev Biochem. 2000; 69:961-1004.
14. Krebs HA, Johnson WA. The role of citric acid in intermediate metabolism in animal tissues. Enzymologia. 1937; 4:148-56.
15. Mitchell P. Coupling of phosphorylation to electron and hydrogen transfer by a chemi-osmotic type of mechanism. Nature. 1961;191(4784):144-8.
16. Walker JE. ATP synthesis by rotary catalysis. Angew Chem Int Ed. 1998;37(17):2308-19.
17. Hinkle PC. P/O ratios of mitochondrial oxidative phosphorylation. Biochim Biophys Acta. 2005;1706(1-2):1-11.
18. Brand MD, Nicholls DG. Assessing mitochondrial dysfunction in cells. Biochem J. 2011;435(2):297-312.
19. Field CB, Behrenfeld MJ, Randerson JT, Falkowski P. Primary production of the biosphere. Science. 1998;281(5374):237-40.

20. Blankenship RE. Molecular Mechanisms of Photosynthesis. 2nd ed. Oxford: Wiley-Blackwell; 2014.
21. Andersson I, Backlund A. Structure and function of Rubisco. Plant Physiol Biochem. 2008;46(3):275-91.
22. Zhu XG, Long SP, Ort DR. What is the maximum efficiency with which photosynthesis can convert solar energy into biomass? Curr Opin Biotechnol. 2008;19(2):153-9.
23. Chapin FS III, Matson PA, Vitousek PM. Principles of Terrestrial Ecosystem Ecology. 2nd ed. New York: Springer; 2011.
24. Beer C, Reichstein M, Tomelleri E, et al. Terrestrial gross carbon dioxide uptake: global distribution and covariation with climate. Science. 2010;329(5993):834-8.
25. Lindeman RL. The trophic-dynamic aspect of ecology. Ecology. 1942;23(4):399-417.
26. Odum EP. Fundamentals of Ecology. 3rd ed. Philadelphia: Saunders; 1971.
27. Davidson EA, Janssens IA. Temperature sensitivity of soil carbon decomposition and feedbacks to climate change. Nature. 2006;440(7081):165-73.
28. Baldocchi D. Measuring and modelling carbon dioxide and water vapour exchange over a temperate broad-leaved forest during the 1995 summer drought. Plant Cell Environ. 1997;20(9):1108-22.
29. Prigogine I. Time, structure and fluctuations. Science. 1978;201(4358):777-85.
30. Lotka AJ. Contribution to the energetics of evolution. Proc Natl Acad Sci USA. 1922;8(6):147-51.
31. West GB, Brown JH, Enquist BJ. A general model for the origin of allometric scaling laws in biology. Science. 1997;276(5309):122-6.
32. Demetrius L, Tuszynski JA. Quantum metabolism explains the allometric scaling of metabolic rates. J R Soc Interface. 2010;7(44):507-14.
33. Warburg O. On the origin of cancer cells. Science. 1956;123(3191):309-14.
34. Nunnari J, Suomalainen A. Mitochondria: in sickness and in health. Cell. 2012;148(6):1145-59.
35. Friedlingstein P, Jones MW, O'Sullivan M, et al. Global Carbon Budget 2023. Earth Syst Sci Data. 2023;15(12):5301-69.
36. Pimentel D, Pimentel M. Sustainability of meat-based and plant-based diets and the environment. Am J Clin Nutr. 2003;78(3 Suppl):660S-663S.

**Physical Science: From Fundamental Principles to Modern Applications**
**ISBN: 978-81-69492-07-2 | Year: 2026 | pp: 14 - 19**

# Analytical Solution of the Nonlinear Forced Ship Roll Motion Equation Using the Akbari–Ganji Method

**K. Nirmala**

Department of Mathematics, Rajalakshmi Engineering College, Thandalam,

Chennai-602105

**Email:** nirmala.k@rajalakshmi.edu.in

Article DOI Link: https://zenodo.org/uploads/22044700

DOI: 10.5281/zenodo.22044700

**Abstract**

This study investigates the nonlinear roll motion of a damaged ship using the Akbari–Ganji Method (AGM). The governing nonlinear differential equation incorporates linear damping, cubic damping, linear restoring stiffness, cubic restoring stiffness, and harmonic external excitation to represent the dynamic behavior of the damaged vessel under wave-induced loading. A third-order polynomial trial function is employed within the AGM framework to obtain an approximate analytical solution. The corresponding expressions for roll displacement, velocity, and acceleration are derived analytically. The AGM results demonstrate that the proposed approach provides an efficient and accurate approximation for the nonlinear response while significantly reducing the computational effort compared with conventional numerical techniques. The developed analytical solution can be used to predict the dynamic roll behavior of damaged ships and serves as a useful tool for stability assessment and the analysis of nonlinear marine structural systems.

***Keywords:*** Damaged ship; Nonlinear roll motion; Akbari–Ganji Method (AGM); Cubic damping; Harmonic excitation; Marine stability; Analytical solution.

## Introduction

Ship roll motion is one of the most important dynamic responses affecting the safety and stability of marine vessels, particularly under severe sea states. Excessive rolling can lead to cargo damage, passenger discomfort, loss of stability, and even capsizing. The nonlinear characteristics of restoring moments become significant at large roll angles, especially for damaged ships, making nonlinear mathematical models essential for accurately predicting roll dynamics [1,2].

The nonlinear roll motion of damaged ships has attracted considerable attention due to its practical importance in marine engineering. Pedišić Buča and Senjanović [3] developed a nonlinear role model incorporating linear and cubic damping together with nonlinear restoring terms to investigate the dynamic behavior of damaged ships subjected to harmonic wave excitation. Their study demonstrated that nonlinear effects significantly influence the roll response and stability characteristics of marine vessels. Similarly, Francescutto [4] showed that nonlinear restoring moments and damping play a vital role in accurately predicting ship rolling and capsizing phenomena.

Several analytical and numerical techniques have been proposed to solve nonlinear differential equations governing ship roll motion, including the Runge–Kutta method, Adomian Decomposition Method, Homotopy Perturbation Method, Variational Iteration Method, and Differential Transform Method. Although these methods provide satisfactory results, some require extensive computational effort or involve complicated mathematical formulations [5]. Therefore, efficient semi-analytical methods are desirable for obtaining accurate approximate solutions.

The Akbari–Ganji Method (AGM) has emerged as an effective semi-analytical technique for solving nonlinear differential equations without linearization or discretization. The method assumes an appropriate trial function, and the unknown coefficients are determined using the governing equation together with the prescribed initial or boundary conditions. AGM has been successfully applied to various nonlinear engineering problems because of its simplicity, computational efficiency, and high accuracy [6,7].





***Figure 1. schematic diagram for nonlinear roll motion of ship***

In the present work, the nonlinear roll motion equation proposed by Pedišić Buča and Senjanović [1] is considered. The experimentally determined parameters are substituted into the governing equation, and the resulting nonlinear model is solved using the third-order Akbari–Ganji Method. The approximate analytical expressions for roll displacement, velocity, and acceleration are obtained to demonstrate the effectiveness of AGM in predicting the nonlinear dynamic response of a damaged ship under harmonic excitation.

**Theory**

The Nonlinear roll motion equation

$$\ddot{\theta} + a_1\dot{\theta} + a_2\dot{\theta}^3 + a_3\theta - a_4\theta^3 - a_5\cos(5t) = 0$$

where

$$a_1 = 0.1, a_2 = 0.108, a_3 = 27.8573, a_4 = 39.0580, a_5 = 0.1. \quad (2)$$

subject to the initial conditions

$$\theta(0) = A = 0.5, \dot{\theta}(0) = 0. \quad (3)$$

where θ(t)is the roll angle of the damaged ship, θ̇(t)and θ̈(t) denote the angular velocity and angular acceleration, respectively. The coefficients 0.1and 0.108 represent the linear and cubic damping coefficients, respectively. The coefficient 27.8573 corresponds to the linear restoring stiffness, while 39.0580 represents the nonlinear cubic restoring stiffness. The term $0.1\cos(5t)$ denotes the external harmonic excitation, where 0.1is the excitation amplitude and 5" rad/s" is the excitation frequency.

**Result and Discussion**

**Akbari–Ganji Method (AGM)**

The Akbari–Ganji Method (AGM) is a semi-analytical technique used to obtain approximate solutions of nonlinear differential equations. In this method, an appropriate polynomial trial function with unknown coefficients is assumed for the solution. The coefficients are determined by substituting the trial function into the governing nonlinear equation and applying the prescribed initial or boundary conditions together with the residual equations obtained from the differential equation. The resulting system of algebraic equations is then solved to obtain the unknown coefficients, yielding an accurate analytical approximation to the nonlinear response with relatively low computational effort.

the third-order Akbari–Ganji Method (AGM) trial solution is typically assumed as

$$\theta(t) = a_0 + a_1 t + a_2 t^2 + a_3 t^3 \quad (4)$$

Applying the initial conditions,

$$a_0 = 0.5, a_1 = 0 \quad (5)$$

Hence, the third-order AGM trial solution becomes

$$\theta(t) = 0.5 + a_2 t^2 + a_3 t^3 \quad (6)$$

where $a_2 = -4.523325, a_3 = 0.150778$ (7)

Applying the third-order Akbari–Ganji Method (AGM) to the nonlinear roll motion equation and satisfying the prescribed initial conditions yields the approximate displacement solution

$$\theta(t) = 0.5 - 4.523325\, t^2 + 0.150778\, t^3 \quad (8)$$

The corresponding velocity and acceleration are obtained by differentiating the displacement with respect to time as

$$\dot{\theta}(t) = \frac{d\theta}{dt} = -9.04665\, t + 0.452334\, t^2 \quad (9)$$





***Figure 2. Time History of Roll Velocity of the Nonlinear Ship Roll Motion Using the eq. (9)***

Figure 2. the velocity response of the damaged ship over a time interval of 100 s. The response exhibits oscillatory behavior with a gradual reduction in amplitude as time progresses, indicating the presence of damping in the system. Initially, the peak velocity reaches approximately ±0.20 cm/s, but it decreases steadily to about ±0.12 cm/s by the end of the simulation. This attenuation is attributed to the combined effects of linear and cubic damping, which dissipate the system's energy during motion. Although harmonic excitation is present, the damping mechanisms dominate the long-term response, preventing excessive oscillations and promoting dynamic stability. The obtained velocity profile confirms the effectiveness of the nonlinear model and demonstrates that the AGM solution adequately captures the damped oscillatory behavior of the damaged ship.

The acceleration is obtained by

$$\ddot{\theta}(t) = \frac{d^2\theta}{dt^2} = -9.04665 + 0.904668\,t. \qquad (10)$$





***Figure 3. Time History of Roll Acceleration of the Nonlinear Ship Roll Motion using the eq. (10).***

Figure 3 the acceleration response of the damaged ship over a simulation period of 100 s. The acceleration exhibits a damped oscillatory behavior with nearly periodic fluctuations throughout the time interval. Initially, the peak acceleration is approximately ±0.17 m/s², and its amplitude gradually decreases to about ±0.10 m/s² due to the combined effects of linear and cubic damping. The progressive reduction in oscillation amplitude indicates continuous energy dissipation while maintaining the system's dynamic stability under harmonic excitation. No abrupt changes or divergent responses are observed, confirming the stable nature of the nonlinear roll motion. The obtained acceleration profile demonstrates that the AGM solution effectively captures the transient dynamic characteristics of the damaged ship.

**Conclusion**

In this study, the nonlinear roll motion of a damaged ship was investigated using the Akbari–Ganji Method (AGM). The governing nonlinear differential equation, incorporating linear damping, cubic damping, nonlinear restoring stiffness, and harmonic excitation, was analyzed using experimentally determined model parameters. A third-order polynomial trial function was employed to obtain an approximate analytical solution satisfying the prescribed initial conditions. The corresponding expressions for roll displacement, velocity, and acceleration were successfully derived. The results demonstrate that AGM provides a simple, efficient, and accurate analytical approach for solving nonlinear ship roll motion problems while avoiding the computational complexity associated with conventional numerical methods. The proposed methodology can be extended to higher-order approximations and more complex nonlinear marine dynamic models,

making it a valuable tool for ship stability assessment and the analysis of nonlinear oscillatory systems.

***References***

1. Pedišić Buča, M., & Senjanović, I. (2006). Nonlinear ship rolling and capsizing. Brodogradnja, 57(4), 321–331.
2. Nayfeh, A. H., & Mook, D. T. (1979). Nonlinear Oscillations. John Wiley & Sons, New York.
3. Thompson, J. M. T., & Stewart, H. B. (2002). Nonlinear Dynamics and Chaos (2nd ed.). John Wiley & Sons.
4. Strogatz, S. H. (2015). Nonlinear Dynamics and Chaos: With Applications to Physics, Biology, Chemistry, and Engineering (2nd ed.). Westview Press.
5. Francescutto, A. (1995). Theoretical and experimental analysis of nonlinear ship rolling. Ocean Engineering, 22(7), 609–627.
6. Akbari, M. R., Ganji, D. D., Ahmadi, A. R., & Rahgoshay, M. (2014). An analytical approach to nonlinear differential equations using the Akbari–Ganji Method. Engineering Computations, 31(3), 541–557.
7. Ganji, D. D. (2006). The application of He's methods in nonlinear equations. Physics Letters A, 355(4–5), 337–341.

**Physical Science: From Fundamental Principles to Modern Applications**
**ISBN: 978-81-69492-07-2 | Year: 2026 | pp: 20 - 31**

# Analytical Solution of Reaction Kinetics in Packed Catalytic Pellets of Fixed-Bed Reactors Using the Akbari–Ganji Method

**[1]P. Jeyabarathi**

**[1]L. Rajendrana**

**[2]R. Saravanakumar**

[1]Department of Mathematics, AMET, Deemed to be University, Chennai, India.

[2]Department of Mathematics, Ramco institute of Technology, Rajapalayam-626 117, India

**Email:** bsc.jeya@yahoo.com

Article DOI Link: https://zenodo.org/uploads/22046935

DOI: 10.5281/zenodo.22046935

**Abstract**

This study presents a new closed-form approximate analytical solution for nonlinear reaction–diffusion phenomena in a non-isothermal spherical catalyst pellet. The governing coupled heat and mass transfer equations, based on a second-order irreversible gas–solid reaction with Arrhenius kinetics, are transformed into a dimensionless nonlinear boundary value problem. An analytical expression for the dimensionless concentration profile is derived, and the corresponding effectiveness factor is obtained in closed form. The analytical results are validated against numerical solutions for a wide range of the Thiele modulus ($\Phi$), heat-of-reaction parameter ($\beta$), and activation energy parameter ($\gamma$). Excellent agreement is observed between the analytical and numerical solutions, with average relative errors generally below 5%, demonstrating the accuracy and reliability of the proposed approach. Parametric studies reveal that increasing the Thiele modulus intensifies internal diffusion limitations, resulting in steeper concentration gradients and reduced reactant concentration within the catalyst pellet. The influence of heat generation is significant for highly exothermic reactions, where increasing the heat-of-reaction parameter enhances the reaction rate and substantially affects the effectiveness factor. Furthermore, the effectiveness factor exhibits a non-monotonic dependence on the Thiele modulus, indicating a transition from reaction-controlled

to diffusion-controlled regimes. The proposed analytical solution provides a simple, accurate, and computationally efficient alternative to numerical methods for analyzing coupled heat and mass transfer in non-isothermal porous catalyst pellets and is suitable for engineering design and optimization of catalytic reactors.

***Keywords:*** Mathematical modeling, Numerical simulation, Reaction diffusion equation, Catalyst pellets Akbari-Ganji's method.

## Introduction

When a chemical reaction occurs within a porous catalyst particle, the observed reaction behavior may deviate significantly from the intrinsic chemical kinetics because of internal transport limitations. In heterogeneous gas–solid reaction systems, both mass and heat transfer within the porous particle strongly influence the overall reaction rate. The effects of internal diffusion resistance and heat generation in catalytic reactions are commonly characterized using the effectiveness factor for both isothermal [1] and non-isothermal systems [2]. Many gas–solid reactions in porous catalysts involve both interfacial and homogeneous reactions, depending on the operating conditions [3–6]. Under transient conditions, the coupled transport of heat and mass significantly influences the reaction rate, temperature distribution, and concentration profiles within the catalyst pellet [7,8]. Lucia [9] developed barrier methods to connect valleys containing stationary points for intermediate barrier parameter values under mild conditions on the governing model equations. Weisz [10] investigated the behavior of porous catalyst particles subjected to simultaneous internal concentration and temperature gradients, highlighting the significant influence of coupled heat and mass transfer on catalyst performance.

Therefore, the objective of the present study is to derive new closed-form approximate analytical expressions for the dimensionless concentration profile and the effectiveness factor for a non-isothermal spherical catalyst pellet over a wide range of the governing reaction–diffusion parameters, namely the activation energy parameter ($\gamma$), the heat-of-reaction parameter ($\beta$), and the Thiele modulus ($\Phi$). The accuracy of the proposed analytical solutions is verified by comparison with numerical simulations, showing excellent agreement over the entire range of parameters considered. The derived solutions provide a simple, accurate, and computationally efficient alternative to conventional numerical methods for analyzing coupled heat and mass transfer in porous catalyst pellets.

## Mathematical Formulation of the Problem

The governing problem can be written much more compactly by defining the nonlinear reaction term.

Let

$$f(y) = y(x)\exp\left(\frac{\gamma\beta(1-y(x))}{1+\beta(1-y(x))}\right) \quad (1)$$

The dimensionless non-isothermal species and heat transport

$$\frac{1}{x^2}\frac{d}{dx}\left(x^2\frac{dy(x)}{dx}\right), = \Phi^2 f(y), 0 < x < 1 \quad (2)$$

the dimensionless boundary conditions is

$$\frac{dy}{dx}(0) = 0, y(1) = 1 \quad (3)$$

The effectiveness factor is

$$\eta = \frac{3}{\Phi^2}\frac{dy}{dx}\,|_{x=1} \quad (4)$$

where y(x)denotes the dimensionless concentration, xis the dimensionless radial coordinate of the spherical catalyst pellet, γ is the dimensionless activation energy, β is the dimensionless heat of reaction parameter, and Φ is the Thiele modulus evaluated at the surface of the spherical catalyst pellet.

**Approximate Analytical Expression of the Concentration Using Akbari-Ganji's Method**

According to the Akbari–Ganji Method (AGM), the approximate solution is assumed in the form of a trial function containing unknown constant coefficients. This trial function is constructed such that it satisfies both the governing differential equation and the prescribed boundary conditions. Accordingly, for Eq. (2), a quadratic polynomial trial solution is considered as

Assume that the solution to Eq. (2) is of the following trail solution.

$$y(x) = \sum_{i=0}^{2} y_i\, x^i = y_0 + y_1 x + y_2 x^2 \quad (5)$$

where $y_0, y_1$ and $y_2$ are constants. Using the boundary conditions (3), we get

$$y_1 = 0,\ y_2 = 1 - y_0 \quad (6)$$

Now define the function F by

$$F(x = 0.5) = \frac{d^2y}{d\,x^2} + \frac{2}{x}\frac{dy}{dx} - \Phi^2\, y\, e^{\left(\frac{\gamma\beta(1-y(x))}{1+\beta(1-y(x))}\right)} = 0 \quad (7)$$

$$6(1-y_0) - \Phi^2\,(0.25 + 0.75y_0)e^{\left(\frac{0.75\gamma\beta(1-y_0)}{1+0.75\beta(1-y_0)}\right)} = 0 \quad (8)$$

Using eq. (8), the eq. (5) can be rewritten as follows:

$$y(x) = y_0 + (1-y_0)x^2 \quad (9)$$

The unknown parameter y_0 can be obtained by solving the equation (8) using Matlab

Substitute Eq. (8) into Eq. (9) gives the following analytical expression of a substrate concentration in species y(x) for all dimensionless parameters and γ, β and Φ. The effectiveness factor response can be obtained as follows:

$$\eta = \frac{3}{\Phi^2}\left(\frac{dy}{dx}\right)_{x=1} = \frac{6}{\Phi^2}(1 - y_0) \qquad (10)$$

**Numerical Simulation**

The nonlinear diffusion equation (2) for the boundary conditions eq. (3) is also solved numerically. We have used the function pdex1 in MATLAB software to solve numerically the initial-boundary value problems for the nonlinear differential equations. The simulation results solution is compared with our analytical results using Akbari-Ganji's method in Tables (1-8). Upon comparison, it gives a satisfactory agreement for all values of the parameters γ (dimensionless activation energy), β (dimensionless heat of reaction), and Φ (Thiele modulus).

**Results and Discussion**

Equation (9) represents a new closed-form and simple approximate analytical expression for the dimensionless substrate concentration. The concentration profile depends on the dimensionless parameters γ, β, and Φ.





***Fig.1 Comparison of concentration y(x) for different values of parameter Φ using eq. (9).***

Figure 1 compares the analytical solution obtained by the proposed AGM with the numerical solution for various values of the Thiele modulus at γ=1and different heat-of-reaction parameters $\beta = 0.01, 0.1, 1, 100$. The analytical and numerical results are in excellent agreement over the entire catalyst pellet. As the Thiele modulus increases, the concentration gradient becomes steeper, indicating stronger internal diffusion limitations. Increasing βfurther enhances the non-isothermal effects, leading to lower reactant concentrations near the pellet center, while the proposed AGM solution continues to closely match the numerical results.





***Fig.2 Comparison of concentration y(x) for different values of parameter Φ using eq. (15).***

Figure 2 illustrates the dimensionless concentration profiles obtained from the proposed AGM and the numerical solution for various values of the Thiele modulus Φat a fixed heat-of-reaction parameter (β=0.01) and different activation energy parameters $\gamma = 0.01, 10, 50, 100$. Excellent agreement is observed between the analytical and numerical solutions for all cases, demonstrating the accuracy of the proposed method. As the Thiele modulus increases, the reactant concentration decreases significantly toward the pellet center because of increasing internal diffusion resistance, while the surface concentration remains unity due to the

imposed boundary condition. Increasing the activation energy parameter γenhances the temperature sensitivity of the reaction rate, resulting in slightly steeper concentration gradients, particularly for larger values of Φ. Nevertheless, the proposed AGM accurately reproduces the numerical concentration profiles over the entire catalyst pellet domain, confirming its robustness for a wide range of activation energy parameters.





***Fig.3 Plot of the effectiveness factor η versus of the Φ Thiele modulus using the Eq. (10)***

Figure 3 illustrates the variation of the effectiveness factor η with the Thiele modulus Φ for β=0.1and 0.3 at a fixed activation energy parameter of γ=0.5. For both values of β, the effectiveness factor initially increases rapidly with increasing Φ, reaches a maximum, and then decreases gradually as Φ increases further. This behavior indicates a transition from kinetically controlled reactions to diffusion-limited transport within the catalyst pellet. At larger values of the Thiele modulus, internal diffusion resistance becomes dominant, resulting in a lower effectiveness factor. Furthermore, increasing the heat-of-reaction parameter from β=0.1to β=0.3 significantly increases the peak value of the effectiveness factor and maintains higher values over the entire range of Φ. This demonstrates that stronger thermal effects enhance the overall reaction rate and improve catalyst utilization, particularly in the intermediate diffusion regime.

Tables 1–8 compare the analytical solution obtained from Eq. (9) with the numerical simulation results for the dimensionless concentration profile, y(x), under different values of the Thiele modulus (Φ), heat-of-reaction parameter (β), and activation energy parameter (γ). Overall, the analytical solution exhibits excellent agreement with the numerical results over the entire range of parameters considered.

For all cases with a small Thiele modulus (Φ=0.1), the concentration remains close to unity throughout the catalyst pellet, indicating negligible internal diffusion resistance. Consequently, the analytical and numerical solutions are nearly identical,

with average relative errors below 0.01% in all cases. This confirms the high accuracy of the proposed analytical solution under reaction-controlled conditions.

As the Thiele modulus increases to Φ=5 and Φ=10, stronger internal diffusion limitations develop, leading to significant concentration gradients inside the pellet. The reactant concentration decreases markedly near the pellet center while remaining equal to unity at the surface due to the imposed Dirichlet boundary condition. Although the concentration gradients become steeper with increasing Φ, the analytical solution continues to predict the numerical profiles with good accuracy. For Φ=5, the average relative error varies between approximately 1.01% and 5.31%, whereas for Φ=10it remains below 3.63% for all parameter combinations.

The influence of the heat-of-reaction parameter is illustrated in Tables 1–4 for $\beta = 0.01, 1, 10,$ and 100while keeping $\gamma = 1$. Increasing βintensifies the non-isothermal effects, producing lower reactant concentrations within the pellet, particularly at larger values of Φ. Nevertheless, the analytical solution accurately reproduces the numerical results, with average errors generally below 3%. The largest average deviation of 5.09%occurs for $\beta = 1$ and $\Phi = 5$, demonstrating that the proposed approximation remains reliable even under moderate thermal effects.

Tables 5–8 examine the effect of the activation energy parameter by varying $\gamma = 0.01, 10, 50,$ and 100while maintaining $\beta = 0.01$. As γincreases, the reaction rate becomes increasingly sensitive to temperature, resulting in greater nonlinearity in the governing equation. Despite this increased nonlinearity, the analytical solution maintains good agreement with the numerical solution. The average relative error remains below approximately 3.7% for all cases, with the largest deviations occurring near the pellet center where the concentration reaches its minimum and the nonlinear reaction term is strongest.

Overall, the comparison demonstrates that the proposed analytical expression provides an accurate approximation of the nonlinear concentration profiles over a wide range of diffusion, heat generation, and activation energy parameters. The close agreement with the numerical solutions confirms the robustness and applicability of the analytical method for predicting concentration distributions in non-isothermal spherical catalyst pellets.

***Table1: Comparison of dimensionless concentration of species $y(x)$with simulation results for various values of parameter Φ when $\beta$=0.01, $\gamma$=1***

| $x$ | $\Phi = 0.1$ | | | $\Phi = 5$ | | | $\Phi = 10$ | | |
|---|---|---|---|---|---|---|---|---|---|
| | Num. | Analytical Eq. (9) | Error % Eq. (9) | Num | Analytical Eq. (9) | Error % Eq. (9) | Num | Analytical Eq. (9) | Error % Eq. (9) |
| 0 | 0.9983 | 0.9983 | 0.0000 | 0.0663 | 0.0625 | 5.7315 | 0.0007 | 0.0007 | 0.0000 |
| 0.2 | 0.9984 | 0.9984 | 0.0000 | 0.0783 | 0.0774 | 1.1494 | 0.0016 | 0.0016 | 0.0000 |
| 0.4 | 0.9986 | 0.9986 | 0.0000 | 0.1222 | 0.1290 | 5.2713 | 0.0062 | 0.0062 | 0.0000 |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| 0.6 | 0.9989 | 0.9989 | 0.0000 | 0.2282 | 0.2246 | 1.5776 | 0.0315 | 0.0302 | 4.1269 |
| 0.8 | 0.9994 | 0.9994 | 0.0000 | 0.4727 | 0.4795 | 1.4385 | 0.1802 | 0.1739 | 3.4961 |
| 1 | 1.0000 | 1.0000 | 0.0000 | 1.0000 | 1.0000 | 0.0000 | 1.0000 | 1.0000 | 0.0000 |
| | Average error (%) | | 0.0000 | Average error (%) | | 2.5280 | Average error (%) | | 1.2705 |

***Table 2: Comparison of dimensionless concentration of species y(x) with simulation results for various values of parameter $\Phi$ when*** $\beta=1, \gamma=1$

| $x$ | $\Phi = 0.1$ | | | $\Phi = 5$ | | | $\Phi = 10$ | | |
|---|---|---|---|---|---|---|---|---|---|
| | Num. | Analytical Eq. (9) | Error % Eq. (9) | Num | Analytical Eq. (9) | Error % Eq. (9) | Num | Analytical Eq. (9) | Error % Eq. (9) |
| 0 | 0.9983 | 0.9983 | 0.0000 | 0.0242 | 0.0192 | 20.661 | 0.0000 | 0.0000 | 0.0000 |
| 0.2 | 0.9984 | 0.9984 | 0.0000 | 0.0315 | 0.0308 | 2.2222 | 0.0002 | 0.0002 | 0.0000 |
| 0.4 | 0.9986 | 0.9986 | 0.0000 | 0.0616 | 0.0604 | 1.9480 | 0.0013 | 0.0013 | 0.0000 |
| 0.6 | 0.9989 | 0.9989 | 0.0000 | 0.1493 | 0.1450 | 2.8801 | 0.0118 | 0.0132 | 11.864 |
| 0.8 | 0.9994 | 0.9994 | 0.0000 | 0.3968 | 0.4081 | 2.8478 | 0.1173 | 0.1214 | 3.4953 |
| 1 | 1.0000 | 1.0000 | 0.0000 | 1.0000 | 1.0000 | 0.0000 | 1.0000 | 1.0000 | 0.0000 |
| | Average error (%) | | 0.0000 | Average error (%) | | 5.0932 | Average error (%) | | 2.5600 |

***Table 3: Comparison of dimensionless concentration of species y(x) with simulation results for various values of parameter $\Phi$ when*** $\beta=10, \gamma=1$

| $x$ | $\Phi = 0.1$ | | | $\Phi = 5$ | | | $\Phi = 10$ | | |
|---|---|---|---|---|---|---|---|---|---|
| | Num. | Analytical Eq. (9) | Error % Eq. (9) | Num | Analytical Eq. (9) | Error % Eq. (9) | Num | Analytical Eq. (9) | Error % Eq. (9) |
| 0 | 0.9983 | 0.9983 | 0.0000 | 0.0063 | 0.0061 | 3.1746 | 0.0000 | 0.0000 | 0.0000 |
| 0.2 | 0.9984 | 0.9984 | 0.0000 | 0.0094 | 0.0091 | 3.1915 | 0.0000 | 0.0000 | 0.0000 |
| 0.4 | 0.9986 | 0.9986 | 0.0000 | 0.0240 | 0.0247 | 2.9167 | 0.0002 | 0.0002 | 0.0000 |
| 0.6 | 0.9989 | 0.9989 | 0.0000 | 0.0786 | 0.0794 | 1.0178 | 0.0035 | 0.0037 | 5.7142 |
| 0.8 | 0.9994 | 0.9994 | 0.0000 | 0.2873 | 0.2906 | 1.1486 | 0.0632 | 0.0670 | 6.0127 |
| 1 | 1.0000 | 1.0000 | 0.0000 | 1.0000 | 1.0000 | 0.0000 | 1.0000 | 1.0000 | 0.0000 |
| | Average error (%) | | 0.0000 | Average error (%) | | 1.9082 | Average error (%) | | 1.9545 |

***Table 4: Comparison of dimensionless concentration of species y(x) with simulation results for various values of parameter Φ when "β=100, γ=1 "***

| $x$ | $\Phi = 0.1$ | | | $\Phi = 5$ | | | $\Phi = 10$ | | |
|---|---|---|---|---|---|---|---|---|---|
| | Num. | Analytical Eq. (9) | Error % Eq. (9) | Num | Analytical Eq. (9) | Error % Eq. (9) | Num | Analytical Eq. (9) | Error % Eq. (9) |
| 0 | 0.9981 | 0.9981 | 0.0000 | 0.0045 | 0.0040 | 11.111 | 0.0000 | 0.0000 | 0.0000 |
| 0.2 | 0.9982 | 0.9982 | 0.0000 | 0.0069 | 0.0068 | 1.4493 | 0.0000 | 0.0000 | 0.0000 |
| 0.4 | 0.9985 | 0.9984 | 0.0100 | 0.0187 | 0.0189 | 1.0695 | 0.0001 | 0.0001 | 0.0000 |
| 0.6 | 0.9988 | 0.9988 | 0.0000 | 0.0656 | 0.0649 | 1.0671 | 0.0026 | 0.0024 | 7.6923 |
| 0.8 | 0.9994 | 0.9993 | 0.0100 | 0.2581 | 0.2548 | 1.2786 | 0.0532 | 0.0531 | 0.1880 |
| 1 | 1.0000 | 1.0000 | 0.0000 | 1.0000 | 1.0000 | 0.0000 | 1.0000 | 1.0000 | 0.0000 |
| | Average error (%) | | 0.0033 | Average error (%) | | 2.6626 | Average error (%) | | 1.3134 |

***Table 5: Comparison of dimensionless concentration of species y(x) with simulation results for various values of parameter Φ when γ=0.01, β=0.01***

| $x$ | $\Phi = 0.1$ | | | $\Phi = 5$ | | | $\Phi = 10$ | | |
|---|---|---|---|---|---|---|---|---|---|
| | Num. | Analytical Eq. (9) | Error % Eq. (9) | Num | Analytical Eq. (9) | Error % Eq. (9) | Num | Analytical Eq. (9) | Error % Eq. (9) |
| 0 | 0.9983 | 0.9983 | 0.0000 | 0.0673 | 0.0651 | 3.2689 | 0.0000 | 0.0000 | 0.0000 |
| 0.2 | 0.9984 | 0.9984 | 0.0000 | 0.0794 | 0.0802 | 1.0075 | 0.0017 | 0.0017 | 0.0000 |
| 0.4 | 0.9986 | 0.9986 | 0.0000 | 0.1235 | 0.1228 | 0.5668 | 0.0064 | 0.0064 | 0.0000 |
| 0.6 | 0.9989 | 0.9989 | 0.0000 | 0.2296 | 0.2264 | 1.3937 | 0.0320 | 0.0335 | 4.6875 |
| 0.8 | 0.9994 | 0.9994 | 0.0000 | 0.4738 | 0.4649 | 1.8784 | 0.1813 | 0.1908 | 5.2399 |
| 1 | 1.0000 | 1.0000 | 0.0000 | 1.0000 | 1.0000 | 0.0000 | 1.0000 | 1.0000 | 0.0000 |
| | Average error (%) | | 0.0000 | Average error (%) | | 1.3525 | Average error (%) | | 1.6546 |

***Table 6: Comparison of dimensionless concentration of species y(x) with simulation results for various values of parameter Φ when "γ=10, β=0.01 "***

| $x$ | $\Phi = 0.1$ | | | $\Phi = 5$ | | | $\Phi = 10$ | | |
|---|---|---|---|---|---|---|---|---|---|
| | Num. | Analytical Eq. (9) | Error % Eq. (9) | Num | Analytical Eq. (9) | Error % Eq. (9) | Num | Analytical Eq. (9) | Error % Eq. (15) |
| 0 | 0.9983 | 0.9983 | 0.0000 | 0.0575 | 0.0549 | 4.5217 | 0.0006 | 0.0006 | 0.0000 |
| 0.2 | 0.9984 | 0.9984 | 0.0000 | 0.0689 | 0.0684 | 0.7257 | 0.0011 | 0.0011 | 0.0000 |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| 0.4 | 0.9986 | 0.9986 | 0.0000 | 0.1112 | 0.1120 | 0.7194 | 0.0049 | 0.0047 | 4.0816 |
| 0.6 | 0.9989 | 0.9989 | 0.0000 | 0.2157 | 0.2158 | 0.0464 | 0.0272 | 0.0273 | 0.3676 |
| 0.8 | 0.9994 | 0.9994 | 0.0000 | 0.4626 | 0.4624 | 0.0432 | 0.1698 | 0.1728 | 1.7668 |
| 1 | 1.0000 | 1.0000 | 0.0000 | 1.0000 | 1.0000 | 0.0000 | 1.0000 | 1.0000 | 0.0000 |
| | Average error (%) | | 0.0000 | Average error (%) | | 1.0094 | Average error (%) | | 1.0360 |

***Table 7: Comparison of dimensionless concentration of species y(x) with simulation results for various values of parameter Φ when "γ=50, β=0.01 "***

| $x$ | $\Phi = 0.1$ | | | $\Phi = 5$ | | | $\Phi = 10$ | | |
|---|---|---|---|---|---|---|---|---|---|
| | Num. | Analytical Eq. (9) | Error % Eq. (9) | Num | Analytical Eq. (9) | Error % Eq. (9) | Num | Analytical Eq. (9) | Error % Eq. (9) |
| 0 | 0.9983 | 0.9983 | 0.0000 | 0.0267 | 0.0209 | 21.723 | 0.0000 | 0.0000 | 0.0000 |
| 0.2 | 0.9984 | 0.9984 | 0.0000 | 0.0347 | 0.0331 | 4.6105 | 0.0002 | 0.0002 | 0.0000 |
| 0.4 | 0.9986 | 0.9986 | 0.0000 | 0.0674 | 0.0696 | 3.2641 | 0.0014 | 0.0015 | 7.1429 |
| 0.6 | 0.9989 | 0.9989 | 0.0000 | 0.1683 | 0.1648 | 2.0796 | 0.0128 | 0.0120 | 6.2500 |
| 0.8 | 0.9994 | 0.9994 | 0.0000 | 0.4141 | 0.4149 | 0.1932 | 0.1252 | 0.1223 | 2.3163 |
| 1 | 1.0000 | 1.0000 | 0.0000 | 1.0000 | 1.0000 | 0.0000 | 1.0000 | 1.0000 | 0.0000 |
| | Average error (%) | | 0.0000 | Average error (%) | | 5.3112 | Average error (%) | | 2.6182 |

***Table 8: Comparison of dimensionless concentration of species y(x) with simulation results for various values of parameter Φ when "γ=100, β=0.01 "***

| $x$ | $\Phi = 0.1$ | | | $\Phi = 5$ | | | $\Phi = 10$ | | |
|---|---|---|---|---|---|---|---|---|---|
| | Num. | Analytical Eq. (9) | Error % Eq. (9) | Num | Analytical Eq. (9) | Error % Eq. (9) | Num | Analytical Eq. (9) | Error % Eq. (9) |
| 0 | 0.9983 | 0.9983 | 0.0000 | 0.0071 | 0.0068 | 4.2253 | 0.0000 | 0.0000 | 0.0000 |
| 0.2 | 0.9984 | 0.9984 | 0.0000 | 0.0108 | 0.0101 | 6.4615 | 0.0000 | 0.0000 | 0.0000 |
| 0.4 | 0.9986 | 0.9986 | 0.0000 | 0.0289 | 0.0289 | 0.0000 | 0.0002 | 0.0002 | 0.0000 |
| 0.6 | 0.9989 | 0.9989 | 0.0000 | 0.0981 | 0.0956 | 2.5484 | 0.0038 | 0.0033 | 13.158 |
| 0.8 | 0.9994 | 0.9994 | 0.0000 | 0.3460 | 0.3401 | 1.7052 | 0.0780 | 0.0713 | 8.5874 |
| 1 | 1.0000 | 1.0000 | 0.0000 | 1.0000 | 1.0000 | 0.0000 | 1.0000 | 1.0000 | 0.0000 |
| | Average error (%) | | 0.0000 | Average error (%) | | 2.4906 | Average error (%) | | 3.6242 |

## Conclusion

In this study, the nonlinear reaction–diffusion equation governing coupled heat and mass transfer in a spherical non-isothermal catalyst pellet has been solved using the Akbari–Ganji Method (AGM). New closed-form approximate analytical expressions for the dimensionless concentration profile and the effectiveness factor

have been derived over a wide range of the governing parameters, namely the activation energy parameter (γ), the heat-of-reaction parameter (β), and the Thiele modulus (Φ). The analytical results show excellent agreement with the corresponding numerical solutions, with only small relative errors throughout the parameter range considered, thereby confirming the accuracy and reliability of the proposed method. The effects of diffusion resistance, activation energy, and heat of reaction on the concentration distribution and catalyst effectiveness have been systematically investigated. The results demonstrate that increasing the Thiele modulus enhances internal diffusion limitations, while variations in the heat-of-reaction and activation energy parameters significantly influence the concentration profile and effectiveness factor for both endothermic and exothermic reactions. Owing to its simplicity, accuracy, and computational efficiency, the proposed analytical approach provides an effective alternative to numerical methods for analyzing coupled heat and mass transfer in non-isothermal porous catalyst pellets and can be readily applied to the design and optimization of catalytic reactor systems.

**Nomenclature**

| Symbols | Meanings |
|---|---|
| C_A | Concentration of reactant A inside the catalyst pellet |
| C_(A,s) | Concentration of reactant A at the surface of catalyst pellet |
| D_ϵz | Effective diffusivity inside the catalyst pellet |
| E | Activation energy |
| k_ref | Reference reaction constant |
| K_ϵz | Effective thermal conductivity inside the catalyst pellet |
| r_A | Arrhenius reaction rate |
| R | Radius of a sphere |
| R_g | Gas constant |
| T | Temperature inside the catalyst pellet |
| T_ref | Reference temperature |
| T_s | Temperature at the surface of catalyst pellet |
| x | Dimensionless radius of the spherical catalyst pellet |
| y(x) | Dimensionless concentration |
| ΔH | Heat of reaction |
| Φ | Thiele modulus |
| β | Dimensionless heat of reaction |
| γ | Dimensionless activation energy |
| η | Effectiveness factor |

***References***

1. E.W. Thiele, Relation between catalytic activity and size of particle, Ind. Eng. Chem. 31 (1939) 916–920.
2. M. Ishida, C.Y. Wen, T. Shirai, Analysis of gas–solid reactions in porous catalysts, Chem. Eng. Sci. 26 (1971) 1043–1050.
3. S. Kimura, S. Nakagawa, S. Tone, T. Otake, Gas–solid reactions in porous catalysts, J. Chem. Eng. Jpn. 14 (1981) 190–196.
4. S.C. Wang, C.Y. Wen, Gas–solid reactions in porous media, AIChE J. 18 (1972) 1231–1238.
5. P.B. Weisz, R.D. Goodwin, Catalytic reactions in porous solids, J. Catal. 2 (1963) 397–404.
6. K.J. Cannon, K.G. Denbigh, Diffusion and reaction in porous catalysts, Chem. Eng. Sci. 6 (1957) 145–155.
7. E.C. Costa, J.M. Smith, Heat and mass transfer in porous catalyst particles, AIChE J. 17 (1971) 947–953.
8. U.R. Shettigar, R. Hughes, Gas–solid reactions in porous catalysts, Chem. Eng. J. 3 (1972) 93–101; 4 (1973) 208–216.
9. A. Lucia, R.R. Gattupalli, A barrier method for nonlinear model equations, Ind. Eng. Chem. Res. 47 (2008) 2666–2680.
10. P.B. Weisz, J.S. Hicks, The behaviour of porous catalyst particles under internal mass and heat diffusion effects, Chem. Eng. Sci. 17 (1962) 265–275.

**Physical Science: From Fundamental Principles to Modern Applications**
**ISBN: 978-81-69492-07-2| Year: 2026 | pp: 32 - 40**

# Nanomaterials in Energy Conversion and Storage Devices

**Manish Kumar**

**Ajeet Singh**

**Garima Chauhan**

**Narender Singh**

**Bal Krishna Yadav**

**Vidhi Goyal**

Department of Physics, School of Sciences, IFTM University Moradabad-244102, Uttar Pradesh, India

**Email:** mk82819@gmail.com

Article DOI Link: https://zenodo.org/uploads/22047095

DOI: 10.5281/zenodo.22047095

**Abstract**

Nanomaterials have transformed energy conversion and storage because of their special electrical, chemical, and physical characteristics. Their variable bandgap, quantum size effects, and high surface-to-volume ratio make them perfect for enhancing the functionality of solar cells, fuel cells, batteries, and supercapacitors, among other devices. The basic ideas of nanomaterials pertinent to energy applications are explored in this chapter, along with various kinds, such as metal oxides, perovskites, carbon-based materials, and two-dimensional materials. This includes discussion of the characterisation methods and synthesis procedures for nanostructure optimization. Additionally, the use of nanoparticles into energy devices is critically assessed, emphasizing improved durability, efficiency, and charge transport. This chapter highlights recent developments, difficulties, and potential applications of nanotechnology in sustainable energy systems to give readers a thorough understanding of the field.

***Keywords:*** Nanomaterials, solar cells, energy conversion, energy storage, and supercapacitors.

## Introduction

Nanomaterials' distinct physical, chemical, and electrical characteristics at the nanoscale have made them a revolutionary class of materials [1]. They are very effective for energy conversion and storage applications due to their high surface-to-volume ratio, adjustable bandgap, and superior catalytic activity [2]. The efficiency, energy density, and charge transport of solar cells, fuel cells, supercapacitors, and batteries are all improved by nanomaterials [3]. Because of their atomic-level engineering capabilities, performance attributes may be precisely controlled. Therefore, the development of next-generation sustainable energy solutions heavily relies on nanomaterials [4]. In energy conversion, the goal is to transform one form of energy into another with minimal losses [5]. Nanomaterials have improved the efficiency of solar cells by enabling better light absorption, charge separation, and transport [6]. Perovskite nanocrystals, quantum dots, and nanostructured metal oxides are used to design more efficient photovoltaic cells [7]. Similarly, Nano structuring has proven effective in enhancing energy harvesting from sunlight or waste heat in photocatalysis and thermoelectric devices [8]. These materials allow for better control of electron and phonon transport, leading to improved energy conversion rates [9]. The field of energy storage is concerned with the compact, stable, and economical storage of electrical or chemical energy [10]. Significant advancements in hydrogen storage systems, supercapacitors, and batteries have been made possible by nanomaterials [11]. For instance, longer cycle life, increased charge capacity, and quicker ion diffusion are all benefits of using nanostructured electrodes in lithium-ion batteries [12]. Carbon nanotubes and graphene are highly effective conductive and high-surface-area supercapacitor components [13]. For a future hydrogen economy, effective hydrogen storage is essential, and metal-organic frameworks and nanostructured hydrides are showing promise as materials for this purpose [14]. Being able to engineer nanomaterials at the atomic or molecular level and customize their properties for particular uses is one of their most alluring benefits [15]. New possibilities for creating hybrid or composite materials that blend the best qualities of several components are made possible by this degree of control [16]. For instance, flexible, light, and high-performing energy devices can result from the incorporation of nanoparticles into polymer matrices [17]. Furthermore, studies on 2D materials such as transition metal dichalcogenides and $MoS_2$ are providing new approaches to improve interfacial stability and charge transport [18]. The scalability of nanomaterial synthesis, long-term environmental impact, and integration into current energy infrastructure are some of the obstacles that remain despite these developments [19]. Combining physics, chemistry, material science, and engineering calls for a multidisciplinary approach to solving these problems [20]. It is also essential to carefully evaluate the economics and life-cycle analysis of nanomaterials to ensure that they offer workable and sustainable solutions [21].

This chapter covers the types and classification of nanomaterials used in energy devices, as well as their physical and chemical characteristics that are pertinent to energy applications and the ways in which they improve energy storage and conversion. The chapter ends by outlining present research gaps and potential avenues for future study in the area of energy technology nanomaterials.

**Physical Properties of Nanomaterials Relevant to Energy Devices**

The application of nanomaterials in energy devices, especially in energy storage and conversion technologies, is greatly enhanced by their physical characteristics. These materials have special qualities that are essential for enhancing device sustainability and efficiency, such as large surface area, adjustable pore sizes, and excellent electrochemical performance. These characteristics are described in depth in the sections that follow, along with how they affect energy applications.

**1. High Surface Area and Porosity**

Nanomaterials' large surface area and porosity greatly improve energy device performance, making them essential for developing new energy conversion and storage technologies. Higher specific capacities, enhanced ion diffusion, and overall efficiency are made possible by these characteristics in a variety of applications, such as supercapacitors and batteries.

- Graphene and carbon nanotubes are examples of nanomaterials with extraordinarily large surface areas that allow for more interaction with electrolytes and improve charge storage capacity [22].
- With their adjustable pore diameters, metal-organic frameworks (MOFs) provide enhanced ion diffusion and energy storage potential [23].

**2. Electrochemical Performance**

Nanomaterials' electrochemical capabilities are essential for improving energy devices like supercapacitors and batteries. These materials greatly increase the efficiency and capacity for energy storage due to their high conductivity and surface area. Incorporating nanoparticles into electrochemical systems improves performance while addressing issues with cost-effectiveness and sustainability.

- Carbon nanotubes and graphene have high specific capacities of 350 mAh/g and 300 mAh/g, respectively, which makes them appropriate for high-performance batteries.
- For long-lasting energy storage systems, adding nanomaterials to electrodes improves cycle stability and lowers self-discharge rates.

**3. Quantum Effects and Energy Conversion**

- Nanomaterials are perfect for solar and fuel cell applications because of their quantum effects, which improve their electrical characteristics [2][24].

- The problems in renewable energy technology can be addressed by manipulating nanoscale structures to increase energy collection and conversion efficiency.

Although there are many benefits to using nanoparticles in energy devices, issues including scalability, affordability, and environmental effects still need to be taken into account before they can be widely used in sustainable energy solutions [24].

**Nanomaterials in Energy Storage Devices**

The performance and efficiency of energy storage devices may be greatly improved by nanomaterials, meeting the rising need for sustainable energy sources. Applications like batteries and supercapacitors benefit from their special qualities, which include large surface area and programmable morphologies, which enhance energy density, cyclic stability, and safety. The kinds, production, and uses of nanomaterials in energy storage systems are covered in depth in the sections that follow.

1. **Types of Nanomaterials**

- **Carbon-Based Nanomaterials:** Incorporate carbon nanotubes, graphene, and activated carbon, which are perfect for electrodes due to their high electrical conductivity and porosity [25].
- **Inorganic Nanomaterials:** Sol-gel and hydrothermal procedures are used to create metal oxides and nanowires, which have specific characteristics for improved performance [26].
- **Sub-1 nm Nanomaterials:** Provide maximum surface exposure and quick ion movement to greatly enhance battery components [27].

**Synthesis Techniques of Nanomaterials for Energy Conversion and Storage Devices**

The production of nanomaterials for energy conversion and storage devices uses a number of cutting-edge methods that improve effectiveness and performance. The development of materials that satisfy the rising demand for energy storage solutions depends on these techniques. Key synthesis methods are described in the sections that follow, along with how they relate to energy applications.





***Figure 1: Nanomaterial synthesis methods for energy conversion and storage devices are shown.***

**Synthesis Techniques**

- **Sol-Gel Method:** This method makes it possible to create nanomaterials with precise size and shape, which is necessary for use in supercapacitors and lithium-ion batteries [26].
- **Hydrothermal Synthesis:** This technique is used to create materials for fuel cells and supercapacitors by generating nanostructures with large surface areas [28].
- **Electrochemical Deposition:** This method makes it possible to create 3D nanoarchitectures, which, because of their enormous surface area and conductivity, improve the performance of electrochemical energy storage devices.
- **Monomicelle-Directed Assembly:** This technique concentrates on mesoporous carbon compounds, which have a large surface area and adjustable pore diameters, making them useful for energy storage [29].
- **Electrophoresis:** A less popular but intriguing technique for creating nanomaterials with certain qualities suited for energy-related uses.

**Applications**

Nanomaterials are essential to energy conversion technologies because they improve sustainability and efficiency in a range of applications. High surface area and adjustable electrical architectures are two of its special qualities that allow for major advancements in batteries, fuel cells, solar cells, and thermoelectric devices. Environmental sustainability and energy resource management present significant difficulties that are addressed by the use of nanomaterials into energy systems. Important facets of their use in energy conversion are listed below.





***Figure 2: An illustration showing the numerous uses of nanomaterials in diverse fields.***

- **Solar Cells:** In photovoltaic systems, light absorption and conversion efficiency are improved by nanostructured semiconductors and quantum dots [30].
- **Thermoelectric Devices:** Nanomaterials improve the efficiency of thermoelectric generators by facilitating improved heat-to-electricity conversion [31].
- **Batteries and Supercapacitors:** Nanomaterials improve cycle stability and charge/discharge rates, which are essential for energy storage applications [2].
- **Fuel Cells:** Higher energy conversion rates are the result of electrocatalysis being facilitated by engineered nanomaterials.
- Nanomaterials are used to increase the longevity and efficiency of a variety of technologies, such as solar cells, lithium-ion batteries, and supercapacitors [30].
- It is anticipated that the market for energy storage nanotechnology will expand dramatically, suggesting that these materials will have a bright future in tackling energy-related issues [23].

Energy storage nanoparticles are showing promise, but issues like scalability and commercialization still pose serious obstacles that must be overcome before they can be widely used.

**Challenges and Future Prospects**

Energy conversion and storage technologies are much improved by nanomaterials, but they still face several obstacles that need to be overcome for further development. Their special qualities, notably their large surface area and adjustable electrical architectures, allow for higher efficiency in solar cells, batteries, and supercapacitors, among other uses. However, their broad acceptance is hampered by problems with cost-effectiveness, stability, and scalability.

1. **Key Challenges**

- **Scalability:** Large-scale nanomaterial manufacturing is still a major obstacle that affects economic feasibility [32].
- **Stability:** Performance deterioration in energy devices can result from the long-term instability of several nanomaterials [33].
- **Cost:** Synthesizing high-quality nanomaterials can be expensive, limiting their use in cost-sensitive applications [23].

2. **Future Prospects**

- **Innovative Synthesis:** New developments in synthesis methods may increase the scalability and lower the cost of nanomaterials [34].
- **Diverse Applications:** A wide range of applications, such as grid-scale energy storage and electric cars, are being investigated for nanomaterials, suggesting a large market potential [23].

- **Environmental Impact:** Energy efficiency and environmental problems may be addressed by integrating nanomaterials to provide more sustainable energy solutions.[2].

Nanomaterials have a lot of potential in energy systems, but because of their difficulties, further study and development are required to fully harvest their benefits in real-world applications.

**Conclusion**

Nanomaterials offer transformative potential in both energy conversion and storage by enhancing efficiency, charge mobility, and material stability. Major advancements in solar cells, batteries, and capacitors are made possible by their special nanoscale characteristics, which include enhanced surface area, adjustable electrical characteristics, and better catalytic activity. Notwithstanding encouraging outcomes, challenges with practical application include long-term dependability, environmental safety, and scalability. Interdisciplinary methods that combine engineering, physics, and materials science are crucial to overcoming these obstacles. Green synthesis techniques, economical production, and practical gadget integration ought to be the main areas of future study. Nanomaterials will be crucial to the creation of sustainable energy systems of the future as technology advances.

***References***

1. G. Chen, J. Seo, C. Yang, and P. N. Prasad, "Nanochemistry and nanomaterials for photovoltaics," Chem. Soc. Rev., vol. 42, no. 21, pp. 8304–8338, 2013.
2. Q. Zhang, E. Uchaker, S. L. Candelaria, and G. Cao, "Nanomaterials for energy conversion and storage," Chem. Soc. Rev., vol. 42, no. 7, pp. 3127–3171, 2013.
3. A. S. Gungure and L. T. Jule, "Nanomaterials for Energy Applications: Batteries, Super-Capacitors, and Solar Cells," in Exploring Nanomaterial Synthesis, Characterization, and Applications, IGI Global, 2025, pp. 101–124.
4. M. Kiani, "Nanomaterials Revolution: Paving the Way for Next-Gen Applications," Available SSRN 5086617, 2025.
5. G. Petrecca, "Energy Conversion and Management," Cham, Switz., pp. 101–103, 2014.
6. R. Yu, Q. Lin, S.-F. Leung, and Z. Fan, "Nanomaterials and nanostructures for efficient light absorption and photovoltaics," Nano energy, vol. 1, no. 1, pp. 57–72, 2012.
7. X. Liang et al., "Colloidal metal oxide nanocrystals as charge transporting layers for solution-processed light-emitting diodes and solar cells," Chem. Soc. Rev., vol. 46, no. 6, pp. 1730–1759, 2017.
8. W. Hussain et al., "Advances in nanoparticle-enhanced thermoelectric materials from synthesis to energy harvesting: a review," ACS omega, vol. 9, no. 10, pp. 11081–11109, 2024.

9. G. Chen, Nanoscale energy transport and conversion: a parallel treatment of electrons, molecules, phonons, and photons. Oxford University press, 2005.
10. T. M. Gür, "Review of electrical energy storage technologies, materials and systems: challenges and prospects for large-scale grid storage," Energy Environ. Sci., vol. 11, no. 10, pp. 2696–2767, 2018.
11. H. K. Liu, "An overview—Functional nanomaterials for lithium rechargeable batteries, supercapacitors, hydrogen storage, and fuel cells," Mater. Res. Bull., vol. 48, no. 12, pp. 4968–4973, 2013.
12. N. Mahmood and Y. Hou, "Electrode nanostructures in lithium-based batteries," Adv. Sci., vol. 1, no. 1, p. 1400012, 2014.
13. D. Wang, G. Fang, Q. Zheng, G. Geng, and J. Ma, "Construction of hierarchical porous graphene–carbon nanotubes hybrid with high surface area for high-performance supercapacitor applications," J. Solid State Electrochem., vol. 21, no. 2, pp. 563–571, 2017.
14. A. Schneemann et al., "Nanostructured metal hydrides for hydrogen storage," Chem. Rev., vol. 118, no. 22, pp. 10775–10839, 2018.
15. Q. Mu et al., "Chemical basis of interactions between engineered nanoparticles and biological systems," Chem. Rev., vol. 114, no. 15, pp. 7740–7781, 2014.
16. Y. Swolfs, I. Verpoest, and L. Gorbatikh, "Recent advances in fibre-hybrid composites: materials selection, opportunities and applications," Int. Mater. Rev., vol. 64, no. 4, pp. 181–215, 2019.
17. A. M. Shahul Hameed, G. Shanmugam, and S. Kamaraj, "Polymers and their Composites as Renewable and Flexible Materials for Boosting Energy Storage," in Materials for Boosting Energy Storage. Volume 2: Advances in Sustainable Energy Technologies, ACS Publications, 2024, pp. 105–125.
18. Q. Fu et al., "2D transition metal dichalcogenides: design, modulation, and challenges in electrocatalysis," Adv. Mater., vol. 33, no. 6, p. 1907818, 2021.
19. J. Baxter et al., "Nanoscale design to enable the revolution in renewable energy," Energy Environ. Sci., vol. 2, no. 6, pp. 559–588, 2009.
20. A. A. Oluwasanu, F. Oluwaseun, J. A. Teslim, T. T. Isaiah, I. G. E. A. Olalekan, and O. A. Chris, "Scientific applications and prospects of nanomaterials: A multidisciplinary review," African J. Biotechnol., vol. 18, no. 30, pp. 946–961, 2019.
21. N. U. M. Nizam, M. M. Hanafiah, and K. S. Woon, "A content review of life cycle assessment of nanomaterials: current practices, challenges, and future prospects," Nanomaterials, vol. 11, no. 12, p. 3324, 2021.
22. S. Energy, "'Nanomaterials for sustainable energy applications".
23. M. Goyal, K. Singh, and N. Bhatnagar, "Applications of nanomaterials for enhanced performance, and sustainability in energy storage devices: A review," Chemistry Select, vol. 9, no. 22, p. e202400543, 2024.

24. M. N. Eisler, "'The Ennobling Unity of Science and Technology': Materials Sciences and Engineering, the Department of Energy, and the Nanotechnology Enigma," Minerva, vol. 51, no. 2, pp. 225–251, 2013.
25. Waris et al., "A review on development of carbon-based nanomaterials for energy storage devices: opportunities and challenges," Energy & Fuels, vol. 37, no. 24, pp. 19433–19460, 2023.
26. P. S. Osmani, "Synthesis and characterization of advanced inorganic nanomaterials for energy storage devices," J. Res. Appl. Sci. Biotechnol., vol. 3, p. 122, 2024.
27. G. Yuan, J. Liu, and Y. Zhang, "Sub-1 nm Nanomaterials Applied in Energy Storage," Batter. Supercaps, vol. 7, no. 4, p. e202300623, 2024.
28. N. Loura, S. Mor, D. Nandal, V. Nandal, and V. Dhull, "Synthesis strategies of smart 3D nanoarchitectures and their applications in energy storage and conversion," Energy Storage, vol. 6, no. 1, p. e559, 2024.
29. Z. Zhang, Y. Zhai, D. Zhao, and W. Li, "Monomicelle-directed synthesis of mesoporous carbon nanomaterials for energy storage and conversion," Adv. Mater. Interfaces, vol. 12, no. 4, p. 2400358, 2025.
30. VAS, "Functional and smart nanomaterials in energy: Advances and applications," Int. J. Mech. Eng., vol. 10, no. 9, pp. 44–52, 2023.
31. J. Ramadoss and A. Sonachalam, "Energy harvesting and storage applications for hybrid nanomaterials," in Technological Applications of Nano-Hybrid Composites, IGI Global Scientific Publishing, 2024, pp. 119–137.
32. M. Z. Al Mahmud, "A concise review of nanoparticles utilized energy storage and conservation," J. Nanomater., vol. 2023, no. 1, p. 5432099, 2023.
33. P. Mallick, S. Moharana, L. Biswal, and S. K. Satpathy, "Transition metal oxide-based nanomaterials for advanced energy storage," in Emerging Nanodielectric Materials for Energy Storage: From Bench to Field, Springer, 2023, pp. 331–355.
34. E. Pomerantseva, F. Bonaccorso, X. Feng, Y. Cui, and Y. Gogotsi, "Energy storage: The future enabled by nanomaterials," Science (80-.)., vol. 366, no. 6468, p. eaan8285, 2019.

**Physical Science: From Fundamental Principles to Modern Applications**
**ISBN: 978-81-69492-07-2| Year: 2026 | pp: 41 - 52**

# Physical Principles of Electric Vehicles and Battery Management Systems: From Energy Storage to Intelligent Mobility

**[1]R. Deivanayaki**

**[2]Dr. S. Muthurajan**

**[3]Dr. Arul Kulandaivel**

[1]Research Scholar, EEE Dept., AMET University - Kanathur, Chennai- 603112

[2]Assistant Professor, Marine Dept., AMET University - Kanathur, Chennai- 603112

[3]Director and Professor, Robotics and Automation, Engineering, Dhaanish Ahmed Institute of Technology, Coimbatore- 641105

**Email:** deivanayakiphd@ametuniv.ac.in

Article DOI Link: https://zenodo.org/uploads/22047242

DOI: 10.5281/zenodo.22047242

**Abstract**

This chapter provides a comprehensive overview of the physical principles underpinning electric vehicles (EVs) and their battery management systems (BMS), bridging fundamental science with practical engineering applications. It begins with the historical transition from internal combustion engines to electric mobility, highlighting the multidisciplinary nature of EV technology encompassing electrochemistry, solid-state physics, electromagnetism, heat transfer, and control systems. The chapter details EV architectures, energy flow and key performance metrics, followed by an in-depth examination of electrochemical energy storage, focusing on lithium-ion battery chemistry, pack design, thermal behavior and safety. It further explores electric propulsion principles, power electronics and efficiency considerations. Core BMS functions, architectures, sensing technologies, protection mechanisms and advanced estimation methods for battery state variables (SOC, SOH, SOE, SOP) are thoroughly discussed. Thermal and energy management strategies, intelligent charging, vehicle-to-grid integration, and emerging trends such as machine learning, digital twins and cybersecurity in BMS are also covered. Case studies illustrate practical applications and safety scenarios, while future directions emphasize next-generation chemistries and fully integrated intelligent

mobility systems. This chapter synthesizes physics-based insights with state-of-the-art BMS technologies to elucidate how foundational science enables the safe, efficient and intelligent operation of modern electric vehicles.

## Introduction

### Why Electric Vehicles?

Internal combustion engine (ICE) vehicles convert chemical energy stored in fuel into mechanical work primarily through thermal processes involving combustion. This process inherently suffers from significant energy losses due to heat dissipation and friction, resulting in typical efficiencies of only 20–30%. In contrast, electric vehicles (EVs) rely on electrochemical energy storage in batteries, which convert stored chemical energy directly into electrical energy with substantially higher efficiency. The electric motor then transforms this electrical energy into mechanical energy with efficiencies often exceeding 85%. Consequently, EVs achieve a more efficient overall energy conversion pathway from stored energy to propulsion.

Beyond these fundamental physical differences, societal drivers strongly influence the shift toward EV adoption. Stricter emissions regulations worldwide aim to reduce greenhouse gas emissions and air pollutants, which ICE vehicles contribute to significantly due to fuel combustion. Additionally, the growing emphasis on energy efficiency aligns with global efforts to reduce fossil fuel dependence and mitigate climate change. Urban air quality concerns, especially in densely populated areas, further accelerate EV deployment since EVs produce zero tailpipe emissions, helping to improve public health and environmental conditions. These combined physical and societal factors form the foundation for the increasing prominence of electric vehicles in modern transportation systems.

### Aim and Structure

The aim of this chapter is to provide a comprehensive understanding of the core physical principles underlying electric vehicles, focusing on three main areas: batteries, propulsion systems, and battery management systems (BMS). One can explore the fundamental electrochemical processes in batteries, including cell structure and energy storage mechanisms, as well as key characteristics of lithium-ion chemistries relevant to EV applications. The propulsion section covers the electromagnetic basis of electric motors, power electronics, and the energy flow within the EV powertrain, highlighting efficiency considerations. Finally, the BMS section explains the critical functions of monitoring, protection, state estimation, and thermal management that ensure safe, reliable, and efficient battery operation.

The chapter integrates principles from physical science disciplines such as chemistry, electromagnetism, and thermodynamics into the context of modern electric vehicle technology. By linking theoretical concepts with practical applications in EVs, it demonstrates how fundamental science drives innovation in

sustainable transportation. The detailed exploration of energy conversion, storage, and management aligns with the textbook's broader aim to illustrate the role of physical science in solving real-world engineering challenges and advancing emerging technologies.

## EV Powertrain and Energy Flow Basics

### 1. EV Architectures and Main Components

The fundamental architecture of an electric vehicle (EV) powertrain can be represented by a simple block diagram illustrating the flow of energy and control signals between key components. Starting from the battery, which serves as the primary energy storage device, electrical energy is supplied to the power electronics. The power electronics system, comprising inverters and converters, manages the conversion and conditioning of electrical energy to match the requirements of the electric motor. The motor then converts this electrical energy into mechanical energy, which drives the wheels to propel the vehicle. Additionally, the system includes a charger that facilitates energy input from the external power grid to recharge the battery, as well as auxiliary systems that support vehicle operation, such as thermal management and control units.






***Figure: Block diagram of Electric Vehicle Powertrain***

### 2. Energy Flow and Efficiency

Efficiency in the grid-to-wheel energy flow involves multiple stages, each with inherent losses that impact the total energy delivered to the vehicle's wheels. Starting from the AC grid, energy passes through the charger, which converts AC to DC for battery storage; charger efficiency typically ranges from 85% to 95%, with losses mainly due to heat dissipation in power electronics. The battery then stores electrical energy electrochemically, with round-trip efficiencies around 90–95%,

influenced by internal resistance and chemical kinetics. The inverter converts DC back to AC to power the motor, operating at efficiencies of approximately 95–98%, with losses from switching and conduction in semiconductor devices. Finally, the electric motor converts electrical energy into mechanical energy with efficiencies often exceeding 85%, depending on motor design and operating conditions.




Regenerative braking recovers kinetic energy during vehicle deceleration by operating the motor as a generator, converting mechanical energy back into electrical energy stored in the battery. This process improves overall vehicle efficiency by reducing energy wasted as heat in traditional friction braking. However, regenerative braking efficiency is limited by factors such as battery charge acceptance rates, inverter and motor losses, and control system responsiveness, typically recovering 60–70% of the braking energy under optimal conditions.

**Physical Principles of Battery Energy Storage (≈2–2.5 pages)**

**1. Electrochemical Cell Fundamentals**

The main elements of an electrochemical cell include the anode, cathode, electrolyte, and separator, each playing a crucial role in energy storage and conversion. The anode and cathode serve as the electrodes where oxidation and reduction reactions occur, respectively, enabling the flow of electrons through an external circuit to produce electrical current. The electrolyte facilitates the movement of ions between the electrodes, maintaining charge balance while preventing direct electron flow internally. The separator physically isolates the anode and cathode to prevent short circuits while allowing ionic transport.

Ion transport within the cell occurs through the electrolyte, enabling charge carriers (typically lithium ions in lithium-ion batteries) to move from one electrode to the other during charge and discharge cycles. In contrast, electrons flow externally

through the circuit, generating usable electrical energy. This separation of ionic and electronic pathways is fundamental to the cell's operation.

The cell voltage arises from the chemical potential difference between the electrodes, reflecting the tendency of electrons to move from the anode to the cathode. This voltage can be understood qualitatively through the Nernst relation, which links the electrode potentials to the concentrations (or activities) of reactants and products involved in the electrochemical reactions. The open-circuit voltage (OCV) of the cell varies with the state of charge (SOC), as changes in ion concentration and electrode composition alter the chemical potentials, providing a measurable indicator of the battery's charge level without current flow.

## 2. Lithium-Ion Batteries for EVs


Typical lithium-ion battery chemistries used in electric vehicles include nickel manganese cobalt oxide (NMC) and lithium iron phosphate (LFP), each exhibiting distinct physical characteristics that influence performance. NMC batteries generally offer higher nominal voltages, typically around 3.6 to 3.7 volts per cell, and greater energy density, which translates to longer driving ranges for EVs. However, they tend to have more complex thermal behavior, requiring sophisticated thermal management to maintain safety and longevity. In contrast, LFP batteries have a slightly lower nominal voltage, around 3.2 to 3.3 volts per cell, and lower energy density, but they provide enhanced thermal stability and longer cycle life, making them more tolerant to high temperatures and reducing safety risks.

Internal resistance is a critical parameter affecting battery performance and efficiency. It arises from ionic resistance within the electrolyte, electronic resistance in the electrodes, and interfacial resistances at electrode–electrolyte boundaries. Higher internal resistance leads to greater voltage drops under load, reducing the effective voltage available for propulsion and causing increased heat generation. This resistance varies with state of charge (SOC), temperature, and battery age, influencing the voltage–SOC relationship that is fundamental for accurate state estimation and battery management.

The voltage–SOC behavior reflects how the cell voltage changes as the battery charges and discharges. Typically, voltage decreases gradually with SOC depletion, but the exact profile depends on chemistry. NMC cells often exhibit a relatively flat voltage plateau over a broad SOC range, which is advantageous for stable power delivery, whereas LFP cells show a more pronounced voltage plateau near mid-SOC levels, requiring careful calibration in battery management systems to ensure accurate SOC estimation.

Rate capability refers to the battery's ability to charge and discharge at different current rates without significant performance degradation. High-rate operation can induce polarization effects and increase internal resistance temporarily, leading to voltage drops and elevated temperatures. NMC chemistries generally support higher

rate capabilities compared to LFP, enabling faster acceleration and charging, but at the cost of increased thermal management demands. Understanding these physical differences helps optimize battery selection and system design for specific EV performance and safety requirements.




Lithium battery charging curve

### 3. From Cell to Pack: Electrical and Thermal Aspects

In an electric vehicle battery pack, cells are connected in series and parallel configurations to achieve the desired voltage and capacity levels. Series connections increase the overall pack voltage by adding the voltages of individual cells, while parallel connections increase the total capacity and current capability by combining the capacities of cells at the same voltage. This modular arrangement allows customization of battery packs for different vehicle power and range requirements.

Cell balancing is essential because individual cells within a pack can exhibit variations in capacity, internal resistance, and state of charge due to manufacturing differences, aging, and operating conditions. Without balancing, these disparities can cause some cells to overcharge or overdischarge, risking reduced performance, safety hazards, and shortened battery life. Balancing circuits redistribute charge among cells or limit charging to ensure uniform voltage and SOC levels, thereby enhancing pack reliability and longevity.

Heat generation in battery packs arises primarily from two sources: Joule heating and reaction heat. Joule heating occurs due to the internal resistance of cells as current flows during charge and discharge, producing heat proportional to the square of the current ($I^2R$ losses). Reaction heat is generated from exothermic or endothermic electrochemical reactions within the cells during operation. Accumulated heat can degrade battery materials, reduce efficiency, and pose safety risks, making effective thermal management critical. Cooling systems, such as air or liquid cooling, are employed to dissipate heat, maintain optimal operating temperatures, and ensure safe and efficient battery performance.

**Electric Propulsion and Power Electronics**

## 1. Electromagnetic Basis of Electric Motors

Electric motors generate torque through the Lorentz force, which arises when a current-carrying conductor is placed within a magnetic field. The interaction between the magnetic field and the electric current produces a force perpendicular to both, creating rotational motion in the motor's rotor. This fundamental principle underpins the conversion of electrical energy into mechanical torque.

The relationship between torque and current in an electric motor is generally linear, meaning that torque increases proportionally with the current supplied to the motor windings. Similarly, the motor's speed is related to the voltage applied; as voltage increases, the motor spins faster, up to its design limits. These simple torque–current and speed–voltage relationships form the basis for controlling motor performance in electric vehicles.

Two main types of electric motors commonly used in EVs are permanent magnet synchronous motors (PMSM) and induction motors. PMSMs use permanent magnets embedded in the rotor to create a constant magnetic field, resulting in high efficiency, high torque density, and precise control. Induction motors, on the other hand, generate the rotor magnetic field through electromagnetic induction from the stator currents, offering robustness and lower cost but typically slightly lower efficiency. Both motor types are integral to EV propulsion, with their selection depending on specific performance, cost, and application requirements.

## 2. Role of Power Electronics

Power electronics plays a central role in an electric vehicle by controlling the flow and conversion of electrical energy between the battery, motor, charging system, and auxiliary loads. Since the battery supplies direct current (DC), while many traction motors require controlled alternating current (AC), an inverter is used as a DC–AC converter. The inverter uses semiconductor switching devices to produce a controlled AC voltage and current, allowing precise regulation of motor speed and torque. During regenerative braking, the direction of energy flow is reversed, and electrical energy generated by the motor is transferred back to the battery.

DC–DC converters are used to adapt the battery voltage to the requirements of low-voltage auxiliary systems such as lighting, electronic control units, sensors, and communication systems. Both inverters and DC–DC converters rely on semiconductor devices such as MOSFETs and IGBTs, which operate through rapid switching between ON and OFF states. In practical operation, these devices experience conduction losses when current flows through them and switching losses during transitions between states. These losses appear mainly as heat and influence the efficiency and thermal requirements of the power electronics system. Therefore, efficient power electronics is essential for minimizing energy losses while providing accurate control of the EV powertrain. The overall performance of the vehicle

depends on the combined efficiency of the battery, power converters, motor, and mechanical drivetrain.


**Battery Management Systems: Core Functions and Physical Basis**

**1. Why a BMS Is Needed**

An EV battery pack consists of many individual electrochemical cells connected in series and parallel. Although the cells are designed to operate together, variations in cell capacity, internal resistance, and temperature can occur. A Battery Management System (BMS) is therefore required to monitor and control the battery so that it operates within safe electrical and thermal limits.

The BMS provides protection against excessive voltage, current, and temperature. These limits are directly related to the physical and electrochemical behavior of the battery cells. Excessive charging voltage can cause undesirable chemical reactions, while deep discharge can damage the cell and reduce its usable capacity. Similarly, high current produces heat due to internal resistance, approximately expressed as P=I2RP=I^2RP=I2R. By monitoring these conditions, the BMS prevents unsafe operation.

In addition to protection, the BMS helps maximize the usable energy and power available from the battery. It may limit charging, discharging, or regenerative braking when the battery is operating under unfavorable conditions, such as very high or low temperatures. The BMS also contributes to battery lifetime by avoiding operating conditions that accelerate degradation, including excessive temperature, high charging rates, and prolonged operation at extreme states of charge. Thus, the BMS provides a balance between safety, performance, and battery life.




**2. Sensing and Protection**

The BMS continuously monitors important battery parameters, including individual cell voltage, pack current, and cell or module temperature. Cell voltage measurement is particularly important because the condition of one cell can affect

the safe operating range of the entire battery pack. Current measurement provides information about the rate of charging and discharging and is also required for estimating the amount of charge remaining in the battery.

Current can be measured using a shunt resistor, where the voltage drop across a known resistance is used to determine current according to I=V/RI=V/RI=V/R, or by using Hall-effect sensors that detect the magnetic field produced by current flow. Temperature is commonly measured using thermistors or similar sensors. Temperature monitoring is essential because battery resistance, electrochemical reaction rates, charging capability, and degradation are strongly influenced by temperature.

Based on these measurements, the BMS provides protection against overvoltage, undervoltage, overcurrent, short circuit, overtemperature, and unsuitable low-temperature conditions. When a limit is approached or exceeded, the BMS may reduce the allowable power, issue a warning, stop charging or discharging, or disconnect the battery using contactors. These protection thresholds are selected according to the safe operating limits of the specific cell chemistry and battery design.

### 3. State Estimation: SOC and SOH

The BMS must estimate the internal condition of the battery because important parameters cannot be measured directly. Two of the most important quantities are the State of Charge (SOC) and State of Health (SOH). SOC represents the amount of usable charge remaining in the battery and is often expressed as a percentage. One basic method of estimating SOC is coulomb counting, in which the current flowing into or out of the battery is integrated over time. However, measurement errors can accumulate, so voltage information and other battery characteristics are often used to improve the estimate.

SOH indicates the condition of the battery relative to its original or reference condition. As a battery ages, its available capacity generally decreases and its internal resistance tends to increase. These changes affect both driving range and power capability. The BMS can use simplified equivalent circuit models, which represent the battery using combinations of voltage sources, resistances, and capacitive elements, to describe its electrical behavior. Filtering and estimation techniques can then combine measured voltage, current, and temperature data to provide improved estimates of SOC and SOH without directly measuring these internal states.


## Thermal and Charging Management


### 1. Battery Thermal Management

Temperature has a significant influence on battery performance, safety, and lifetime. At low temperatures, electrochemical reactions become slower and internal

resistance increases, reducing the battery's ability to deliver and accept power. At high temperatures, unwanted chemical reactions and degradation processes can accelerate. Therefore, effective thermal management is necessary to maintain the battery within a suitable operating temperature range and to ensure that the cells remain at relatively uniform temperatures.

Battery cooling systems commonly use either air or liquid cooling. Air cooling is relatively simple, lightweight, and inexpensive, but its heat-transfer capability is limited. Liquid cooling provides more effective heat removal and better temperature uniformity, making it suitable for high-power EV battery packs, although it requires additional components and greater system complexity. The effectiveness of thermal management depends on the thermal path between the cell and the cooling medium. Materials and interfaces with low thermal resistance allow heat to move more easily away from the battery, reducing temperature rise during high-power operation and charging.




## 2. Charging Profiles and Limits

Charging an EV battery requires careful control because the electrochemical processes inside the cells impose limits on the charging rate. Lithium-ion batteries are commonly charged using a Constant-Current/Constant-Voltage (CC–CV) profile. Initially, the battery is charged with a controlled constant current, causing the cell voltage to gradually increase. When the upper voltage limit is reached, the

charger maintains a nearly constant voltage while the charging current gradually decreases.

The maximum charging rate is limited by factors such as temperature, internal resistance, battery state of charge, and electrochemical reaction rates. High charging currents increase heat generation and may accelerate degradation. Under certain conditions, particularly at low temperatures or very high charging rates, lithium plating can occur at the negative electrode, potentially reducing battery capacity and affecting safety. Fast charging reduces charging time but generally increases thermal and electrochemical stress compared with normal charging. Therefore, the BMS continuously adjusts the allowable charging power according to the battery's operating condition to achieve a balance between charging speed, safety, and long-term battery life.

**Outlook: Towards Intelligent Mobility**

**1. Smarter BMS and Connected EVs**

The development of EV technology is leading to increasingly intelligent Battery Management Systems. Traditional BMS designs primarily relied on fixed threshold-based protection, whereas modern systems increasingly use model-based and data-driven approaches to estimate battery condition and predict future behavior. These advanced methods can improve the estimation of SOC and SOH, detect abnormal conditions at an early stage, optimize charging, and support predictive maintenance.

EVs are also becoming part of a broader energy and transportation ecosystem. Smart charging can coordinate vehicle charging with electricity demand and renewable energy availability. Technologies such as vehicle-to-grid (V2G) can potentially allow EV batteries to supply electrical energy back to the grid when required. As EVs become connected with smart grids, renewable energy systems, and autonomous transportation technologies, the vehicle is increasingly viewed not only as a means of transportation but also as a flexible energy resource within an intelligent mobility system.

**2. Key Takeaways**

Electric vehicles demonstrate how fundamental principles of physical science are applied to modern transportation technology. Batteries function as electrochemical energy storage systems, converting chemical energy into electrical energy during discharge and storing electrical energy during charging. Electric motors and power electronics act as electromagnetic and electrical energy converters, transforming electrical energy into mechanical motion and enabling controlled energy flow during propulsion and regenerative braking.

The Battery Management System serves as the intelligent control system of the battery pack by monitoring voltage, current, and temperature while managing safety, performance, and battery lifetime. Thermal management and charging

control further demonstrate the importance of heat transfer, electrochemistry, electrical resistance, and material behavior in practical EV operation. Together, these concepts illustrate how principles from electromagnetism, thermodynamics, electrochemistry, materials science, electronics, and control systems are integrated to create efficient and intelligent mobility technologies.

***References***


1. Hannan, M. A., Lipu, M. S. H., Hussain, A., & Mohamed, A. (2018). A review of lithium-ion battery state of charge estimation and management system in electric vehicle applications. Renewable and Sustainable Energy Reviews, 78, 834–854.
2. Krishna, T. N. V., Kumar, S. V. S. V. P. D., Srinivasa Rao, S., & Chang, L. (2024). Powering the future: Advanced battery management systems (BMS) for electric vehicles. Energies, 17, 3360. (Battery Energy Storage Systems for Electric Vehicles - AIP Publishing, 2025)
3. Baldini, A. et al. (2025). Battery Management System for Electric Vehicles: Comprehensive review of circuitry configuration and algorithms. Technologies, 13(2), 19. (Battery Energy Storage Systems for Electric Vehicles - AIP Publishing, 2025)
4. Challoob, A. et al. (2026). Energy and battery management systems for electrical vehicles: A comprehensive review and recommendations. [Preprint / Journal article]. (Gnanasekaran et al., 2023)
5. Zhang, K. et al. (2025). A concise review of power batteries and battery management systems for electric and hybrid vehicles. Journal / Preprint.
6. Piller, S., Perrin, M., & Jossen, A. (2001). Methods for state-of-charge determination and their applications. Journal of Power Sources, 96(1), 113–120.
7. Bashash, S., Fathy, H. K. (2011). Modeling and control of plug-in hybrid electric vehicles for power grid support. IEEE Transactions on Control Systems Technology, 19(3), 593–603.
8. Chan, C. C., & Wong, Y. S. (2004). Electric vehicles charge forward. IEEE Power and Energy Magazine, 2(6), 24–33.
9. Liu, H., & Mi, C. (2021). Power Electronics for Electric Vehicles and Energy Storage. CRC Press. (Kishan et al., 2023)
10. Buja, G., Bertoluzzo, M., & Kormendi, D. (2016). Control strategies for road vehicles electrification. IEEE Transactions on Vehicle Technology, 64(5), 1706–1719.

**Physical Science: From Fundamental Principles to Modern Applications**
**ISBN: 978-81-69492-07-2| Year: 2026 | pp: 53 - 57**

# Physical Science: From Fundamental Principles to Modern Applications

**Dr. G. D. Jemi**

Associate Professor, VSB Engineering College, Karur

**Email:** gdjemi@gmail.com

Article DOI Link: https://zenodo.org/uploads/22047353

DOI: 10.5281/zenodo.22047353

**Abstract**

Physical science is the study of matter, energy, and the rules that connect them. It covers mechanics, heat, light, electricity, and even the tiny world of atoms. These ideas are not just theory. They shape the phones we use, the cars we drive, and the hospitals that keep us alive. This paper looks at some basic laws of physics and shows how they turn into real tools we use every day. It also looks at where this field might go next.

***Keywords:*** Mechanics, thermodynamics, electromagnetism, optics, applied science.


## Introduction

Physical science starts with simple questions. Why does a ball fall? Why does metal get hot when you rub it? Scientists like Newton, Faraday, and Einstein spent their lives trying to answer questions like these. Over time, their answers turned into laws. Laws turned into machines and machines changed the world we live in.A lot of students learn physics as formulas on a page.

F equals ma. E equals mc squared. But these formulas are not just for exams. They run bridges, MRI machines, engines, and even the internet. This paper tries to connect the dots between the classroom and the real world, one topic at a time.

## Mechanics and Structural Engineering

Mechanics is the oldest branch of physics. It deals with forces, motion, and balance. One of its biggest real-world jobs is holding up bridges. A suspension bridge looks simple from far away, just cables and a road. But every cable is carrying a load calculated using tension, weight, and gravity. Engineers use Newton's laws to make sure the bridge does not fall under its own weight, or under traffic, or under wind. Without mechanics, none of these structures would stand for more than a day.




**Electromagnetism in Medicine**

Electricity and magnetism used to be two separate topics until scientists found out they are actually linked. This discovery changed medicine forever. Take the MRI machine. Inside it is a huge electromagnet, way stronger than any fridge magnet you have seen. It lines up hydrogen atoms in your body using a magnetic field, then reads how they react. Doctors get a full picture of your insides without cutting you open. This machine only exists because someone understood how electric current creates a magnetic field.



**Thermodynamics and Engines**

Thermodynamics studies heat and how it moves. It sounds boring until you realize your car would not move an inch without it. Inside an engine, fuel burns and creates heat. That heat expands gas, and the gaspushesapiston. This push turns into the spin of your wheels. It is basically controlled explosions happening again and again,

guided by the laws of thermodynamics. The same ideas run refrigerators, air conditioners, and power plants too.



**Optics and the Internet**

Light does not just help us see, it also carries information. This is the whole idea behind fiber optic cables. Inside a fiber optic wire, light bounces along a thin glass strand using total internal reflection, a fairly basic idea from optics. That bouncing light carries data across oceans in seconds. Every video call, every website, every message you send probably passed through a glass wire thinner than a hair, just because light knows how to bend and bounce the right way.



**Semiconductors and Solar Energy**

Not all physics happens with big machines. Some of it happens inside tiny slices of silicon. Solar panels work because of the photoelectric effect, the same idea

Einstein won his Nobel Prize for. Light hits a semiconductor, knocks electrons loose, and that movement of electrons becomes electric current. This one small idea now powers homes, satellites, and even calculators sitting in a drawer somewhere.



**Future Work**

Physics is not done yet, not even close. Quantum computers are being built right now using ideas that barely existed thirty years ago. Scientists are also working on fusion energy, trying to copy what stars do inside a lab on Earth. Nanotechnology is shrinking machines down to sizes we cannot even see with a normal microscope. Future research should focus on making these ideas cheaper and easier to build at scale. A lot of physics works fine in a lab but struggles once it needs to reach millions of people. That gap between lab and life is where a lot of future work needs to happen.

**Conclusion**

Physical science is not stuck in textbooks. It is in the bridge you drive over, the hospital scan that finds a tumor, the engine under your car, the internet you are using right now, and the panel on your neighbor's roof. Fundamental laws written down decades or even centuries ago are still running the modern world.

***References***

1. Halliday, D., Resnick, R., & Walker, J. Fundamentals of Physics. Wiley.
2. Kleppner, D., & Kolenkow, R. An Introduction to Mechanics. Cambridge University Press.
3. Cengel, Y. A., & Boles, M. A. Thermodynamics: An Engineering Approach. McGraw Hill.
4. Zemansky, M. W., & Dittman, R. H. Heat and Thermodynamics. McGraw-Hill.
5. Griffiths, D. J. Introduction to Electrodynamics. Cambridge University Press.

6. Sadiku, M. N. O. Elements of Electromagnetics. Oxford University Press.
7. Griffiths, D. J. Introduction to Quantum Mechanics. Cambridge University Press.
8. Sakurai, J. J., & Napolitano, J. Modern Quantum Mechanics. Cambridge University Press.
9. Einstein, A. Relativity: The Special and the General Theory. Crown Publishers.
10. Hartle, J. B. Gravity: An Introduction to Einstein's General Relativity. Addison-Wesley.
11. Serway, R. A., & Jewett, J. W. Physics for Scientists and Engineers. Cengage.
12. Tipler, P. A., & Mosca, G. Physics for Scientists and Engineers. W.H. Freeman

**Physical Science: From Fundamental Principles to Modern Applications**
**ISBN: 978-81-69492-07-2| Year: 2026 | pp: 58 - 76**

# Green Synthesis, Characterization and Biological Studied of Gold Nanoparticles from Various Plant Extracts

**D.T. Sakhare**

U.G, P.G. & Research Centre, Department of Chemistry, Shivaji, Art's, Comm. & Science College Kannad. Dist. Chhatrapti Sambhajinagar.431103, (M.S.) India

**Email:** sakharedhondiram@yahoo.com

Article DOI Link: https://zenodo.org/uploads/22047403

DOI: 10.5281/zenodo.22047403

**Abstract**

Nanotechnology is a trending area in research field for studying particles at nano scales and it is used over conventional methods and gives size dependent parcels of the functional accoutrements. The present review includes study on green technology for the synthesis of gold nanoparticles from various extracts of different plant parts. The green nanotechnology field that provides sustainability in various implementations. The nanomaterial synthesis using conventional nanotechnology involves the release of poisonous nanomaterials that creates the issue of nanotoxicity but the green nanotechnology helps in derogation of the risk and hazards due to the same. The gold nanoparticles using plants extracts because of their diversity, sustainability and eco-friendly nature. It is concluded that gold nanoparticles synthesized using plants extract such as leaf, root, seed and fruit extracts have antioxidant and antimicrobial activity. Due to their SPR frequency, biocompatibility and tunable property gold nanoparticles has great application in cancer treatment, biosensor, drug delivery and enhancement of plant growth.

***Keywords:*** Green chemistry, green analytical chemistry, clean chemistry, atom economy, sustainable development.

## Introduction


The nanotechnology sector has proven to be one of the most active research fields [1]. Owing to their broad uses in catalysis, sensing, electronics, photonics and medicines, the synthesis of nanoparticles has gained significant attention in recent decades [2]. Scientists have understood the potential of biological organisms to reduce metal precursors since the nineteenth century, but the mechanisms are still not known. Researchers have drawn attention towards biological methods due to the

success of nanoparticle synthesis using natural reduction, capping and stabilizing agents, and avoiding harmful chemicals and high energy consumption [3]. A wide variety of products (e.g., Quantum dots (Q-dots) of cadmium sulphide, titanium oxide hybrid-based electrochemical biosensors and oxorubicin-loaded heparinized nanoparticles) can be developed through nanotechnology, and applicable to a broad array of scientific fields, including optoelectronics, biosensors, nano-biotechnology, biomedicine and others [4]. Creation, exploitation and synthesis are nanotechnology concepts that typically consider materials smaller than 1 mm in dimension [5]. Many different methods, such as physical, chemical and green (biological) techniques, have been used to synthesize nanoparticles [6]. The stabilized nanoparticles are formed by reducing ions through reduction (palladium NPs), nucleation (silver NPs) and growth system (silver NPs) [7]. Green chemistry, which uses chemical principles to reduce or eliminate the use of hazardous substances, has led to considerable reductions in toxic residues, which are harmful to man and the environment.

Green chemistry may be defined as chemical-assisted pollution-prevention strategies employed in specific domains such as green analytical chemistry, ecologically friendly analytical chemistry and clean analytical methodologies [8]. Thus, green synthesis is regarded as a viable approach for nanoparticle synthesis since it is biocompatible, inert and environmentally safe [9].

## 1. Different Types of Nanotechnologies

In general, the three types of nanotechnologies are wet, dry and computational. Wet nanotechnology is concerned with the investigation of living organisms and their components such as tissues, enzymes and membranes that are predominantly found in water-based systems.




***Fig, 1. Different types of nanotechnologies.***

Physical chemistry and inorganic compounds such as carbon and silicon are associated with dry nanotechnology. On the other hand, computational nanotechnology is associated with simulations of nanometer-sized components [10]. The three nanotechnologies, viz., wet, dry and computational, are interdependent for optimal functionality (Figure 1).

## 2. Biosynthesis of Novel Metal Nanoparticles Using Plant Extracts

Nanoparticles with sizes ranging from 1 to 100 nm bind larger particles to atomic or molecular structures. They are synthesized via different approaches, mainly divided into physical and chemical processes (Figure 2). The physical process involves laser ablation, condensation, evaporation, etc., whereas the chemical process involves hydrazine, sodium borohydride, green synthesis, etc. Using plant species to produce nanoparticles has been termed a green technique (Figures 2 and 3) and the most reliable environmentally sustainable approach. Nowadays, researchers are attracted towards biological synthesis, including the use of natural reducing, capping and stabilizing agents and without using hazardous, high-cost chemicals and high-power consumption [11] (Figures 2). NPs are extensively utilized in human contact areas (medicine and agriculture, and synthesis methods that do not use harmful compounds are increasingly required.





***Fig.2 Different methods of nanoparticle synthesis.***

## 3. Green Nanotechnology

Green nanotechnology is related to the field that provides sustainability in various implementations. The main aim of it is the development of non-threating methods

for the NPs synthesis. The nanomaterial synthesis involves the release of poisonous nanomaterials that creates the issue of nanotoxicity, the green nanotechnology helps in derogation of the risk and hazards due to the same. It pursuit to the evaluate the synthetic styles that help to reduce the use of toxic chemicals with intensifying the capability of current synthesis techniques. Green nanotechnology concern with the production of green products. Green products are those whose synthesis start from nontoxic precursor, use of natural source as raw material, involve less energy consumption, use of green solvents and no toxic disposal. The aim of green nanotechnology is to develop environment friendly nanoparticles, develop green methods for large scale nanoparticle production, discover efficient approaches for using nanoparticles in the development of novel nano-devices [12].

## 4. Why We Use Green Nanotechnology

There is an increasing problem of environmental pollution in today's world due to humanistic activities. Something which is greener and cleaner is more preferable. Green nano-products can be directly applied to check damage from known adulterants and incorporation into environmental technologies can remediate unsafe waste sites, treat pollutants, plant pathogens and related toxins, sense and examiner environmental adulterants, and clean and desalinate weakened water. We prefer green nanotechnology because it provides safe and energy efficient products, reduction in waste and greenhouse gas emissions and involve the use of renewable materials [13].





***Fig. 3. Principles of Green Chemistry on which Green Nanotechnology Based***

Green nanotechnology work on the 12 principles of green chemistry (shown in Figure 3.) such as to design new nanomaterials to achieve economic, social, health, and environmental benefits. The principles of green chemistry impeccably apply to green nanotechnology and nano-manufacturing processes to produce safe, cleaner and more sustainable nanomaterials."

## 5. Gold Nanoparticles

Gold is the quintessential noble element. In its bulk shape, gold's uses in jewellery, coinage, and electronics are widely recognized. Gold nanoparticles (Au NPs) have attracted extensive attention in the last decades due to their unique catalytic, photo physical and electronic properties. Au NPs of various shapes and sizes can be synthesized by adopting different methods (physical, chemical and biological). The Au nanospheres were primary accomplishment in the field of Au NPs, while they were not perfectly spherical. Surfactant, polymers, pharmaceuticals, DNA, RNA, proteins and oligonucleotides are some of the functionalizing agents with which Au NPs can be conjugated [14]. They have broad applications in the fields of environment sensing, electronics, biomedicine and fine chemical synthesis. Because of their multivalency, gold nanoparticles can shield unstable medicines or inadequately soluble imaging contrast agents and facilitate their effective delivery to else inapproachable regions of the body. Optical property of gold nanoparticles helps us to construct optical biosensors such as optical biosensor, electrochemical biosensor and piezoelectric biosensor [15].

The objective of my study is to describe the green synthesis of gold nanoparticles using plants and their biological applications.

## Techniques For Gold Nanoparticle Synthesis

There are different methods for Au NPs synthesis as shown in Figure 2.

## 1. Top-Down and Bottom-Up Approach

Au NPs can be synthesized by two techniques: top-down approach and bottom-up approach. In top-down approach, a suitable starting molecule is reduced in size, better known as 'modules. Top-down approach includes different physical methods for synthesizing nanoparticles. Different physical methods for nanoparticle synthesis are, molecular beam emphasis, sputter deposition, laser desorption, diffusion flame synthesis, milling method, laser ablation and lithographic techniques etc. In bottom-up approach, the nanoparticles are initially prepared and latterly assembled into final materials by chemicals or biological procedures of synthesis. The bottom-up technique offers the advantage of improving the likelihood of creating nanoparticles with fewer flaws and more uniform chemical compositions. Bottom-up approach includes chemical and biological methods to synthesize gold nanoparticles. Different chemical methods for synthesizing nanoparticles are electro deposition, sol–gel process, chemical vapour deposition

soft chemical method, Langmuir Blodgett method, co-precipitation method [16] and wet chemical method. Biological methods involve plants and microorganisms such as algae, virus, bacteria, fungi etc.





***Figure 2. Different Methods of Nanoparticle Synthesis***

## 2. Why we Choose Biological Method for Gold NPs Synthesis

In physical and chemical methods, there is a problem about the control of crystal growth, size and size distribution, stability and aggregation of NPs. Due to different drawbacks of chemical and physical methods, biological approach for synthesizing NPs have been increasing. Biological methods are based on green technology aimed at overcoming negative effects on environment. Biological approach utilizes biological materials as reducing bioactive agents, isolated from microorganisms and plants that are eco-friendly, prevent pollution and no production of waste, effective synthesis and additional energy saving and its economical production of NPs is also very important.

In the biological approach bacteria, yeasts, fungi, algae and plants, etc. may be used for producing green NPs at high scale because they contain reducing and capping agent. In biological methods there is use of non-toxic capping agent, less hazardous reducing agent, and environment friendly solvent, no need of high temperature calcination for the production of final product, non-toxic organic solvents are used,

methods that used plants can be suitably settled for large scale production of nano-particles [17].

### 3. Why Plants are Best Agents

From all biological entities plants are the best agent because of their diversity, sustainability, and their waste are also eco-friendly. By using plants, it is easier to maintain cell culture and can also be appropriately settled up for large scale production of nanoparticles. Plants can reduce metal ions faster than fungi or bacteria. The plant mediated nanoparticles are more diverse in size and shape comparatively to those produced by other organisms.

Biomolecules of plant extracts can be used in single step synthesis of NPs by reducing metal ions to NPs. Plants extract act both as reducing and capping agents for synthesizing nanoparticle. The biomolecules like vitamins, proteins, alkaloids, polysaccharides, amino acids, and organic acids such as citrates that are present in plant extract help in bioreduction of MNPs. We can faster synthesis rate by using plant extracts of high production capability and increasing the reaction temperature. We can also control particle size and shape by changing the plant type or temperature and composition of the reaction mixture [18].

### General Mechanism for Green Synthesis of Nanoparticles from Plants

There are many researches about synthesis of nanoparticles from plants. The general mechanism for synthesis of nanoparticles from plants is presented in Figure 3. For synthesis of nanoparticles there are three steps: activation, growth and termination.

- **Activation:** Firstly, plant parts (fruits, leaves, stems, roots) are washed with distilled water and small pieces are boiled to make the extraction and then mixed with solution of metal ion. Plant extracts comprise bioactive agents such as phenolic acids, sugars, polyphenols, terpenoids, proteins, alkaloids, etc., that firstly reduce the metallic ions and then stabilize them. The metal ions are reduced by biomolecules present in plant extract. The metal salts are converted to metal nanoparticles by oxidation-reduction mechanisms. Therefore, the metals are converted to nanoscale zero-valent metallic particles [19].
- **Growth Phase:** After the formation of nanoscale metallic particles nucleation takes place. The separated metal atoms congregate to form metal NPs and again biological reduction of metal ions takes place. Along with the process of nucleation, nanoparticles combine to form divergent shapes like rods, cubes, triangles, pentagons, spheres.
- **Termination phase:** NPs are stabilized and capped by plant metabolites. Reduction of metal ion is indicated by change in culture colour. In this final step nanoparticles obtain their optimistic and stable morphologies.





***Figure 3. Mechanism for Synthesis of Nanoparticles from Plants***

Different plant parts like fruits, leaves, stems, roots and their extracts have been used for different metal nanoparticles synthesis. Many exemplifications are given in Table 2.

***Table 2. Synthesis of Different Nanoparticles Using Various Plant Parts and their Activities***

| Sr. No. | Plans | Plant part used | Nanoparticles | Activity of Nanoparticles | Reference |
|---|---|---|---|---|---|
| 1 | *Acalypha indica* | Leaves | Ag | Antimicrobial activity | [20] |
| 2 | *Amaranthus dubius* | Leaves | Fe | Photocatalytic and Antioxidant activity | [21] |
| 3 | *Asparagus adscendens* | Root & Leaves | Cu | Antimicrobial activity | [22] |
| 4 | *Berberis asiatica* | Roots | Ag | Antimicrobial activity | [23] |
| 5 | *Catharanthus roseus* | Leaves | Ag | Antiplasmodial activity | [24] |

| | | | | | |
|---|---|---|---|---|---|
| 6 | *Celastrus paniculatus* | Leaves | Cu | Photocatalytic and antifungal activity | [25] |
| 7 | *Cleome viscosa* | Fruit | Ag | Antibacterial and anticancer Activity | [26] |
| 8 | *Coleus aromaticus* | Leaves | Ag | Bactericidal activity | [27] |
| 9 | *Cuminum cyminum* | Seed | Cu | Antimicrobial activity | [28] |
| 10 | *Desmodium gangeticum* | Root | Cu | Antimicrobial activity | [29] |
| 11 | *Diospyros paniculata* | Root | Ag | Antimicrobial activity | [30] |
| 12 | *Euphorbia esula* | Leaves | Cu | Catalytic activity | [31] |
| 13 | *Glycyrrhiza glabra* | Root | Ag | Anti-ulcer activity | [32] |
| 14 | *Lagenaria Siceraria* | Leaves | Fe-oxide | Antimicrobial Activity | [33] |
| 15 | *Lantana camara* | Fruit | Ag | Antimicrobial Activity | [34] |
| 16 | *Lawsonia inermis* | Leaves | Fe | Antimicrobial Activity | [35] |
| 17 | *Magnolia kobus* | Leaves | Cu | Antimicrobial Activity | [36] |
| 18 | *Malus domestica* | Fruit | Ag | Antimicrobial Activity | [37] |
| 19 | *Moringa oleifera* | Seed | Fe | Antimicrobial Activity | [38] |
| 20 | *Persea americana* | Seed | Cu | Antimicrobial Activity | [39] |
| 21 | *Piper nigrum* | Seed | $SnO_2$ | Antitumor activity | [40] |
| 22 | *Punica granatum* | Seed | $Fe_2O_3$ | Photocatalyticactivity | [41] |
| 23 | *Rheum palmatum* | Root | Ag | Antibacterial activity | [42] |
| 24 | *Rheum palmatum* | Root | $CuO_2$ | Heterogeneous catalytic activity | [42] |

| | | | | | |
|---|---|---|---|---|---|
| 25 | *Tradescantia spathacea* | Leaves | $SnO_2$ | Photoantioxidant activity | [44] |
| 26 | *Trigonella foenum graecum* | Seed | Ag & Fe-oxide | Antibacterial and Antioxidant Activities | [45] |

**Green Synthesis of Gold Nanoparticles Using Various Extracts of Different Plants**

**1. By Using Leaf Extract**

Au NPs can be synthesized by the use of leaf extract of different plants. Leaf extract of *Buhinia purpurea* and HAuCl4 used to prepare gold nanoparticles. Synthesized NPs has excellent anticancer, oxidant, catalytic property. These nanoparticles act as good catalyst for reduction reaction of methylene blue and rhodamine B by NaBH4. Synthesized gold nanoparticles have anticancer activity on lung carcinoma cell line. Au NPs of average size 15.3 nm has also been synthesized using leaf extract of *Cacumen platycladi*. Synthesized NPs were of diverse morphology such as sphere, triangles. In this synthesis flavonoids and reducing sugars act both as reducing and protecting agent. Author studied the effect of temperature and pH on size of nanoparticles. Size of NPs decrease with increasing temperature and pH [46].

*Hibiscus-rosa-sinensis's* leaf extract has also been used to synthesize the gold NPs of different shapes and sizes by varying the ratio of metal salts and extract. From FTIR it was confirmed that amine group was responsible for gold NPs stabilization. Au NPs has also been synthesized using *Cerasus serrulata* leaf extract. The synthesized NPs have size in range from 5 to 25 nm and spherical in shape. *C. serrulata* contain five main compounds which help in the process of reduction. But the major groups were Butylhydroxytoluene, Hydrocoumarin and coumarin; from these coumarin is best which act as reducing and capping agent for Au NPs synthesis. The synthesized NPs show antibacterial activity against *Escherichia coli* a gram-negative bacterium.

*Magnolia kobus* has also been used for synthesizing Au NPs. Nanoplates of width 250-300 nm and thickness of 5-7 nm were formed using 5% leaf broth at 25°C and the impact of concentration and temperature on the synthesis rate and size/shape of gold NPs were studied. It was observed that rate of synthesis increases with the temperature and size of NPs decrease with increasing concentration of leaf extract. From FTIR it was confirmed that Au NPs were surrounded by some proteins and metabolites like terpenoids with numerous functional groups such as alcohols, aldehydes, amines, carboxylic acids and ketones.

*Murraya koenigii* can also be used for the conflation of gold nanoparticle. Varying concentration of leaf extracts of *M. koenigii* was added to HAuCl4.3H2O to obtain different colloids such as g1, g2, g3, g4 and g5 of different shape and size. Average

shape and size of Au NPs prepared was spherical and 20nm respectively. FTIR measurement shows that biomolecules responsible for capping and efficient stabilization in *M. koenigii* leaf are polyphenols, flavonoids and alkaloids [47].

**2. By Using Root Extract**

Au NPS of spherical shape and 10-15nm in diameter have been prepared using *Glycyrrhiza uralensis* root extract. The reduction of methylene blue with Glycyrrhiza root extract is catalysed by Au NPs that have been prepared. Catalytic activity was confirmed by the decrease in absorbance value of methylene blue in UV-Vis spectra. The in vitro cytotoxicity of Au NPs was appraised by the colour change from purple to yellow at 517nm. These Au NPs are toxic toward murine macrophage and non-toxic toward breast cancer cell lines.

Use of *Lanthana camara* Linn root extract has also been reported for synthesis of Au NPs of average size 11-32nm with spherical morphology. It was reported that N-H and O-H functional groups are responsible for reduction of Au ions to Au NPs and flavonoids for capping and stabilization of Au NPs. The *L. camara* Au NPs have dose dependent significant inhibitory effect on breast cancer cell line (MDA-MB-231) and normal cell line (Vero).

Au NPs have also been synthesized using root extract of *Morinda citrifolia*. The synthesized Au NPs were 12.17-38-26 nm in size. From FTIR spectrum, it was reported that proteins present in root extract act as reducing and capping agents. Root extract of *Trianthema decandra* has also been used for the synthesis of Au NPs. Synthesized NPs were of different shapes such as spherical, triangular, hexagonal and cubic with size ranging from 33.7 to 99.3nm. Triangular nanoparticles show excellent antibacterial activity against *Y. enterocolitica, S. faecalis*, *E. coli*, *P. vulgaris* and *S. aureus*. Hence these synthesized Au NPs can be used for treatment of human infection due to microorganisms.

Au NPs with various shapes such as triangular, spherical and hexagonal with average size 24.7nm have also been prepared using root extract of *Arctium lappa*. The author reported that synthesized NPs have significant catalytic role for detoxification of common dye Rhodamine B (RhB). Synthesized Au NPs have significant catalytic role for the degradation of 4-Nitrophenol using NaBH4 [48].

**3. By Using Seed Extract**

Au NPs synthesized from seed extract of *Abelmoschus esculentus* were of various sizes and the reason was that the nucleation and aggregation occur consecutively. FTIR shows that -OH functional group in the extract act as capping agent in NPs synthesis. The synthesized Au NPs have antifungal activity against *P. graminis*, *A. flavus, A. niger* and *C. albicans*. Hence these NPs have great potential to be used for drug preparation against fungal diseases.

Seed extract of *Benincasa hispida* has also been used for Au NPs synthesis. Different colloids were prepared using different concentrations of extract to solution

of chloroauric acid. The reduction process was fast when 35ml of extract was used against 30ml solution of chloroauric acid. The produced particles were approximately spherical in form, according to TEM image. The polyol present in seed extract help in reducing chloroauric acid and –COOH group present in protein aid in stability of Au NPs.

Polydispersed Au NPs can be synthesized using *Cuminum cyminum* seed extract. The author reported the effect of pH and temperature on morphology the NPs. Increase in temperature and pH result in the production of spherical Au NPs and triangular nano-plates obtained at lower temperature and pH.

The Au NPs synthesized from seed extract of *Terminalia chebula* has significant antimicrobial activity. Antimicrobial properties were studied using *E. coli* and *S. aureus* but TC-Au NPs shows antimicrobial activity against *S. aureus*.

Au NPs of spherical shape with average size 15.2 nm has been synthesized using *Elettaria cardamomum* seed extract. Au NPs (B3) synthesized using 10ml of extract against 30ml solution of HAuCl4 has significant antioxidant activity against DPPH, NO and OH. This radical scavenging activity enhances with increasing concentration of B3 Au NP. These NPs have effective antibacterial activity against *S. aureus, E. coli* and *P. aeruginosa*. Due to antibacterial and antimicrobial activity, Au NPs (B3) has significant application in pharmaceutical. The synthesized Au NPs has cytotoxicity aid against HeL (Human erythroleukemia) a cell lines, so it can be used for human cancer therapy [49].

**4. By Using Fruit Extract**

Polydispersed Au NPs with different shapes and average size 20nm has been synthesized using fruit extract of *Hovenia dulcis*. The synthesized Au NPs have maximum antioxidant activity. These Au NPs have radical scavenging activities for DPPH and hydrogen peroxide. These Au NPs are likewise antimicrobial against *E. coli* and *S. aureus* bacteria.

Au NPs synthesized from *Terminalia arjuna* fruit extract are predominantly spherical in morphology with 25nm average size. Tannin, saponins, terpenoid, glycosides, flavonoids and polyphenolic compounds of the fruit extract of T. arjuna act as reducing and capping agents for Au NPs's synthesis. TA-Au NPs helps to improve seed germination and plant vegetative growth of seedling of *Gloriosa superba.*

Au NPs of sizes 5 to 10nm can be synthesized using *Lycopersicon esculentum* (Tomato) fruit extract. Tomato juice contains citric acid and ascorbic acid that act as reducing agent. Tomato extract does not act as capping agent, so in this synthesis sodium dodecyl sulfate (SDS) act as capping agent. Methyl parathion can be estimated and detected by using LE-Au NPs in the presence of SDS, hence these Au NPs act as colorimetric sensor. Polydisperse and non-spherical Au NPs can be synthesized using *Mimusops elengi* fruit extract. Antibacterial activity against gram

negative bacteria (*E. coli*) and gram-positive bacteria (*S. aureus*) and antifungal activity against Aspergillus niger and *Aspergillus tubingenesis* of synthesized Au NPs has also been reported. [50].

**Biological Applications of Gold Nanoparticles**

**1. Cancer Treatment Using Photothermal Therapy**

Cancer is unregulated growth of cells which may spread to other parts of body. Due to unique property of absorption and scattering of electromagnetic radiation, high biocompatiblity and high photothermal efficiency, Au NPs are used for the treatment of cancer using photothermal method.





***Figure 4. Schematic Diagram Showing Photothermal Therapy Using Au NPs***

Biological tissue and water rarely absorb any radiation, so Au NPs with SPR frequency in near-infrared region are best source for bioimaging in locating the tumors. Surface modification of NPs are done to provide protection against aggregation, for specific interactions with cells using tumor specific agents, as well as targeted transport and accumulation in desired organs. Au NPs engulfed in tumor cell absorb radiations and convert them into heat causing hyperthermia of tumor cells leading to cell death [51].

**2. Drug Delivery**

Au NPs can also be used as vehicle for drug delivery in treatment of diseases. For drug delivery Au NPs's surfaces are modified with cationic polymers or reactive functional groups (e.g. thiol, carboxyl and amine). Drugs are adsorbed on the surface of Au NP either covalently or noncovalently. Au NP with drug entered into cell either by gene gun or by natural untaken by cell. Inside the cell Au NP release the drug, this release may be due to natural cell functioning or induced by different methods (e.g. photothermal). There are various experiments that have proven the functioning of Au NPs in drug delivery [52].





***Figure 5. Schematic Diagram for Drug Delivery Using Gold Nanoparticle***

### 3. Biosensors

Generally, sensors are used to specify the presence of analytes and read outs are used for analyte concentration determination. There is change in optical property of gold nanoparticle if optical read out is used. Cysteine-linked core-satellite Au NPs has been used for detection of Co2+spiked in diluted human serum. Au NP's biosensor has been developed for the detection of E. coli O157: H7. The bacteria were detected by measuring the electrochemical signal of Au NPs [53].

### 4. Enhancement in Plant Growth

Au NPs helps in enhancing plant growth and seed yield. In Brassica juncea Au NPs increased permeability of seed capsule, more light absorbance by chlorophyll thus fastening the photochemical reaction and increase in number of leaves. Seed yield and growth of Arabidopsis thaliana also enhanced by Au NPs. Au NPs synthesized using fruit extract of Terminalia arjuna, have significant effect on inducing seed germination and growth of Gloriosa superba plant [54].

## Conclusions

The paper article concluded that, nanotechnology deals with study of particle at nanoscale and great application in real world. Due to small-size nanoparticles have improved chemical, physical, and biological properties. Green nanotechnology that works on principles of green chemistry provides green, safe and sustainable method for nanosynthesis. There are different green methods to prepare gold nanoparticles; the present study involves synthesizes gold nanoparticles using plants extracts because of their diversity, sustainability and eco-friendly nature. It is concluded that

gold nanoparticles synthesized using plants extract such as leaf, root, seed and fruit extracts have antioxidant and antimicrobial activity. Due to their SPR frequency, biocompatibility and tunable property gold nanoparticles has great application in cancer treatment, biosensor, drug delivery and enhancement of plant growth.

***References***


1. Sakhare D.T.; Green Synthesis, Characterization of Metal Nanoparticles from Plant Extracts and Their Possible Applications as Biological Activity, Gis Science Journal, 2021,8(10), 1132-1168.
2. Korbekandi, H.; Production of nanoparticles using organisms Production of nanoparticles using organisms.Crit. Rev. Biotechnol. 2009, 29, 279–306.
3. Sakhare D.T., Suitable Biological Method for the Eco-friendly Green Synthesis of Silver & Iron Nanoparticles from Various Plants and Spices Extract. Journal of Interdisciplinary Cycle Research, 2021, 13(11), 742-759.
4. D.T. Sakhare, Synthesis of Silver Nanoparticles Using Plants Extract and Analysis of Their Antimicrobial Evaluation, World Journal of Pharmacy and Pharmaceutical Sciences, 2025, 14(8), 292-301.https://doi.org/10.20959/wjpps20258-30442
5. Sakhare D.T., Green synthesis, characterization and application of nanoparticles, International Journal of Creative Research Thoughts, 2020, 8, (6) PP. 2817-2829.
6. Sinha, S.; Pan, I.; Chanda, P.; Sen, S.K. Nanoparticles fabrication using ambient biological resources. J. Appl. Biosci. 2009, 19, 1113–1130.
7. D.T. Sakhare, Green Synthesis, Characterization and Biomedical Applications of Zn and ZnO Nanoparticles, Elixir Applied Chemistry,145(2020) 54666-54675.
8. Assistant, M.; Reddy, R.; Assistant, N.; Lemoor, T. Research Project on Green Nanotechnology Usage in Automobiles. 2016, No. 4, 5144–5156.
9. D.T. Sakhare, Green Synthesis of Silver Nanoparticles from Sarcopharyngia ventricosa, Journal of Cardiovascular Disease Research, 14(8),2023, 2315-2329.
10. Sun, L.; Liu, D.; Wang, Z. Functional Gold Nanoparticle - Peptide Complexes as CellTargeting Agents. Langmuir 2008, 24 (18), 10293–10297.
11. D.T. Sakhare, Green Synthesis, Characterization of Metal Nanoparticles from Plant Extracts and Their Possible Applications as Biological Activity, GIS Science Journal, 8(10), 2021,1132-1168
12. Sakhare D.T., Green Synthesis of Transition metal & Transitions metal oxides of Nanoparticles and their Antimicrobial Activity, Journal of Xi'an Shiyou University, Natural Science Edition, 2020,16(7), 207-237.

13. Sakhare D. T., Green Synthesis of Nanoparticles from Plant Extracts with Antiviral, Antioxidant and Antimicrobial Activity, Journal of Xi'an University of Architecture & Technology, 14(3),2022, 169-192.
14. D.T. Sakhare, Green Synthesis, Characterization and Biomedical Applications of Zn and ZnO Nanoparticles, Elixir Appl. Chem., 145(2020) ,54666-54675.
15. Sakhare D.T. Suitable Biological Method for the Eco-friendly Green Synthesis of Silver & Iron Nanoparticles from Various Plants and Spices Extract, Journal of Interdisciplinary Cycle Research,2021,13(11), 742-759.
16. Sakhare D. T., Green Synthesis, Characterization, Antimicrobial Activity and Applications of Cu, and CuO Nanoparticles. International Journal of Scientific & Engineering Research,11(6), 2020 -1471-1499.
17. D. T. Sakhare, Green Synthesis, Characterization, Antimicrobial Activity and Applications of Cu, and CuO Nanoparticles. International Journal of Scientific & Engineering Research,11(6), 2020 -1471-1499.
18. Iravani, S. Green Synthesis of Metal Nanoparticles Using Plants. Green Chem. 2011, 13 (10), 2638–2650.
19. D.T. Sakhare, Green Synthesis, Characterization and Anti-Inflammatory Activity of Silver Nanoparticle by Using Phyllanthus Emblica Leaf Extract, World Journal of Pharmaceutical Research 2025,14(16),587-597. https://doi.org/10.20959/wjpr202516-37876
20. D.T. Sakhare, Green Synthesis, Characterization and Antimicrobial Activity of Iron Nanoparticles Using Hibiscus Leaf Extract, Journal of Biotechnology and Food Engineering 2(1), 2024,310-321.
21. D.T. Sakhare, Green Synthesis, Characterization and Antimicrobial Properties of Copper Nanoparticles Using Plant Leaf Extracts, International Journal of Research Studies on Environment, Earth, and Allied Sciences, 2025, 2(5), 104-109.
22. D.T. Sakhare, Green Synthesis of Gold Nanoparticles from Various Plant Extracts and Their Biological Applications, International Journal of Advance and Applied Research,5(4),2024, 87-100.
23. M.K. Deepa, Green Synthesis of Silver Nanoparticles from Glycyrrhiza Glabra Root Extract for the Treatment of Gastric Ulcer. J. Dev. Drugs 2016, 5 (2), 152.
24. D.T. Sakhare, Recent Advances in Green Synthesis of Nanoparticles Using Plant Extracts and Their Biological activity, 'Research Journey' Innovative & Sustainable Chemistry 2023, Special Issue 333: 111-124.
25. Kanagasubbulakshmi, S.; Kadirvelu, K. Green Synthesis of Iron Oxide Nanoparticles Using Lagenaria Siceraria and Evaluation of Its Antimicrobial Activity. 2017, 2 (4), 422–427.
26. D.T. Sakhare, Green Synthesis of Transition metal & Transitions metal oxides of Nanoparticles and their Antimicrobial Activity, 2020:16 (7) 207-237. [26]. Naseem, T.; Antibacterial Activity of Green Synthesis of Iron

Nanoparticles Using Lawsonia Inermis and Gardenia Jasminoides Leaves Extract. 2015, 2015, 7.

27. D.T. Sakhare, Green synthesis, characterization and application of nanoparticles, International Journal of Creative Research Thoughts, 2020, 8(6), 2817-2829.
28. Roy, K.; Sarkar, C. K.; Ghosh, C. K. Green Synthesis of Silver Nanoparticles Using Fruit Extract of Malus Domestica and Study of Its Antimicrobial Activity. Dig. J. Nanomater. Biostructures 2014, 9 (3), 1137–1147.
29. D.T. Sakhare, Methods of Preparation and Characterization of Nanoparticles., Our Heritage Journal. 2020, 68(30),6428-6447.
30. Rajeshkumar, S.; Rinitha, G. Nanostructural Characterization of Antimicrobial and Antioxidant Copper Nanoparticles Synthesized Using Novel Persea Americana Seeds. Open Nano 2018, 3,18–27.
31. D.T. Sakhare, Suitable Biological Method for the Eco-friendly Green Synthesis of Silver & Iron Nanoparticles from Various Plants and Spices Extract, Journal of Interdisciplinary Cycle Research, 13(11), 2021, 742-759.
32. D.T. Sakhare, Green Synthesis of Gold Nanoparticles from Various Plant Extracts and Their Biological Applications, International Journal of Scientific Research in Science and Technology, 2025, 12(6),39-51.
33. D.T. Sakhare, Green Approach to Synthesis, Characterization of Silver Nanoparticles by Using Tridax Procumbens Leaf Extract and Their Antibacterial Activity, International Journal of Food and Nutrition Science, 11(11),2022,126-133.
34. Zhan, G.; Huang, J.; Lin, L. Synthesis of Gold Nanoparticles by Cacumen Platycladi Leaf Extract and Its Simulated Solution: Toward the Plant-Mediated Biosynthetic Mechanism. 2011, 13 (10), 4957–4968.
35. Song, J. Y.; Jang, H.; Kim, B. S. Biological Synthesis of Gold Nanoparticles Using Magnolia Kobus and Diopyros Kaki Leaf Extracts. 2009, 44, 1133–1138.
36. D.T. Sakhare, Green Synthesis of Transition metal & Transitions metal oxides of Nanoparticles and their Antimicrobial Activity, Journal of Xi'an Shiyou University, Natural Science Edition ,2020, 16 (7), 207-237.
37. Huo, Y.; Singh, P.; Kim, Y. J.; Soshnikova, V.; Markus, J.; Ahn, S.; Castro-aceituno, V.; Chokkalingam, M.; Bae, K.; Yang, D. C.; Huo, Y.; Singh, P.; Kim, Y. J.; Soshnikova, V. Biological Synthesis of Gold and Silver Chloride Nanoparticles by Glycyrrhiza Uralensis and in Vitro Applications. Artif. Cells, Nanomedicine, Biotechnol. 2018, 46 (2), 303–312.
38. D.T. Sakhare, Green Synthesis of Silver Nanoparticles from Sarcopharyngia ventricosa, Journal of Cardiovascular Disease Research ,14(8),2023, 2315-2329.

39. Geethalakshmi, R. and Sarada, D. V. L. Gold and Silver Nanoparticles from Trianthema Decandra: Synthesis, Characterization, and Antimicrobial Properties. Int. J. Nanomedicine2012, 7, 5375–5384.
40. D.T. Sakhare, Green Biosynthesis of Silver and Gold Nanoparticles from Plant Extracts and Their Applications as Antimicrobial Agents in Agricultural Area, Rabindra Bharati Journal of Philosophy, 23(2), 2022, 42-59.
41. Jayaseelan, C.; Ramkumar, R.; Abdul, A.; Perumal, P. Green Synthesis of Gold Nanoparticles Using Seed Aqueous Extract of Abelmoschus Esculentus and Its Antifungal Activity. Ind. Crop. Prod. 2013, 45, 423–429.
42. D.T. Sakhare, Ajuga bracteosa: A Review on Endangered Indian Medicinal Plant, European Chemical Bulletin, 2023,12(Special issue 12), 1380-1398.
43. Sneha, K.; Sathishkumar, M.; Lee, S. Y.; Bae, M. A.; Yun, Y. Biosynthesis of Au Nanoparticles Using Cumin Seed Powder Extract. J. Nanosci. Nanotechnol. 2011, 11, 1811–1814.
44. D.T. Sakhare, Green Synthesis, Characterization and Antimicrobial Activity of Copper Nanoparticles Using Syzygium Cumini Plant Leaf Extract., Conference Proceeding.2023, 141-148.
45. A. Rajan; Rajan, A. R.; Philip, D. Elettaria Cardamomum Seed Mediated Rapid Synthesis of Gold Nanoparticles and Its Biological Activities. Open Nano 2017, 2, 1–8.
46. D.T. Sakhare, Green Approach to Synthesis, Characterization of Silver Nanoparticles by Using Tridax Procumbens Leaf Extract and Their Antibacterial Activity, International Journal of Food and Nutrition Science, 11(11),2022,126-133.
47. Majumdar, M.; Biswas, S. C.; Rupasree Choudhury, P. U.; Adhikary, A.; Dijendra Nath Roy, and T. K. M.; Citrus. Synthesis of Gold Nanoparticles Using Citrus Macroptera Fruit Extract: Anti-Biofilm and Anticancer Activity. Chem. Sel. 2019, 4 (19), 5714–5723.
48. D.T. Sakhare, Green Synthesis, Characterization, Antimicrobial Activity and Applications of Cu, and CuO, Nanoparticles, International Journal of Scientific & Engineering Research, 11(6), (2020) 1471–1499.
49. Sztandera, K.; Gorzkiewicz, M.; Klajnert-Maculewicz, B. Gold Nanoparticles in Cancer Treatment. Mol. Pharm. 2019, 16 (1), 1–23.
50. D.T. Sakhare, Green Synthesis of Nanoparticles from Plant Extracts with Antiviral, Antioxidant and Antimicrobial Activity. Journal of Xi'an University of Architecture & Technology,14(3),2022, 169-192.
51. Liang, J.-J.; Wu, J.; Ding, Y. Gold Nanoparticle-Based Drug Delivery Platform for Antineoplastic Chemotherapy. Curr. Drug Metab. 2014, 15, 620–631.
52. D.T. Sakhare, Nanotechnology for Herbal Medicines and Plant Research, International Journal of Advance and Innovative Research, 8(4), 2021,5-12.

53. Wang, Y.; Alocilja, E. C. Gold Nanoparticle-Labeled Biosensor for Rapid and Sensitive Detection of Bacterial Pathogens. J. Biol. Eng. 2015, 9 (1), 1–7.
54. D.T. Sakhare, Synthesis of Silver Nanoparticles from Medicinal Plants and its iological Activities, Juni Khyat (2020) 10 (7)4, 154–168.

**Physical Science: From Fundamental Principles to Modern Applications**
**ISBN: 978-81-69492-07-2| Year: 2026 | pp: 77 - 88**

# Sensors and Smart Detection Systems

**[1]Aswini M**

**[2]S. Muthurajan**

[1]Research Scholar, Department of Electrical and Electronics Engineering, AMET University, Kanathur, Chennai-603112

[2]Assistant Professor, Department of Marine Engineering, AMET University, Kanathur, Chennai-603112

**Email:** aswinifalls@gmail.com

Article DOI Link: https://zenodo.org/uploads/22047438

DOI: 10.5281/zenodo.22047438

**Abstract**

Sensors and smart detection systems have become indispensable components of modern engineering by enabling machines and devices to observe, measure, and respond intelligently to changes in their surroundings. A sensor is a device that detects physical, chemical, or biological parameters and converts them into electrical signals that can be processed for monitoring and control. With rapid advancements in the Internet of Things (IoT), Artificial Intelligence (AI), wireless communication, and embedded systems, traditional sensors have evolved into smart detection systems capable of real-time data collection, analysis, and autonomous decision-making. These systems improve operational efficiency, enhance safety, and support predictive maintenance across various engineering applications.

A smart detection system typically integrates sensors, signal conditioning circuits, data acquisition units, communication modules, processing devices, and user interfaces into a single intelligent platform. The collected sensor data are transmitted through wired or wireless networks to local processors or cloud servers, where AI and machine learning algorithms analyze the information to identify patterns, detect abnormalities, and generate timely alerts. Such capabilities enable continuous monitoring and reduce the need for manual intervention, making these systems highly valuable in industrial automation, healthcare, environmental monitoring, transportation, agriculture, and smart city infrastructures.

Despite their significant advantages, smart detection systems also face challenges related to sensor calibration, energy consumption, cybersecurity, communication reliability, and data privacy. Continuous research is therefore focused on developing

low-power sensors, intelligent edge computing, self-powered sensing devices, digital twin technologies, and next-generation wireless communication to overcome these limitations. This chapter presents an overview of sensor fundamentals, classification, operating principles, smart detection architectures, communication technologies, major applications, current challenges, and future trends. It aims to provide students, researchers, and practicing engineers with a clear understanding of how modern sensing technologies contribute to intelligent automation and support the development of smart, connected, and sustainable engineering systems.

***Keywords:*** Sensors, Smart Detection Systems, Internet of Things (IoT), Artificial Intelligence, Wireless Sensor Networks

## Introduction

The rapid advancement of digital technologies has transformed the way modern systems interact with their surroundings. At the heart of this transformation are sensors, which act as the primary interface between the physical environment and electronic systems. Sensors detect changes in physical, chemical, or biological parameters such as temperature, pressure, light, humidity, motion, and gas concentration, and convert these changes into electrical signals that can be processed by computers or control systems. These signals provide valuable information for monitoring, analysis, and decision-making, making sensors indispensable in today's intelligent systems.





***Figure 1: General Architecture of a Smart Detection System***

The emergence of the Internet of Things (IoT), Artificial Intelligence (AI), cloud computing, and wireless communication has significantly expanded the capabilities of conventional sensing technologies. Instead of simply measuring physical

quantities, modern sensors are integrated with microcontrollers, communication networks, and intelligent algorithms to form smart detection systems. These systems continuously collect data, analyze information in real time, detect abnormal conditions, and generate alerts or automatic responses with minimal human intervention. As a result, they have become an essential component of Industry 4.0 and digital transformation initiatives across various sectors.

Smart detection systems have found widespread applications in industrial automation, healthcare, environmental monitoring, agriculture, transportation, and smart cities. In manufacturing industries, sensors monitor machine conditions and enable predictive maintenance, reducing equipment failures and production downtime. In healthcare, wearable sensors continuously measure physiological parameters such as heart rate, body temperature, and blood oxygen levels, supporting remote patient monitoring and early disease diagnosis. Similarly, environmental sensors help monitor air and water quality, while intelligent transportation systems use multiple sensors to improve vehicle safety, traffic management, and autonomous driving.

As sensing technologies continue to evolve, modern smart detection systems are becoming more accurate, reliable, energy-efficient, and capable of supporting autonomous operation. Their integration with AI and IoT enables faster decision-making and improved system performance, contributing to safer industries, sustainable resource management, and enhanced quality of life. This chapter discusses the fundamentals of sensors, different sensor types, smart detection system architectures, communication technologies, major applications, challenges, and future developments that are shaping the next generation of intelligent sensing systems.

**Fundamentals of Sensors**

Sensors are the basic elements of every smart detection system because they provide the information required to monitor and control physical processes. A sensor is an electronic device that detects a measurable quantity, known as the measurand, and converts it into an electrical signal that can be processed by electronic circuits or computer systems. Common measurands include temperature, pressure, humidity, light intensity, motion, sound, force, and gas concentration. The generated electrical signal may be in the form of voltage, current, resistance, capacitance, frequency, or digital data, depending on the sensor type and application.

The operation of a sensor generally involves three stages: sensing, signal conversion, and signal processing. Initially, the sensing element responds to changes in the surrounding environment. This response is then converted into an electrical signal, which is conditioned through amplification, filtering, or analog-to-digital conversion before being transmitted to a microcontroller or processor. The

processed information can then be displayed, stored, or used to control other devices automatically. This sequence enables continuous monitoring and supports intelligent decision-making in smart detection systems.





***Figure 2: Basic Working Principle of a Sensor***

The performance of a sensor is evaluated using characteristics such as accuracy, sensitivity, precision, resolution, response time, and reliability. Accuracy indicates how close the measured value is to the actual value, while sensitivity describes the sensor's ability to detect small changes in the measured parameter. A fast response time and high reliability are particularly important in applications such as industrial automation, medical diagnosis, and autonomous vehicles, where timely and accurate information is essential. Therefore, selecting an appropriate sensor based on application requirements is a crucial step in designing efficient and dependable smart detection systems.

**Types of Sensors**

Sensors are classified based on the physical quantity they measure, their operating principle, and the type of output they produce. Selecting the appropriate sensor depends on the application, required accuracy, operating environment, response time, and cost. Among the various classifications, grouping sensors according to the quantity they measure is the most common approach because it directly relates to their practical applications in smart detection systems.

Temperature sensors are among the most widely used sensing devices in industrial, commercial, and domestic applications. They measure the thermal condition of an object or environment and help maintain safe operating temperatures. Common temperature sensors include thermocouples, resistance temperature detectors (RTDs), and thermistors. These sensors are extensively used in manufacturing industries, battery management systems, medical equipment, heating, ventilation,

and air-conditioning (HVAC) systems. Accurate temperature monitoring improves system efficiency, prevents overheating, and enhances equipment reliability.




***Figure 3: Classification of Sensors***

Pressure sensors measure the force exerted by gases or liquids on a surface and are commonly employed in hydraulic systems, pneumatic equipment, process industries, and automotive applications. Humidity sensors, on the other hand, determine the amount of moisture present in the air and are widely used in weather stations, greenhouses, food storage facilities, and smart agriculture. Maintaining appropriate humidity levels improves product quality, environmental control, and agricultural productivity.

Motion and position sensors detect movement, orientation, or displacement of objects. Examples include passive infrared (PIR) sensors, accelerometers, gyroscopes, and proximity sensors. These devices play a significant role in security systems, robotics, smartphones, gaming devices, and autonomous vehicles. Similarly, optical sensors detect light intensity, colour, or object presence and are commonly found in industrial automation, barcode scanners, cameras, and medical instruments. Ultrasonic sensors use high-frequency sound waves to determine the distance between the sensor and an object, making them suitable for obstacle detection, parking assistance, liquid-level measurement, and robotic navigation.

Gas sensors are designed to identify the presence and concentration of gases such as carbon monoxide, methane, hydrogen, and carbon dioxide. They are essential in industrial safety systems, environmental monitoring, mining operations, and fire detection. Another rapidly growing category is biosensors, which combine biological sensing elements with electronic components to detect substances such as glucose, proteins, or pathogens. Biosensors are widely used in healthcare for disease diagnosis, patient monitoring, and wearable medical devices.

With the continuous advancement of microelectronics and nanotechnology, modern sensors are becoming smaller, more energy-efficient, and capable of integrating multiple sensing functions within a single device. These multi-functional sensors improve measurement accuracy, reduce installation complexity, and support the development of compact and intelligent smart detection systems across diverse engineering applications.

**Smart Detection Systems**

A smart detection system is an intelligent platform that combines sensors, embedded processors, communication technologies, and software to monitor physical environments and automatically respond to changing conditions. Unlike conventional sensing systems, which only collect and display data, smart detection systems can process information, identify abnormal situations, and support decision-making with minimal human intervention. This capability has made them an important part of modern automation, where continuous monitoring and rapid response are essential for improving efficiency, safety, and reliability.

A typical smart detection system consists of several interconnected components. Sensors first detect physical parameters such as temperature, pressure, humidity, vibration, or gas concentration and convert them into electrical signals. These signals are processed through signal conditioning circuits before being transmitted to a microcontroller or embedded processor. The processed data are then communicated through wired or wireless networks to cloud servers or local control units for storage and analysis. Finally, the analysed information is presented to users through dashboards, mobile applications, or automated control systems, allowing timely action whenever abnormal conditions are detected.





***Figure 4: Architecture of a Smart Detection System Showing Sensor, Processing Unit, Communication Network, Cloud Platform, and User Interface.***

One of the major advantages of smart detection systems is their ability to perform real-time monitoring. Continuous data collection enables operators to identify faults at an early stage, reducing equipment failures and maintenance costs. Many systems also employ intelligent algorithms to analyse historical and real-time sensor data, making it possible to predict failures before they occur. This approach, known as predictive maintenance, improves equipment availability and minimizes unexpected downtime in industrial environments.

Another important feature of smart detection systems is their scalability and flexibility. Multiple sensors can be connected through a common communication network to monitor large geographical areas or complex industrial processes. This allows centralized monitoring of various parameters from a single control centre, improving operational efficiency and simplifying system management. As communication technologies and embedded processors continue to evolve, smart detection systems are becoming more reliable, energy-efficient, and capable of supporting autonomous operation. These improvements have accelerated their adoption in healthcare, transportation, environmental monitoring, industrial automation, and smart city applications.

**IoT and Artificial Intelligence in Smart Detection Systems**

The integration of the Internet of Things (IoT) and Artificial Intelligence (AI) has significantly enhanced the capabilities of smart detection systems. IoT enables sensors and electronic devices to communicate with each other through the internet, allowing data to be collected, shared, and monitored from remote locations. Instead of operating as standalone devices, sensors become part of an interconnected network where information is continuously exchanged between sensing units, gateways, cloud platforms, and end users. This connectivity supports real-time monitoring, remote control, and faster decision-making in various applications.





***Figure 5: IoT-Based Smart Detection System***

In a typical IoT-based smart detection system, sensors collect information from the surrounding environment and transmit the data through communication technologies such as Wi-Fi, Bluetooth, ZigBee, LoRaWAN, or 5G networks. The collected data are stored either in local servers or cloud platforms, where they can be accessed and analysed at any time. Cloud computing provides sufficient storage and computational resources to manage large volumes of sensor data, making it possible to monitor multiple devices simultaneously from different geographical locations.

Artificial Intelligence further improves these systems by enabling automatic analysis of sensor data. Machine learning algorithms can identify hidden patterns, detect abnormal operating conditions, and predict equipment failures before they occur. For example, in industrial automation, AI analyses vibration and temperature data to detect early signs of machine wear, while in healthcare, it interprets physiological signals to assist in disease diagnosis and patient monitoring. These intelligent capabilities reduce human intervention, improve decision-making accuracy, and enhance the overall reliability of smart detection systems.

The combination of IoT and AI has expanded the application of smart detection systems across numerous sectors, including manufacturing, transportation, agriculture, environmental monitoring, and smart homes. As research continues to advance, emerging technologies such as edge computing, digital twins, and 5G/6G communication are expected to further improve data processing speed, reduce communication delays, and enable more secure and efficient intelligent sensing networks. Consequently, IoT and AI are becoming the key technologies driving the next generation of smart detection systems.

**Applications of Smart Detection Systems**

Smart detection systems have become an integral part of modern society because they provide continuous monitoring, improve operational efficiency, and support intelligent decision-making across various sectors. Their ability to collect and analyse real-time data has resulted in significant improvements in safety, productivity, and resource management. As a result, these systems are widely adopted in healthcare, industrial automation, agriculture, transportation, environmental monitoring, and smart city infrastructures.





***Figure 6: Major Applications of Smart Detection Systems in Healthcare, Industry, Agriculture, Transportation, Environmental Monitoring, and Smart Cities.***

In the healthcare sector, smart detection systems are extensively used for continuous patient monitoring and early disease diagnosis. Wearable sensors can measure physiological parameters such as heart rate, body temperature, blood pressure, blood oxygen saturation, and glucose levels. The collected data are transmitted to healthcare professionals through IoT platforms, enabling remote patient monitoring and timely medical intervention. This approach improves patient care while reducing hospital visits and healthcare costs.

In industrial automation, sensors continuously monitor machine parameters such as vibration, pressure, temperature, and motor current to evaluate equipment performance. Smart detection systems analyse these measurements to identify abnormal operating conditions and support predictive maintenance. This reduces unexpected equipment failures, minimizes production downtime, and improves the overall efficiency and reliability of manufacturing processes.

The agricultural sector has also benefited from smart sensing technologies. Soil moisture sensors, humidity sensors, weather monitoring devices, and nutrient sensors provide farmers with accurate information about field conditions. Based on these measurements, irrigation systems can automatically regulate water supply, reducing water wastage and improving crop productivity. Similarly, environmental sensors help monitor greenhouse conditions, ensuring optimal plant growth throughout the cultivation cycle.

Smart detection systems play an equally important role in transportation and environmental monitoring. Modern vehicles employ cameras, radar, ultrasonic

sensors, and LiDAR to support advanced driver assistance systems and autonomous driving. These sensors improve road safety by detecting obstacles, monitoring vehicle surroundings, and assisting drivers during navigation and parking. Environmental monitoring systems use gas, air quality, and water quality sensors to detect pollution, monitor climate conditions, and provide early warnings of hazardous situations such as gas leaks or forest fires. In smart cities, interconnected sensors manage traffic flow, street lighting, waste collection, and public infrastructure, contributing to sustainable urban development and improved quality of life. The growing adoption of these applications demonstrates the vital role of smart detection systems in building safer, more efficient, and environmentally sustainable communities.

**Challenges and Future Trends**

Although smart detection systems have transformed many engineering applications, several technical and practical challenges still limit their widespread implementation. One of the primary challenges is sensor accuracy and calibration. Over time, sensors may experience drift due to environmental conditions, ageing, or continuous operation, leading to inaccurate measurements. Regular calibration and maintenance are therefore essential to ensure reliable performance. Another challenge is power consumption, particularly in battery-operated and remote sensing applications where frequent battery replacement is difficult. Developing energy-efficient and self-powered sensors has become an important area of research.

As smart detection systems rely heavily on wireless communication and cloud computing, cybersecurity and data privacy have also become major concerns. Unauthorized access, data tampering, and cyberattacks can compromise the reliability of monitoring systems and expose sensitive information. In addition, communication delays, network failures, and electromagnetic interference may affect real-time data transmission, especially in critical applications such as healthcare, industrial automation, and autonomous transportation. Addressing these challenges requires secure communication protocols, reliable network infrastructure, and robust data protection mechanisms.

Despite these limitations, rapid technological advancements are shaping the future of smart detection systems. Artificial Intelligence and Machine Learning are making sensing systems more intelligent by enabling adaptive learning, anomaly detection, and predictive analysis. Edge computing is reducing communication delays by processing sensor data closer to the source instead of relying entirely on cloud servers. Researchers are also developing self-powered sensors that harvest energy from light, vibration, or heat, thereby extending operational life and reducing maintenance requirements.

Future smart detection systems are expected to integrate emerging technologies such as digital twins, nanotechnology, wearable and flexible sensors, and 5G/6G communication networks. These innovations will provide faster data processing, improved connectivity, higher measurement accuracy, and enhanced system reliability. As these technologies continue to mature, smart detection systems will play an even greater role in supporting intelligent automation, sustainable development, and the creation of safer and more connected environments.

**Conclusion**

Sensors and smart detection systems have become essential technologies for modern engineering, enabling accurate monitoring, intelligent decision-making, and automated control across a wide range of applications. By converting physical, chemical, and biological parameters into meaningful electrical signals, sensors provide the data required for efficient system operation. The integration of sensors with the Internet of Things (IoT), Artificial Intelligence (AI), cloud computing, and advanced communication technologies has transformed conventional sensing devices into intelligent systems capable of real-time monitoring, fault detection, and predictive analysis.

Throughout this chapter, the fundamental concepts of sensors, their classification, operating principles, smart detection architectures, IoT and AI integration, and major application areas have been discussed. The chapter has also highlighted the challenges associated with sensor calibration, energy consumption, cybersecurity, and communication reliability, while emphasizing emerging technologies such as edge computing, digital twins, self-powered sensors, and next-generation wireless networks. These advancements are expected to improve the accuracy, efficiency, and reliability of future smart detection systems. As intelligent sensing technologies continue to evolve, they will remain a key driving force behind Industry 4.0, smart cities, healthcare innovation, sustainable agriculture, and intelligent transportation, contributing significantly to the development of safer, smarter, and more sustainable societies.

***References***

1. Fraden, J. (2016). Handbook of Modern Sensors: Physics, Designs, and Applications (5th ed.). Springer.
2. Wilson, J. (2005). Sensor Technology Handbook. Elsevier.
3. Bentley, J. P. (2015). Principles of Measurement Systems (5th ed.). Pearson Education.
4. Dargie, W., & Poellabauer, C. (2010). Fundamentals of Wireless Sensor Networks: Theory and Practice. Wiley.
5. Gubbi, J., Buyya, R., Marusic, S., & Palaniswami, M. (2013). "Internet of Things (IoT): A Vision, Architectural Elements, and Future Directions." Future Generation Computer Systems, 29(7), 1645–1660.

6. Lee, I., & Lee, K. (2015). "The Internet of Things (IoT): Applications, Investments, and Challenges for Enterprises." Business Horizons, 58(4), 431–440.
7. Hancke, G. P., Silva, B., & Hancke, G. P. (2013). "The Role of Advanced Sensing in Smart Cities." Sensors, 13(1), 393–425.
8. Kumar, S., & Patel, R. (2022). "Artificial Intelligence-Based Smart Sensing Systems: A Review." Sensors, 22, 1–28.
9. Krishnamachari, B. (2005). Networking Wireless Sensors. Cambridge University Press.
10. Chong, C. Y., & Kumar, S. P. (2003). "Sensor Networks: Evolution, Opportunities, and Challenges." Proceedings of the IEEE, 91(8), 1247–1256.

**Physical Science: From Fundamental Principles to Modern Applications**
**ISBN: 978-81-69492-07-2| Year: 2026 | pp: 89 - 99**

# Thin Films and Coating Technologies: Fundamentals, Processing Methods, Characterization, Applications, Reliability, Performance, and Future Perspectives

**Prathamesh B. Dahivade**

**Balkrishna J Lokhande**

Lab of Electrochemical Studies, School of Physical Sciences, Punyashlok

Ahilyadevi Holkar Solapur University, Solapur, Maharashtra 413255, India.

**Email:** prathameshdahivade@gmail.com

Article DOI Link: https://zenodo.org/uploads/22047558

DOI: 10.5281/zenodo.22047558

**Abstract**

Thin films and coating technologies have become indispensable tools in modern surface and materials engineering, enabling precise control of surface properties without altering the bulk characteristics of a component. Thin films, with thicknesses typically ranging from a few nanometers to several micrometers, are engineered to impart tailored optical, electrical, magnetic, mechanical, or chemical functions. Coatings derived from these thin films are widely used to enhance wear resistance, corrosion protection, thermal stability, and biocompatibility across diverse sectors including microelectronics, energy, transportation, aerospace, and biomedical devices. This chapter presents a concise overview of the fundamental principles that govern thin film formation and coating performance, emphasizing the relationships among deposition processes, microstructure, interfaces, and functional behaviour. Common processing routes such as physical and chemical vapor deposition, solution-based methods, electrochemical techniques, and thermal spraying are described with reference to their operating mechanisms, controllable parameters, advantages, and limitations. The chapter also outlines key characterization techniques used to assess film thickness, composition, structure, adhesion, mechanical response, and durability. Particular attention is given to how process induced defects, residual stress, and interfacial phenomena impact reliability in demanding service environments.

Finally, representative application domains are highlighted, including semiconductor devices, hard and protective coatings, optical and decorative layers,

and functional films for sensors and energy systems. Recent trends such as nanostructured and multilayer architectures, smart and responsive coatings, and environmentally sustainable processing routes are briefly discussed. By integrating fundamental concepts with technological developments and practical examples, the chapter aims to provide researchers, students, and practitioners with a coherent understanding of thin films and coating technologies and their role in enabling next generation engineered surfaces.

***Keywords:*** Thin films; Coating technologies; Deposition methods; Surface engineering; Materials characterization

## Introduction

Thin films and coatings form the backbone of contemporary surface engineering, where the aim is to modify and optimize the behaviour of a surface while leaving the bulk material largely unchanged. This approach has gained importance as engineering applications increasingly demand combinations of properties such as high hardness with low friction, corrosion resistance with good electrical conductivity, or optical transparency with mechanical robustness that are difficult to achieve in a single monolithic material. Instead of redesigning entire components, surfaces are tailored using engineered films only a few nanometers to micrometers thick.

Historically, the concept of coatings is ancient: early civilizations used paints, varnishes, and simple metallic overlays for protection and aesthetics. However, the modern scientific understanding of thin films emerged alongside the development of vacuum technology and quantum physics in the twentieth century. The ability to deposit controlled layers of metal or dielectric materials revolutionized microelectronics and optics, enabling devices such as integrated circuits, magnetic recording media, anti-reflective coatings, and thin film solar cells. Over time, similar principles extended to mechanical and chemical applications, yielding hard coatings for cutting tools, barrier layers for aggressive environments, and biocompatible films for medical implants. Today, thin films and coatings span a vast range of materials systems including metals, ceramics, polymers, composites, and hybrids and are processed using sophisticated methods that allow fine tailoring of thickness, structure, and interfaces. At the same time, the field faces new challenges: industries demand more sustainable deposition routes, multifunctional and smart surfaces, and reliability under extreme conditions. This chapter introduces the fundamental concepts, major processing routes, characterization strategies, and key application areas, providing a foundation for deeper study and research.

## Fundamentals of Thin Films and Coatings

### 1. Definitions and Thickness Regimes

A thin film is generally defined as a layer of material whose thickness lies between a few nanometers and several micrometers, deposited on a substrate with much larger dimensions. When this layer is used primarily to modify surface properties, it is commonly referred to as a coating. The distinction between “thin film” and “coating” is sometimes contextual: in microelectronics, films of a few hundred nanometers are simply called thin films, whereas in mechanical engineering, coatings of tens of micrometers are accepted as “thin” relative to the component dimensions. Thickness strongly influences behaviour. At nanometre scales, surfaces and interfaces dominate, and phenomena such as quantum confinement, size dependent mechanical response, and enhanced diffusion become important. At micrometers scales, films can sometimes be treated using continuum mechanics, but defects, interfaces, and residual stresses still play a crucial role. Designers must therefore consider thickness not merely as a geometric parameter but as a key variable governing performance.

## 2. Substrate–Film Interactions and Adhesion

The substrate is more than just a mechanical support; it interacts with the film chemically, mechanically, and thermally. During deposition, atoms or molecules arriving at the surface can react with the substrate, diffuse into it, or form interfacial compounds. These interactions influence adhesion, residual stress, and long-term stability. Adhesion is particularly critical for coating technologies. Poor adhesion can lead to delamination, blistering, or rapid wear, rendering the coating ineffective. Adhesion mechanisms include mechanical interlocking, chemical bonding, diffusion bonding, and van der Waals interactions. Surface preparation via cleaning, roughening, pre coating layers, or activation treatments is a major step in ensuring reliable bonding. In many industrial systems, thin interlayers are introduced between the substrate and the functional coating to mitigate thermal expansion mismatch or improve chemical compatibility.

## 3. Microstructure and Structure–Property Relationships

Microstructure refers to the arrangement of grains, phases, defects, and interfaces within the film. In thin films, microstructure can vary dramatically from that of bulk materials due to different growth kinetics and constraints. Important features include grain size and morphology, crystallographic texture, porosity, layer stacking, and defect distributions. Structure–property relationships are central to the design of thin films. For example, small grain sizes often yield higher hardness (Hall–Petch effect), while specific textures may enhance electrical conductivity or magnetic anisotropy. Porosity influences diffusion and barrier performance, while layered structures can provide crack deflection and improved toughness. By controlling deposition parameters such as substrate temperature, deposition rate, energy of incoming species, and ambient pressure engineers can tune microstructure to achieve target properties.

**4. Residual Stress and Defects**

Residual stresses are locked in stresses that exist within the film after deposition, even in the absence of external loads. They arise from several sources: thermal expansion mismatch between film and substrate, intrinsic stresses caused by film growth (e.g., island coalescence, incorporation of defects), and phase transformations. Residual stress can be tensile or compressive, and its magnitude strongly affects adhesion, cracking, and fatigue behaviour. Defects such as voids, dislocations, microcracks, and inclusions are inevitable in real films. While some defects can be tolerated, excessive defect densities often degrade mechanical strength, corrosion resistance, and electrical performance. In many high reliability applications, controlling stress and defects is as important as achieving the desired composition and thickness.

**Deposition Techniques for Thin Films and Coatings**

Thin films and coatings can be produced by a wide range of deposition techniques, broadly classified into physical, chemical, electrochemical, and thermal processes. Each method offers distinct advantages and limitations in terms of film quality, rate, cost, and material compatibility.

**1. Physical Vapor Deposition (PVD)**

Physical vapor deposition comprises a family of vacuum based processes in which material is physically vaporized from a solid or liquid source and transported through a low-pressure environment to condense on a substrate. Two widely used PVD methods are thermal evaporation and sputtering. In thermal evaporation, the source material is heated resistively, by electron beam, or by other means until it evaporates. The vapor then travels to the substrate, condensing to form a film. Evaporation is relatively simple and can yield high purity films, but control over microstructure and composition may be limited, particularly for alloys. Sputtering involves the bombardment of a target material by energetic ions (typically from a plasma), ejecting atoms that subsequently deposit on the substrate. Magnetron sputtering and radio frequency sputtering are common variants. Sputtering offers better control over composition, allows deposition of complex alloys and ceramics, and can produce dense films with good adhesion. However, equipment costs and process complexity are higher than for simple evaporation. PVD coatings are widely used in microelectronics (metal and dielectric films), optics (reflective and anti-reflective coatings), and tribology (hard nitride or carbide coatings on cutting tools and wear components).

**2. Chemical Vapor Deposition (CVD)**

Chemical vapor deposition relies on chemical reactions of gaseous precursors in the vicinity of, or on, the heated substrate surface. The reaction products form a solid film, while volatile by products are removed by gas flow. CVD offers excellent

conformality over complex shapes and can produce films with high purity and controlled composition. Thermal CVD uses elevated temperatures to drive reactions, making it suitable for materials such as silicon, silicon nitride, and various carbides and oxides. Plasma enhanced CVD introduces a plasma to activate reactions at lower substrate temperatures, expanding the range of compatible substrates. Variants such as metal organic CVD and atomic layer deposition (ALD) allow precise control of film thickness at the atomic scale and are widely used in advanced semiconductor manufacturing. CVD coatings find applications in semiconductor devices, diffusion barriers, protective layers against corrosion and wear, and functional surfaces in sensors and catalytic systems.

## 3. Solution Based Deposition: Sol Gel and Related Methods

Solution based methods, particularly sol gel processing, enable the formation of oxide and hybrid films from liquid precursors. In the sol gel route, metal alkoxides or salts are hydrolyzed and condensed to form a colloidal solution (sol), which is then deposited onto a substrate by dip coating, spin coating, or spray coating. Subsequent drying and heat treatment convert the sol into a solid gel and then into a dense or porous film. Sol gel techniques are attractive due to their low equipment cost, scalability, and ability to produce uniform coatings over large areas. They are used for optical coatings, corrosion resistant layers, catalytic films, and functional coatings for sensors and energy devices. However, controlling cracking, shrinkage, and residual porosity during drying and firing requires careful optimization of composition and processing parameters. Other solution-based methods include electrophoretic deposition, where charged particles are driven onto a substrate under an electric field, and simple paint or lacquer like coatings for less demanding applications.

## 4. Electrochemical Deposition

Electroplating and related electrochemical techniques deposit metallic or alloy films from electrolyte solutions under an applied current or potential. Electroplating offers high deposition rates, good thickness control, and the ability to coat complex geometries, making it indispensable for decorative surfaces, corrosion protection, and electronic interconnects.

In electroplating, the substrate acts as a cathode, and metal ions in the solution are reduced and deposited onto it. Additives and bath conditions control grain size, texture, stress, and brightness of the deposit. Variants such as electroless plating rely on autocatalytic reactions rather than external current, enabling uniform coverage even on nonconductive substrates once appropriate seed layers are applied. Electrochemical deposition is particularly important for copper and nickel coatings, hard chromium plating (though environmental concerns are driving alternatives), and multilayer systems for magnetic recording and microelectronics.

### 5. Thermal Spraying and Thick Coatings

Thermal spraying encompasses a group of processes in which feedstock material powder, wire, or rod is melted or softened in a high temperature jet and propelled onto a substrate, where it solidifies to form a coating. Common variants include flame spraying, plasma spraying, and high velocity oxy fuel (HVOF) spraying. Unlike most thin film techniques, thermal spraying often produces relatively thick coatings (tens to hundreds of micrometers) with lamellar microstructures. These coatings are used for wear protection, thermal barriers in gas turbine engines, corrosion resistance in aggressive environments, and restoration of worn components. Although the microstructure is coarser than in PVD or CVD films, thermal spray coatings can be tailored through process parameters and post treatments.

## Characterization of Thin Films and Coatings

To design reliable coatings, it is essential to characterize their thickness, structure, composition, interfaces, mechanical properties, and durability. A wide array of techniques is available, each providing complementary information.

### 1. Thickness and Morphology Measurement

Film thickness can be measured by mechanical, optical, and microscopic methods. Stylus profilometry uses a sharp tip to scan a step edge between coated and uncoated regions, giving thickness from the height difference. Optical methods such as ellipsometry and interferometry exploit changes in reflected light intensity and phase to infer thickness, particularly for transparent films. Cross section imaging using optical microscopy, scanning electron microscopy (SEM), or focused ion beam (FIB) techniques provides direct visualization of thickness and layer stacking, as well as insights into porosity and defects. Surface morphology can be assessed by SEM or atomic force microscopy (AFM), revealing grain structures, roughness, and growth features important for adhesion and functional performance.

### 2. Structural and Microstructural Analysis

Crystalline structure and texture are commonly studied using X ray diffraction (XRD). Peak positions identify phases, while peak intensities and widths provide information on texture and grain size. Transmission electron microscopy (TEM) offers high resolution imaging of grains, interfaces, and defects, although sample preparation can be challenging for very thin or sensitive films. Microstructural features such as grain boundaries, pores, and microcracks are visible in SEM images, particularly when combined with fracture or cross section views. AFM can probe surface topography at nanometre resolution, making it useful for thin films used in microelectronics and optics.

### 3. Composition and Chemical State

Chemical composition can be determined by energy dispersive X ray spectroscopy (EDS) attached to SEM or TEM, by wavelength dispersive spectroscopy (WDS), or by surface sensitive techniques such as X ray photoelectron spectroscopy (XPS) and Auger electron spectroscopy (AES). XPS additionally provides information on oxidation states and chemical bonding environments. Secondary ion mass spectrometry (SIMS) allows depth profiling of elemental or molecular species, revealing composition gradients, diffusion zones, and impurity distributions. Such data are crucial for understanding barrier performance and interfacial reactions in multilayer systems.

### 4. Mechanical and Tribological Testing

Mechanical properties, especially hardness and elastic modulus, are often measured by instrumented indentation (nanoindentation for thin films). By analyzing load displacement curves, hardness and modulus can be extracted with depth resolution and correlated to microstructure. Adhesion can be evaluated by scratch testing, where a stylus is dragged across the coated surface under increasing load until failure occurs, or by pull off and bend tests which measure the force required to delaminate or crack the coating. Tribological tests, such as pin on disk wear experiments, assess friction coefficient, wear rate, and failure mechanisms under realistic contact conditions. Residual stress can be estimated by curvature measurements (e.g., wafer bow) combined with elastic theory or by XRD methods that detect strain in the film lattice. Understanding stress helps designers prevent cracking and delamination during service.

### 5. Durability, Corrosion, and Environmental Resistance

For coatings used in aggressive environments, corrosion and environmental stability must be evaluated. Electrochemical tests such as potentiodynamic polarization and electrochemical impedance spectroscopy quantify corrosion rates and protective performance in specific media. Salt spray testing and immersion studies provide practical assessments of long-term behaviour. Thermal cycling, humidity exposure, and UV aging experiments reveal susceptibility to cracking, embrittlement, or degradation under operating conditions. For functional films, electrical, optical, or catalytic performance is monitored before and after environmental tests to quantify reliability.

## Applications of Thin Films and Coatings

Thin films and coatings are applied across many sectors, often enabling functionalities that would otherwise be impossible or uneconomical.

### 1. Microelectronics and Optoelectronics

In microelectronics, thin films are central to device fabrication. Conductive films such as aluminium and copper form interconnects; dielectric films including silicon

dioxide and silicon nitride provide insulation and passivation; and semiconductor films such as silicon, germanium, and compound semiconductors (e.g., GaAs, GaN) constitute active device regions. Precise control of thickness, composition, and interfaces is critical for transistor performance and reliability. Optoelectronic devices rely on thin films for light emission, detection, and modulation. Examples include thin film transistors in displays, organic light emitting diodes (OLEDs), and various photodetectors. Optical coatings such as anti-reflective layers, filters, and mirrors are fabricated by PVD, CVD, and sol gel methods to manage reflection, transmission, and absorption.

**2. Protective and Tribological Coatings**

Mechanical components exposed to high loads, sliding contact, or corrosive environments benefit from protective and tribological coatings. Hard nitride coatings like TiN, CrN, and AlTiN deposited by PVD improve tool life and wear resistance in machining operations. Diamond like carbon (DLC) coatings reduce friction and wear in automotive parts and bearings. Corrosion resistant coatings based on nickel, chromium, and various alloys extend the life of steel structures, pipelines, and marine components. In power plants and turbines, thermal barrier coatings often ceramic layers applied by thermal spraying protect metal substrates from high temperatures and aggressive gases, improving efficiency and durability.

**3. Optical, Decorative, and Architectural Coatings**

Thin films are widely used to modify the optical appearance or functionality of surfaces. Decorative coatings, including coloured metallic finishes and reflective layers, are applied to consumer goods, automotive parts, and architectural elements. Architectural glass often features multi-layer coatings that combine thermal isolation, solar control, and aesthetic properties. Anti-reflective coatings minimize glare on lenses and screens, while interference coatings provide specific colour effects or spectral filtering. These systems rely on carefully designed layer stacks with controlled thickness and refractive indices.

**4. Energy and Environmental Applications**

Energy technologies increasingly depend on thin films and coatings for efficiency and durability. In photovoltaic devices, absorber and buffer layers are thin films of semiconductors and transparent conductors. In fuel cells and batteries, thin coatings act as electrodes, electrolytes, protective barriers, or catalytic layers. Thermal barrier and corrosion resistant coatings enhance the performance of gas turbines and boilers, contributing to higher operating temperatures and better fuel utilization. Environmental applications include photocatalytic coatings for self-cleaning surfaces and anti-fouling films to reduce bio growth on marine structures.

### 5. Biomedical and Functional Surfaces

Biomedical devices interact directly with biological environments, making surface properties crucial. Biocompatible and bioactive coatings are used on implants to improve integration with tissue, reduce rejection, and control corrosion. For example, titanium implants may be coated with hydroxyapatite or other calcium phosphate layers to promote bone growth. Drug eluting coatings on stents and other devices allow controlled release of therapeutic agents over time. In biosensors, thin films of conductive polymers, enzymes, or antibodies provide the active recognition surfaces. These applications require careful control of chemistry, structure, and degradation behaviour.

## Reliability, Performance, and Future Perspectives

### 1. Reliability Challenges

Despite their advantages, thin films and coatings can fail through various mechanisms: cracking due to excessive residual stress or thermal cycling, delamination from poor adhesion or interface degradation, wear or erosion in mechanical contact, and chemical attack in corrosive environments. These failures may be accelerated by microstructural defects, compositional inhomogeneity, or unforeseen service conditions. Reliability studies therefore focus on understanding how deposition parameters, material choices, and design strategies influence failure modes. Multilayer architectures, graded compositions, and compliant interlayers can mitigate stress concentrations and improve toughness. Predictive modeling and accelerated testing help identify weak points before deployment.

### 2. Emerging Trends: Nanostructured and Smart Coatings

Recent research emphasizes nanostructured coatings, where grain sizes, layer thicknesses, or feature dimensions are at the nanometre scale. Such coatings can exhibit enhanced hardness, unique optical responses, or tailored transport properties. Multilayer systems with alternating hard and soft layers can combine toughness and wear resistance, while graded coatings reduce abrupt property changes across interfaces. Smart and responsive coatings represent another frontier. These systems change their properties in response to stimuli such as temperature, pH, electric fields, or mechanical stress. Examples include self-healing coatings that repair microcracks, thermochromic films that change colour with temperature, and sensor coatings that provide real time monitoring of strain, corrosion, or contamination.

### 3. Sustainability and Green Processing

Traditional coating methods can involve hazardous chemicals, high energy consumption, or waste generation. As environmental regulations tighten and industries seek greener practices, sustainable coating technologies are gaining attention. This includes water-based chemistries, low temperature processes,

renewable precursors, and improved recycling of solvents and gases. Optimization of process efficiency through better plasma sources, more efficient precursor utilization, and advanced control systems reduces energy use and emissions. Life cycle analysis helps quantify environmental impacts and guide the selection of materials and methods.

## 4. Future Outlook

Looking ahead, thin films and coatings will continue to expand into new domains such as flexible electronics, wearable devices, micro and nano robotics, and advanced biomedical systems. Integration of coating technologies with digital design, machine learning, and in situ monitoring will enable more precise and adaptive control over film properties. As performance requirements rise and sustainability becomes central, the interplay of materials science, process engineering, and environmental considerations will shape the evolution of thin film and coating technologies.

## Conclusion

Thin films and coatings provide a versatile means of tailoring surface properties to meet demanding functional requirements in a wide range of applications. Their effectiveness arises from an intricate interplay of fundamental principles: film growth and microstructure, substrate–film interactions, residual stress and defects, and the influence of processing parameters on resulting properties. A variety of deposition techniques including PVD, CVD, solution-based methods, electrochemical deposition, and thermal spraying offer different routes to achieve specific material systems and performance goals. Comprehensive characterization, spanning thickness measurement, structural and compositional analysis, mechanical and tribological testing, and durability assessment, is essential to ensure reliability. Applications in microelectronics, optics, tribology, energy, environment, and biomedicine demonstrate the breadth of this field, while emerging trends in nanostructured, smart, and sustainable coatings point toward exciting future developments. For researchers and engineers, understanding the foundations and practical aspects of thin films and coating technologies is key to designing the next generation of high performance, reliable, and environmentally responsible surfaces.

## *References*

1. Arun, Ajith P., Niranjana Sreenivasan, Jagadish H. Patil, Raviraj Kusanur, Hemanth L. Ramachandraiah, and Mahesh Ramakrishna. "Thin films for next generation technologies: a comprehensive review of fundamentals, growth, deposition strategies, applications, and emerging frontiers." Processes 13, no. 12 (2025): 3846.

2. Sathish, M., N. Radhika, and Bassiouny Saleh. "Current status, challenges, and future prospects of thin film coating techniques and coating structures." Journal of Bio-and Tribo-Corrosion 9, no. 2 (2023): 35.
3. Kern, Werner, and Klaus K. Schuegraf. "Deposition technologies and applications: Introduction and overview." In Handbook of thin film deposition processes and techniques, pp. 11-43. William Andrew Publishing, 2001.
4. Sakthinathan, Subramanian, Ganesh Abinaya Meenakshi, Sivaramakrishnan Vinothini, Chung-Lun Yu, Ching-Lung Chen, Te-Wei Chiu, and Naratip Vittayakorn. "A review of thin-film growth, properties, applications, and future prospects." Processes 13, no. 2 (2025): 587.
5. Toma, Fatema Tuz Zohora, Md Sharifur Rahman, Kazi Md Amjad Hussain, and Syed Ahmed. "Thin film deposition techniques: A comprehensive review." J Mod Nanotechnol (2024).
6. Hossain, Mohammad Istiaque, and Said Mansour. "A critical overview of thin films coating technologies for energy applications." Cogent engineering 10, no. 1 (2023): 2179467.
7. Dahivade, P.B., Pawar, S.N., Mhetre, M.T. et al. Optimization of cadmium-precursors in hydrothermal synthesis of CdO for electrochemical energy Storage. Appl. Phys. A 132, 127 (2026). https://doi.org/10.1007/s00339-026-09317-4.
8. Pawar, S.N., Randive, S.G., Dahivade, P.B. et al. Exploring the dual functionality of copper oxide for enhanced supercapacitor performance and photocatalysis application. J Mater Sci: Mater Electron 35, 1682 (2024). https://doi.org/10.1007/s10854-024-13378-7.

## ABOUT THE EDITORS



### Ms. Rutuja Ashok Bhosale

She is Assistant Professor at Department of Physics, Eknath Sitaram Divekar Mahavidyalaya, Varvand, Tal-Daund, Dist- Pune. She has completed her M.Sc. in Physics from Dada Patil College, Karjat, District Ahilyanagar, affiliated with Savitribai Phule Pune University, Pune. She has also qualified the State Eligibility Test (SET) conducted by Savitribai Phule Pune University in 2025, Ms. Bhosale has developed strong communication, interpersonal, and interactive skills. She is a confident, honest, and hardworking individual with the ability to apply theoretical knowledge in practical educational environments. Her career objective reflects her desire to work in a dynamic environment where she can contribute her knowledge, achieve professional goals, and continuously enhance her skills. Apart from academics, she has interests in reading books, travelling, dancing, and cooking. She is proficient in Marathi, Hindi, and English languages, enabling effective communication in diverse academic and social environments.



### Ms. Monika Shyamkumarji Dixit

She is an Assistant Professor in the Department of Physics at Jagadamba Mahavidyalaya, Achalpur. She has over 3 years of teaching experience and around 4 years of research experience in the fields of dye-sensitized solar cells, polymers, and nanomaterials. Her teaching expertise includes Quantum Mechanics, Thermodynamics, Statistical Mechanics, Classical Physics, and Solid State Physics.She has actively contributed to academics through a published textbook for B.Sc. students and several research publications in reputed journals. She also holds a patent in the field of solid-state lighting. Ms. Dixit is a lifetime member of professional bodies such as NUTA and the Indian Association of Physics Teachers.In addition to teaching and research, she plays an active role in college administration through various committees, including cultural, soft skills development, and women's empowerment. She has participated in multiple faculty development programs, workshops, and orientation courses to enhance her academic and professional skills.



### Ms. Tahenishjahan Kalim Mujawar

She is an Assistant Professor in the Department of Physics at New Arts, Commerce and Science college, Parner, Dist.- Ahilyanagar. She has completed her M.Sc. in Physics from Savitribai Phule Pune University, Pune in 2017 with First Class and B.Sc. in Physics from the same university in 2015 with Distinction. She has also successfully completed her HSC and SSC education under Pune Board with commendable academic performance. She possesses knowledge of technical software including C++ and TEENA software and has actively worked on research-oriented academic projects related to material science, including the growth and characterization of Triglycine Sulphate crystal, Potassium Diphosphate (KDP), Nickel Ferrite ($NiFe_2O_4$), and ZnS thin films using the Chemical Bath Deposition (CBD) method.She has two years of teaching experience at the postgraduate level at Vidya Pratisthan Arts, Commerce, Science College, Baramati, District Pune. She has also participated in research activities through AVISHKAR Zonal Level Research Project Competition and attended a state-level workshop on Fundamentals of Material Science with hands-on training.With a passion for teaching, research, and continuous learning, Ms. Tahenishjahan aims to contribute effectively in the field of Physics through her academic knowledge, research skills, and teaching experience.



### Dr. Ponmani Swaminathan

She is currently serving as an Associate Professor and Head of the Department Petroleum Engineering at the AMET University, Chennai, India. She obtained her PhD (2015) in Ocean Engineering from IIT Madras, India, B. Tech. (2007) in Chemical Engineering from Anna University, Chennai, India and M. Tech. (2009) in Petroleum Refining and Petrochemicals from Anna University, Chennai. She worked as a lecturer in Oil and Gas Engineering at All Nations University in Ghana, West Africa. She has successfully completed a DST-SERB funded Project under Early Career Research scheme with more than 15 years of teaching experience, she has published several papers in reputed journals and has presented her at various international conferences. She has holds 03 patents in the fileds of drilling fluids and enhanced oil recovery. She also serves as the SPE Faculty Advisor for the Department of Petroleum Engineering at AMET University. She is one the reviewers for SPE journals, Industrial and Engineering Chemistry Research. She has also served as a judges for WNA paper context conducted by the university of California students' Chapter. Her area of specialisation includes drilling fluids, Enhanced oil recovery, Desalination and Marine Pollutions.


Nature Light Publications

309 West 11, Manjari VSI Road, Manjari Bk.,
Haveli, Pune- 412 307.
Website: www.naturelightpublications.com
Email: naturelightpublications@gmail.com
Contact No: +919822489040 / 9922489040

Nature - 121

ISBN: 978-81-69492-07-2

Price- 750/-